

## IFBR 11P37T1/L-9

Inductive proximity switch - hygiene

Article number: 11014609

### Overview

- 4 mm
- PNP break function (NC)
- cable PVC, 2 m
- -40 ... 80 °C
- IP 68/69K & proTect+



Picture similar



### Technical data

#### General data

Mounting type	Flush
Special type	Hygienic design
Nominal sensing distance S <sub>n</sub>	4 mm
Hysteresis	2 ... 15 % of S <sub>r</sub>
Output indicator	LED red
Approvals/certificates	Ecolab Adapted from EHEDG REGULATION (EC) 1935/2004 REGULATION (EC) 2023/2006 REGULATION (EU) 1282/2011 FDA 21 CFR § 175.300 FDA 21 CFR § 177.2600 FCN 742

Ecolab  
Adapted from EHEDG  
REGULATION (EC) 1935/2004  
REGULATION (EC) 2023/2006  
REGULATION (EU) 1282/2011  
FDA 21 CFR § 175.300  
FDA 21 CFR § 177.2600  
FCN 742

#### Electrical data

Switching frequency	< 1 kHz
Voltage supply range +V <sub>s</sub>	6 ... 30 VDC
Current consumption max. (no load)	10 mA

#### Electrical data

Output circuit	PNP break function (NC)
Voltage drop V <sub>d</sub>	< 2 VDC
Output current	< 200 mA
Output current (at cleaning temperature)	< 100 mA
Short circuit protection	Yes
Reverse polarity protection	Yes

#### Mechanical data

Type	Cylindrical smooth
Material (sensing face)	LCP
Housing material	Stainless steel 1.4404 (V4A); LSR
Dimension	11 mm
Housing length	54 mm
Connection types	Cable PVC, 2 m

#### Ambient conditions

Operating temperature	-40 ... +80 °C
Cleaning temperature	80 ... +100 °C (30 min/day)
Protection class	IP 68/69K & proTect+

### Remarks


- Sensor compliant with various food regulations (see approvals)
- LSR = Liquid Silicon Rubber

# IFBR 11P37T1/L-9

Inductive proximity switch - hygiene

Article number: 11014609

## Dimension drawing



## Connection diagram

