



Frame	
Maximum rated current	
Number of poles	
Breaker type	
UL489/CSA C22.2	
Interrupting capacity	120/240V
(kA rms)	240V ac
AC(50/60HZ)	480V ac
UL, CSA	600V ac
	600Y/347V ac
UL489 DC	
Interrupting capacity	250V dc-2P
(kA) DC	500V dc-3P
UL, CSA	600V dc-3P
IEC 60947-2	
Ultimate breaking capacity,	220/240V
(kA rms) AC	380/415V
50/60Hz, Icu	480/500V
Service breaking capacity, Ics (%Icu)	
Insulation voltage, Ui	
Impulse withstand voltage, Uimp	
Rated short-time withstand current (Icw)	
Utilization category	
TRIP UNITS	Amperes
F : Fixed	ATU
A : Adjustable	FMU
T : Thermal	FTU
M : Magnetic	ETS
E : Electronics	ETM
	OCR
MCP	Amperes
	MCP
MCS	Amperes
	MCS
Unit mounted	
Mechanical lugs	
Busbar connectors	
Control wire terminal kit	
Terminal shields	
Interphase barriers	
Shunt trip	
Undervoltage trip	
Auxiliary switch	
Alarm switch	
Fault alarm switch	
Flange cable handle	
Flange variable-depth mechanism	
Directly-mounted rotary operating handle	
NEMA-Door-mounted operating mechanisms	
IEC-Door-mounted operating mechanisms	
Mechanical interlocks	
Handle padlock attachment	
Motor operator	
Weight(approximate)	2-Pole
lbs.(kg)	3-Pole
Dimensions	W x H x D
Inches(mm)	2-Pole
	3-Pole

UTS800		
800A		
3		
N	H	L
UTS800		
-	-	-
65	100	150
35	65	100
18	35	50
-	-	-
UTS800		
-	-	-
UTS800		
65	100	150
35	65	100
18	35	50
100%		
1000 Vac		
8 kVac		
18kA	-	-
B	A	A
400/600/630/800A		
-	-	-
-	-	-
-	-	-
-	-	-
-	-	-
800A		
•		
800A		
•		
800A		
•		
Unit mounted		
Mechanical lugs		
Busbar connectors		
Control wire terminal kit		
Terminal shields		
Interphase barriers		
Shunt trip		
Undervoltage trip		
Auxiliary switch		
Alarm switch		
Fault alarm switch		
Flange cable handle		
Flange variable-depth mechanism		
Directly-mounted rotary operating handle		
NEMA-Door-mounted operating mechanisms		
IEC-Door-mounted operating mechanisms		
Mechanical interlocks		
Handle padlock attachment		
Motor operator		
Weight(approximate)		
lbs.(kg)		
31.35(14.22)		
W	H	D
-	-	-
8.27(210)	12.88(327.2)	6(152.5)

UTS1200			
1200A			
3			
N	H	P	L
UTS1200			
-	-	-	-
50	100	65	150
35	65	50	100
18	25	50	35
-	-	-	-
UTS1200			
-	-	-	-
UTS1200			
50	100	65	150
35	65	50	100
25	35	50	50
100%			
1000 Vac			
8 kVac			
25kA	-	25kA	-
B	A	B	A
800/1000/1200A			
-	-	-	-
-	-	-	-
-	-	-	-
-	-	-	-
1200A			
•			
1200A			
•			
Unit mounted			
Mechanical lugs			
Busbar connectors			
Control wire terminal kit			
Terminal shields			
Interphase barriers			
Shunt trip			
Undervoltage trip			
Auxiliary switch			
Alarm switch			
Fault alarm switch			
Flange cable handle			
Flange variable-depth mechanism			
Directly-mounted rotary operating handle			
NEMA-Door-mounted operating mechanisms			
IEC-Door-mounted operating mechanisms			
Mechanical interlocks			
Handle padlock attachment			
Motor operator			
Weight(approximate)			
lbs.(kg)			
40.28(18.27)			
W	H	D	
-	-	-	
8.27(210)	16.26(413)	6(152.5)	