

Mechanical latch unit



Applying contactors	Type	Rebound coil voltage	
		Nominal volt.	Rated volt.
GM-9 to 40 type (9 to 40A frame)	AL-9	AC100V	100~127V 50/60Hz
		AC200V	200~240V 50/60Hz
GM-50 to 85 type (50 to 85A frame)	AL-50	AC300V	260~350V 50/60Hz
		AC400V	380~440V 50/60Hz
		AC500V	460~550V 50/60Hz
		DC12V	DC12V
		DC24V	DC24V
		DC48V	DC48V
		DC100V	DC100~110V
		DC125V	DC120~125V
		DC200V	DC200~220V



Note)

GMC-100, 125 type (100, 125A frame)	AL-100		
GMC-150 type (150A frame)	AL-150	AC100V	100~127V 50/60Hz
GMC-180, 220 type (180, 220A frame)	AL-220	AC200V	200~240V 50/60Hz
GMC-300, 400 type (300, 400A frame)	AL-400		

Note) As connection of latch unit it requires experts' skill, it is not separately provided from magnetic contactor.

Terminal cover unit for Contactors



Applying contactors	Type		Remarks
	for 3 Pole	for 4 Pole	
GMC-100, 125 type (100, 125A frame)	AP100	AP220/4	2 pcs included
GMC-150 type (150A frame)	AP150		
GMC-180, 220 type (180, 220A frame)	AP220		
GMC-300, 400 type (300, 400A frame)	AP400	AP400/4	
GMC-600, 800 type (600, 800A frame)	AP800	AP800/4	

Terminal cover unit for Thermal overload relays



Applying relays	Type	Remarks
GTK, GTH-125	APT125	
GTK, GTH-150	APT150	
GTK, GTH-220	APT220	
GTK, GTH-400	APT400	
GTK, GTH-600	APT600	