

## Terminal Lug Connection

Unit: in [mm]




**M1** 1-Hole  
167 °F (75 °C)  
Cu wire only  
14-3/0 AWG  
2.5~95 mm<sup>2</sup>  
89 in-lb (10 N.m)



**M2** 1-Hole  
167 °F (75 °C)  
Cu wire only  
8 AWG - 350 kcmil  
10~185 mm<sup>2</sup>  
230 in-lb (23 N.m)



**M3** 2-Holes  
167 °F (75 °C)  
Cu wire only  
3 AWG - 250 kcmil  
35~120 mm<sup>2</sup>  
310 in-lb (35 N.m)



**M1** 3-Holes  
167 °F (75 °C)  
Cu wire only  
14-10 AWG  
2.5~6 mm<sup>2</sup>  
44.5 in-lb (5 N.m)

8-3 AWG  
10~35 mm<sup>2</sup>  
89 in-lb (10 N.m)



**M3** 1-Hole  
167 °F (75 °C)  
Cu wire only  
3/0 AWG - 500 kcmil  
95~240 mm<sup>2</sup>  
310 in-lb (35 N.m)



**M4** 2-Holes  
167 °F (75 °C)  
Cu wire only  
(2) 3/0 AWG - 400 kcmil  
(2) 95~185 mm<sup>2</sup>  
310 in-lb (35 N.m)