



A-K4P-M8-R-G-5M-GY-1-X-X-4

- Pre-wired cable
- 4-pole

Data

Ordering data

Product type description	A-K4P-M8-R-G-5M-GY-1-X-X-4
Article number (order number)	103011342
EAN (European Article Number)	4030661476957
eCl@ss number, version 12.0	27-06-03-11
eCl@ss number, version 11.0	27-06-03-11
eCl@ss number, version 9.0	27-06-03-11
ETIM number, version 7.0	EC001855
ETIM number, version 6.0	EC001855

General data

Standards	EN IEC 61076-2-104
Gross weight	167 g

General data - Features

Number of poles	4
Number of cable wires	4

Mechanical data - Connection technique

Length of cable	5 m
Wire cross-section	0.25 mm ²
Cable diameter	4.7 mm
Bending radius (fixed)	5 x Ø-cable
Bending radius (repeated)	10 x Ø-cable
Colour of the Cable mantle	Grey
Material of the Cable mantle	PVC

Mechanical data - connector side A

Connector typ	Female connector, M8
Design	straight
Connector latching	Latching interlocking
Material of the gland	Plastic, TPU
Material of the handle	Plastic, TPU
Colour of the handle	Grey

Ambient conditions

Degree of protection	IP65 IP67 IP69
Ambient temperature (Connector)	-30 ... +90 °C
Ambient temperature (fixed)	-25 ... +80 °C
Ambient temperature (moved)	+0 ... +80 °C

Electrical data

Thermal test current	4 A
Rated operating voltage	60 VAC

Rated operating voltage	60 VDC
Operating current	4,000 mA

Pin assignment

PIN 1	Brown
PIN 2	White
PIN 3	Blue
PIN 4	Black

Ordering code

Product type description:

(1)-(2)-(3)-(4)-(5)-(6)-(7)-(8)-(9)-(10)-(11)-(12)-(13)-(14)

(1)

A	Pre-wired cable
V	Interconnector
S	Connector without cable

(2)a

K	female connector
KK	Female plug - female plug
S	Male connector
SS	Connector - connector
SK	Connector - female plug

(2)b

3P	3-pole
4P	4-pole
5P	5-pole
6P	6-pole

7P	7-pole
8P	8-pole
9P	9-pole
10P	10-pole
11P	11-pole
12P	12-pole
23P	23-pole
2P+PE	2 pole + PE
3P+PE	3 pole + PE

(3)

M8	M8 / round 8 mm
M12	M12
M18	M18
M23	M23
DIN43650	DIN 43650

(4)

R	Latching interlocking
S	Screw locking

(5)

G	straight
W	angled

(6)

X	without
0.3M	0,3 m
0,5M	0,5 m
1M	1 m
1.5 m	1.5 m

2M	2 m
2.5M	2.5 m
3M	3 m
5M	5 m
10M	10 m
15M	15 m
20M	20 m

(7)

X	without
BK	Black
GY	Grey
OG	Orange

(8)

X	-
1	PVC
2	PUR
3	Rubber
4	Silicone

(9)

X	Neutral
1LP	1x LED - PNP
2LP	2x LED - PNP
3LP	3x LED - PNP

(10)

X	without
A	A-coding
B	B-Coding

(11)

1	without
2	UL
3	CSA
4	USA/CAN

(12)

69	IP69K
-----------	-------

(13)

VA	Material, thread/knurled nut, stainless steel (VA)
-----------	--

(14)

075	0.75 mm ² cable section
------------	------------------------------------

Pictures

Product picture (catalogue individual photo)



ID: k0804f09
| 95.8 kB | .jpg | 352.778 x 210.608 mm - 1000 x 597 px - 72 dpi
| 12.8 kB | .png | 74.083 x 44.097 mm - 210 x 125 px - 72 dpi

Schmersal, Inc., 15 Skyline Drive, Hawthorne, NY 10532

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on: 22/06/2023, 10:20