



V-SK4P-M12P-S-G-3M-BK-2-X-T-4

Data

Ordering data

| | |
|-------------------------------|-------------------------------|
| Product type description | V-SK4P-M12P-S-G-3M-BK-2-X-T-4 |
| Article number (order number) | 103013432 |
| EAN (European Article Number) | 4030661490922 |
| eCl@ss number, version 12.0 | 27-06-03-11 |
| eCl@ss number, version 11.0 | 27-06-03-11 |
| eCl@ss number, version 9.0 | 27-06-03-11 |
| ETIM number, version 7.0 | EC001855 |
| ETIM number, version 6.0 | EC001855 |

General data

| | |
|--------------|--------------------|
| Standards | EN IEC 61076-2-111 |
| Gross weight | 407 g |

General data - Features

| | |
|---------------------------|---------|
| Halogen free | Yes (1) |
| Cable drag chain suitable | Yes (1) |
| Number of cable wires | 4 |

Mechanical data

Tightening torque, maximum 1 Nm

Mechanical data - Connection technique

Length of cable 3 m
Wire cross-section 1.5 mm²
Cable diameter 9.6 mm
Bending radius (fixed) 4 x Ø-cable
Bending radius (repeated) 7.5 x Ø-cable
Colour of the Cable mantle Black
Material of the Cable mantle PUR

Mechanical data - connector side A

Connector typ Female connector, M12
Design straight
Connector coding T
Connector latching Screw locking
Material of the gland Metal, CuZn, nickel-plated
Material of the handle Plastic, TPU
Colour of the handle Black

Mechanical data - connector side B

Connector typ Male connector, M12
Design straight
Connector coding T
Connector latching Screw locking
Material of the gland Metal, CuZn, nickel-plated

| | |
|------------------------|--------------|
| Material of the handle | Plastic, TPU |
| Colour of the handle | Black |

Ambient conditions

| | |
|---------------------------------|----------------------|
| Degree of protection | IP65 IP67 IP68 |
| Ambient temperature (Connector) | -30 ... +90 °C |
| Ambient temperature (fixed) | -40 ... +80 °C |
| Ambient temperature (moved) | -25 ... +80 °C |

Electrical data

| | |
|-------------------------|-----------|
| Thermal test current | 12 A |
| Rated operating voltage | 63 VDC |
| Operating current | 12,000 mA |

Pictures

Product picture (catalogue individual photo)



ID: k1204f18
 | 21.4 kB | .png | 74.083 x 53.269 mm - 210 x 151 px - 72 dpi
 | 199.1 kB | .jpg | 352.778 x 254.353 mm - 1000 x 721 px - 72 dpi
 | 13.2 kB | .jpg | 112.889 x 81.492 mm - 320 x 231 px - 72 dpi
 | 28.7 kB | .jpg | 123.472 x 88.9 mm - 350 x 252 px - 72 dpi

Schmersal, Inc., 15 Skyline Drive, Hawthorne, NY 10532

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on: 11/10/2023, 12:19