



## V-SK4P-M12P-S-G-7,5M-BK-2-X-T-4

### Data

#### Ordering data

|                               |                                 |
|-------------------------------|---------------------------------|
| Product type description      | V-SK4P-M12P-S-G-7,5M-BK-2-X-T-4 |
| Article number (order number) | 103013434                       |
| EAN (European Article Number) | 4030661490946                   |
| eCl@ss number, version 12.0   | 27-06-03-11                     |
| eCl@ss number, version 11.0   | 27-06-03-11                     |
| eCl@ss number, version 9.0    | 27-06-03-11                     |
| ETIM number, version 7.0      | EC001855                        |
| ETIM number, version 6.0      | EC001855                        |

#### General data

|              |                    |
|--------------|--------------------|
| Standards    | EN IEC 61076-2-111 |
| Gross weight | 952 g              |

#### General data - Features

|                           |         |
|---------------------------|---------|
| Halogen free              | Yes (1) |
| Cable drag chain suitable | Yes (1) |
| Number of cable wires     | 4       |

## Mechanical data

Tightening torque, maximum 1 Nm

## Mechanical data - Connection technique

Length of cable 7.5 m  
Wire cross-section 1.5 mm<sup>2</sup>  
Cable diameter 9.6 mm  
Bending radius (fixed) 4 x Ø-cable  
Bending radius (repeated) 7.5 x Ø-cable  
Colour of the Cable mantle Black  
Material of the Cable mantle PUR

## Mechanical data - connector side A

Connector typ Female connector, M12  
Design straight  
Connector coding T  
Connector latching Screw locking  
Material of the gland Metal, CuZn, nickel-plated  
Material of the handle Plastic, TPU  
Colour of the handle Black

## Mechanical data - connector side B

Connector typ Male connector, M12  
Design straight  
Connector coding T  
Connector latching Screw locking  
Material of the gland Metal, CuZn, nickel-plated

|                        |              |
|------------------------|--------------|
| Material of the handle | Plastic, TPU |
| Colour of the handle   | Black        |

## Ambient conditions

|                                 |                      |
|---------------------------------|----------------------|
| Degree of protection            | IP65<br>IP67<br>IP68 |
| Ambient temperature (Connector) | -30 ... +90 °C       |
| Ambient temperature (fixed)     | -40 ... +80 °C       |
| Ambient temperature (moved)     | -25 ... +80 °C       |

## Electrical data

|                         |           |
|-------------------------|-----------|
| Thermal test current    | 12 A      |
| Rated operating voltage | 63 VDC    |
| Operating current       | 12,000 mA |

## Pictures

### Product picture (catalogue individual photo)



ID: k1204f18  
| 21.4 kB | .png | 74.083 x 53.269 mm - 210 x 151 px - 72 dpi  
| 199.1 kB | .jpg | 352.778 x 254.353 mm - 1000 x 721 px - 72 dpi  
| 13.2 kB | .jpg | 112.889 x 81.492 mm - 320 x 231 px - 72 dpi  
| 28.7 kB | .jpg | 123.472 x 88.9 mm - 350 x 252 px - 72 dpi

Schmersal, Inc., 15 Skyline Drive, Hawthorne, NY 10532

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on: 11/10/2023, 12:22