



Protection – ATEX

Explosion Protection Catalogue | Version 05



SCHMERSAL
Safe solutions for your industry

www.schmersal.net

You will also find detailed information regarding our product variety on our website: www.schmersal.net.



Online documentation in 13 languages

The online catalogue for our customers is permanently updated. The Main catalogue can be consulted on the Internet in as much as 13 languages.

The technical data of our entire product range are always up-to-date. The declarations of conformity, the test certificates and the mounting instructions can be consulted or even downloaded as well.

Service for designers

The online catalogue also includes the technical drawings of our products – a special service to designers. In this way, they can be downloaded and directly fed in CAD-systems.

The Schmersal homepage furthermore contains up-to-date information on general subjects, technical articles on machine safety as well as news regarding events and trainings. To be bookmarked!

The direct way

If you need further information or you want personal advice, you can call us as well:
+ 49-(0) 2 02-64 74-0.

The addresses of our representations in Germany and abroad can be found on the front pages of this catalogue.

**We are at your disposal –
anyplace, anywhere, anytime!**



Attention!

The data specified in this catalogue are carefully checked typical standard values.
Subject to technical modifications and error.

Content

Introduction	The basics of explosion protection	4
Safety-monitoring modules	PROTECT SRB 101EXi.....	16
	PROTECT SRB 200EXi.....	18
Safety switch	EX-AZ 16-...-3D	22
	EX-AZ 335-...-3D	25
	EX-AZ 355-...-3D	26
	EX-AZ 415-...-3D	28
	EX-AZ 3350-...-3D	30
Solenoid interlocks	EX-AZM 170-...-3G/D	34
	EX-AZM 161-...-3D	36
	EX-AZM 415-...-3D	40
Position switches	EX-Z/T 235-...-3D	44
	EX-Z/T 335-...-3G/D	54
	EX-Z/T 355-...-3G/D	55
	EX-MAF 330-...-3D	60
	EX-T 335-.....	62
	EX-T/M 441-...	68
	EX-T/M 250-...	69
	EX-TS 064-.....	70
	EX-MS 064-.....	71
	EX-T. 064-.....	73
	EX-M. 064 R.....	74
	EX-M. 064 L.....	75
Safety switch for hinged guards	EX-TV.S 335.....	78
Belt alignment switches / Slack-wire switch	EX-T/M 441-...	82
	EX-T/M 250-...	83
Pull-wire emergency-stop switches	EX-ZQ 900-3D	86
	EX-T3Z 068-...	88
Safety sensors	EX-BNS 250-...-3G/D.....	92
	EX-BNS 33-...-3G/D.....	94
	EX-BNS 120-...-3G/D.....	96
	EX-BNS 180-...-3G/D.....	98
	EX-BNS 303-...-3G/D	100
	EX-CSS 180-...-3G/D	102
Magnetic reed switches	EX-BN 20-...-3G/D	106
Control devices and indicator lights	EX-RDT.....	114
	EX-RDM.....	114
	EX-RDL.....	115
	EX-RDLM.....	115
	EX-RMLH.....	116
	EX-RDP40	117
	EX-RDRZ45	118
	EX-RDRZ45rt.....	119
	EX-RW...21/32	120
	EX-RW...21.1/32.1	120
	EX-RS	122
	EX-RF10	124
	EX-RF03	124
	EX-RLDE ws 24	125
	EX-EBG 331.O	126
	EX-EBG 633.O	126
	EX-EBG 665.O	126
Trapped key system	EX-SHGV-...-3G/D (selector switch; key-operated selector switch)	134
	EX-SVM1-...-2G/D (interlocking device)	135
	EX-SHGV-...-2G/D (guard locking device)	136

Explosion protection

The basics of explosion protection

The implementation of the ATEX Directives (ATEX: ATmosphères EXplosibles) in Europe has changed the way of thinking with regard to the explosion protection. The manufacturers must follow the directive 94/4/EC to fulfill the harmonised standards in Europe. The directive is obligatory in all Member States and transposed into national law. This was carried out until 2003. On the other side the users have to fulfill the directive 1999/92/EC regarding the basic safety and health requirements for operation. Both Directives are based upon the standards listed in the Official Journal (OJ) of the European Commission. Not only the gas explosive protection is now standardised, but also the protection for dust atmospheres. In a few countries, e.g. in Germany, explosion protection regulations existed already at national level, however not harmonised. Due to the internationalisation and the standardisation on EN basis, the standards defining the requirements on equipment to be used in explosive atmospheres will gradually be re-

placed by the European Standards series EN 60079. Hybrid mixtures from gas and dust are included in the standardisation work as well. The mechanical explosion protection required by the ATEX Directives however still is in its "infancy".

The comprehensive product portfolio from Schmersal and Elan Schaltelemente complies with the requirements of the standards and directives. Our existing products and our innovations are consistently developed and refined on the basis of the current standards as well as the amendments, which are in the transitional stage. In this way, both the standard requirements and safety technology are integrated in the potentially explosive areas.

Source of ignition	Examples of the cause
Sparks	Mechanically generated sparks (e.g. by friction, stroke or cutting removal operations), electric sparks
Electric arcs/flashovers	Short-circuit, switching operations
Hot surfaces	Current in electrical installations, heaters and radiators, machining, heating during operation
Flames and hot gases	By combustion reactions, spark projection during welding
Electrical installations	Even extra-low voltages ($U < 50 \text{ V}$) still can generate sufficient energy to ignite an explosive atmosphere. Opening/closing of contacts, loose or defective contacts
Static electricity	Separately arranged conductive parts, many plastics
Equalizing currents	Reverse current from generators, earth connection in case of faults, induction
Electromagnetic waves in the $3 \times 10^{11} \dots 3 \times 10^{15} \text{ Hz}$ range	Laser beam for range finding, especially in case of beam focusing
High frequency $10^4 \dots 3 \times 10^{12} \text{ Hz}$	Radio signals, industrial high-frequency generators for heating, drying, cutting, etc.
Lightning	Atmospheric disturbances
Ionizing radiation	X-ray device, radioactive substances, energy absorption leads to heating
Ultrasonic	Energy absorption in solid/liquid substances leads to heating
Adiabatic compression and shock waves	Strokewise opening of valves
Exothermal reactions	Chemical reaction



The basic physic and technical principles

Complete combustion

Combustion or burning is a complex sequence of exothermic chemical reactions. A fire starts when a flammable and/or combustible material with an adequate supply of oxygen is exothermically disintegrated. Depending on the speed of combustion, we speak of deflagration, explosion or detonation.

A complete combustion causes significant damages, which varies with the combustion speed.

Order of magnitude of the speed of combustion

Deflagration	cm/s
Explosion	m/s
Detonation	km/s

Explosion

An explosion can only occur, when three factors come together: flammable material in ignitable quantities, oxygen and an ignition source. If one component is missing, no exothermic reaction will occur.

Oxygen

When a flammable substance is mixed with oxygen, a potentially explosive mixture is created.

For gases, the concentration ratio determines whether an explosion is possible. The mixture can only be ignited if the concentration of the substance in air is within the lower and upper explosive limits. Mixtures with concentrations smaller or greater these limits will not explode. A few chemically unstable substances (e.g. acetylene, ethylene oxide) have self-decomposing properties and therefore can also produce exothermal reactions without oxygen.

In these cases, the upper explosion limit (UEL) is 100 vol. %. For pressurised gases, the explosion ranges change. Dusts are also classified by a lower explosion limit (approx. at 20...60 g/m³) and an upper explosion limit (approx. at 2...6 kg/m³).

Potentially explosive substance

Any flammable substance in the form of gas, mist, vapour or dust is considered as potentially explosive substance. For mists and dusts, a potentially explosive atmosphere occurs when the drop or the particle size is smaller than 1 mm. Frequently-used mists, aerosols and dusts have a particle size between 0.001 mm and 0.1 mm. Dusts with larger particle sizes are not combustible.

Deposits of dust can be compared to porous elements and have hollow portion of up to 90%. The increase of temperature of dust deposits can cause the spontaneous ignition of the dust-like flammable substance. If a deposit of dust with small particle size is swirled up, the dust, along with the oxygen in the air, forms a combustible dust/air mix. The bigger the size reduction, the higher the explosion danger, since the surface of the hollow space increases. Dust explosions are often the consequence of smouldering dust layers which become stirred up and already carry the ignition initiation.

The potential danger of explosive dust atmospheres and the selection of the appropriate safety measures are evaluated by means of the safety characteristics of the substances concerned. To this end, dusts are classified in accordance with two of their substance-specific properties:


- Conductivity

Dusts are considered to be conductive when they have a specific electric resistance of up to 10^3 ohmmeters.

- Combustibility

Combustible dusts are characterised by the fact that they can burn or smoulder when mixed with air and that they form explosive mixtures along with oxygen under atmospheric pressure and at temperatures ranging from -20°C to $+60^\circ\text{C}$.

The safety characteristics of swirled up dusts are for instance the minimum ignition energy and the ignition temperature, whereas for deposits of dust the smouldering temperature is a characteristic feature.



The basics of explosion protection

EN 60079-10/14

Classification of zones and selection of equipment

Setting-up installations in potentially explosive areas involves a great deal of precautions to be taken. For instance, the equipment, the resources, the cables and conductors as well as the construction have to meet special requirements. In case of doubt, the consultation of experts during the planning is recommended.

Risk assessment

It is the responsibility and duty of the user to perform a risk analysis prior to installing new facilities.

He must verify where there is a risk of explosion and then divide areas into zones accordingly. Every plant must be examined for its particularities.

If nonetheless an explosion would be caused, the possible hazard scenario must be taken into consideration in the forefront. Can chain reaction occur, are damages to the building to be expected and which are the impacts of the explosion of subsequent plant components and parts?

Potential interactions with adjacent plants can occur, which cannot be produced on the individual plant.

The risk analysis requires a great deal of experience as well as a correct assessment.

In case of doubt, consulting experts on this matter is highly recommended, considering that the risk analysis builds the basis of all further measures to be taken before the installation can be put into operation.

Analysis of the explosion protection risk

The user of a machine or installation has to perform an accurate analysis according to the standards EN 60079-10, EN 60079-14 and EN 1127-1. On the basis of this analysis, he has to classify the areas in which explosive atmospheres may be present into zones. These observations must be documented.

Documentation of the explosion protection

The documentation is essential to ensure a safe operation of the installation in the potentially explosive area. It is drawn up prior to the set-up and must always be kept up-to-date. In case of changes to the installation, all the described influences data must be taken into account.

Example of an explosion protection document

Object responsible

Called by name in the documentation

Description of the structural/constructional and geographic conditions

Layout plan, building map, plant ventilation system

Description of the procedure, description of the plant with regard to explosion protection

Substance characteristics, list of all data including explosion-relevant parameters

Risk analysis, refer to checklist below

Protection concept, zone classification, explosion protection types used

Organisational measures

Instructions, prescriptions in written, work authorisations



Classification of the potentially explosive areas into zones

To determine the necessary protective measures to be taken and to select appropriate equipment, the potentially explosive areas have to be classified into zones. This classification of the potentially explosive areas into zones is based upon the frequency and the duration of the presence of the dangerous explosive atmosphere.

These framework conditions (frequency, duration) determine the classification and identification of gas explosion risk areas as zone 0, 1 or 2 as well as the required measures to be taken in order to avoid active sources of ignition.

Dust explosion risk areas are accordingly classified as zone 20, 21 or 22.

The EN 60079-10 standard can provide help with the classification of gas explosion risk areas into zones. The zone definition is included in all common documentation, i.e. in the ATEX Directive 1999/92/EC as well.

Zone 0 is an area, in which an explosive atmosphere consisting of a mixture with air of flammable substances in the form of gas, vapour or mist is present continuously or for long periods or frequently.

- Example: these conditions are usually found only inside containers, pipes, apparatus (evaporators, reaction chambers etc.).

Zone 1 is an area, in which an explosive atmosphere consisting of a mixture with air of flammable substances in the form of gas, vapour or mist is likely to occur occasionally in normal operation.

- Example: areas in the immediate surroundings of zone 0, of intakes and inlets, the areas around filling units and discharging equipment, the immediate surroundings of highly fragile apparatus or conductors in glass, ceramics etc., the area around insufficiently sealing gaskets, e.g. on pumps and dampers, the interior of apparatus such as evaporators and reaction chambers.

Zone 2 is an area, in which an explosive atmosphere consisting of a mixture with air of flammable substances in the form of gas, vapour or mist is not likely to occur in normal operation but, if it does occur, will persist for a short period only.

- Example: areas surrounding zone 0 or 1, specific storage plants

Zone 20 is an area, in which an explosive atmosphere in the form of a cloud of combustible dust in air is present continuously or for long periods or frequently.

- Example: these conditions are usually found only inside containers, pipes, apparatus, e.g. mills and grinders, dryers, mixers, feed pipes, silos etc.

Zone 21 is an area, in which an explosive atmosphere in the form of a cloud of combustible dust in air is likely to occur occasionally in normal operation.

- Example: also areas in the vicinity of inlets or work stations where dust is poured into containers, as well as areas where there are dust deposits and where a combustible dust/air mixture could form in the course of normal operation.

Zone 22 is an area, in which an explosive atmosphere in the form of combustible dust in air is not likely to occur in normal operation but, if it does occur, will persist for a short period only.

- Example: this could also include areas in the vicinity of devices containing dust, protection systems or components from which dust leaks and forms deposits (e.g. milling/grinding facilities, from which dust leaks and forms layers)

Dust Ex: selection according to the smouldering temperature and the ignition temperature

When selecting electrical apparatus for use in dust explosion risk areas, the smouldering temperature of the deposited dust and the ignition temperature of the potentially explosive dust/air mixture must be known, regardless of the zone.

The smouldering temperature is the lowest temperature of a hot surface on which a dust deposit of a defined thickness is ignited.

The ignition temperature of a dust cloud is the lowest temperature of a heated wall of an oven that ignites the dust/air mixture upon brief contact.

Combustible dusts are not divided into temperature classes like gases. The maximum surface temperature must be mentioned on the electrical equipment.

The table below summarizes the explosion parameters (ignition temperature, smouldering temperature and minimum ignition energy) of a few dusts.

Please note that for flammable substances a collective name, e.g. mill dust, designates different kinds of that product, each of them with diverging safety characteristics and parameters. Wheat flour for instance has other parameters than rye flour.

The specific parameters of the dust, which is permanent in each dust explosive area, must be determined. When the parameters of collective names are used, miscalculations can occur.

Substance	Ignition temperature Ti [°C]	Smouldering tempe- rature Ts [°C]	ø Minimum energy ø Emin [mJ]
Flour	≥ 380	≥ 300	≥ 30
Wood	≥ 410	≥ 200	≥ 100
Brown coal	≥ 380	≥ 225	-
Coal	≥ 500	≥ 240	≥ 1000
PVC	≥ 530	≥ 340	≥ 5
Aluminium	≥ 560	≥ 270	≥ 5
Sulphur	≥ 240	≥ 250	10

The basics of explosion protection

Types of protection

General overview

Essential requirements

The EN 60079-0 describes the essential requirements, which apply to all types of explosion protection.

Mechanical protection

Mechanical tests are carried out in accordance with EN 60079-0. The enclosures or the exterior part of the enclosure, pushbuttons must withstand high impact energy.

Type of protection „n“ EN 60079-15

The type of protection “n” originally was used as stand-alone standard for use in ATEX category 3G respectively was defined as zone 2 standard in IECEx. This standard has been designed for normal operation. The fault analysis, which is performed for the other types of protection, is not executed, considering that the explosive atmosphere and the ignition spark are very unlikely to occur simultaneously in zone 2; in other words: electrical apparatus cannot ignite an explosive atmosphere surrounding them in normal operation and under defined abnormal operating conditions.

Meanwhile, the EN 60079-15 has been rewritten, so that the essential requirements are now described in the EN 60079-0.

This reflects for instance in the following way: The type of protection Ex nL has been replaced with the Ex ic type of protection relative to intrinsic safety. The sub-group is transferred from the EN 60079-15 into the EN 60079-11. This leads to changes, which could require a more accurate analysis.

Temperature classes for gases (EN 60079-0):

Classification of the maximum surface temperature into classes for electrical apparatus belonging to Equipment Group II

T1	T2	T2	T4	T5	T6
450°C	300°C	200°C	135°C	100°C	85°C

Ignition protection type and the main characteristics

Ignition protection type | Basic principle, main application

Oil immersion „o“	The source of ignition is permanently immersed in oil. Application: switchgear and transformers
Pressurized enclosures „p“	The formation of a potentially explosive atmosphere inside an enclosure is prevented by maintaining a positive internal pressure of protective gas in relation to the surrounding atmosphere. Application: machinery, commutation motors, control cabinets, monitors, keyboards, analysers
Powder filling „q“	A fine granular packing material surrounds the ignition source, thus making it impossible for an electric arc created in the enclosure under certain operating conditions to ignite a potentially explosive atmosphere surrounding the enclosure. Application: capacitors, condensers, electronic ballast, sensors
Flameproof enclosures „d“	Parts which can ignite a potentially explosive atmosphere are surrounded by an enclosure which withstands the pressure of an explosive mixture exploding inside the enclosure and prevents the transmission of the explosion to the atmosphere surrounding the enclosure. Application: switchgear, spark-generating parts, power engineering, heavy-current engineering
Increased safety „e“	Additional measures are applied to increase the level of safety, thus preventing the possibility of excessive temperatures and the occurrence of sparks or electric arcs within the enclosure or on exposed parts of electrical apparatus, where such ignition sources would not occur in normal service. Application: terminal and connection boxes (engines)
Encapsulation „m“	Parts that are capable of igniting an explosive atmosphere by either sparking or heating are enclosed in a compound in such way as to avoid ignition of an explosive atmosphere. Application: sensors, variable speed drives
Intrinsic safety „i“	An electric circuit is intrinsically safe if no sparks or thermal effects produced under specified test conditions are not capable of causing ignition of a given explosive atmosphere. Application: measurement and control technology
Intrinsically safe systems „i-SYST“	The entirety of interlinked and interconnected electrical apparatus, documented by a system description. Circuits used completely or partly inside hazardous areas are intrinsic safe.

Intrinsic safety

Principle

The type of protection "intrinsic safety" Ex i is based on the principle of limitation of current, voltage and storables energy within an electric circuit. Intrinsic safety does not reduce the potentially explosive substance and/or the oxidizing agent.

The ignition of an explosive mixture is avoided, when neither electric sparks nor the effect of heat can occur. The electrical energy is limited in order to keep electrical sparks below the ignition limit.

The energy limitation avoids the excessive heating of the electrical apparatus and its surfaces. This also applies to the sensors integrated in the intrinsically safe electrical circuits. Electrical energy can be stored in capacities (condensers) or inductivities (coils) within the intrinsically safe electrical circuit.

Zener diodes, which are used for limiting voltage, become conductive as of a specific voltage. The increased voltage is conducted

through the zener diode, i.e. the electrical circuit in the EX zone has limited voltage.

A series-wired resistance limits the current in the potentially explosive area.

$$I_{\max} = I_o = U_o / R$$

With the limitation of voltage and current, the maximum power is

$$P_o = U_o^2 / 4R$$

The authorised maximum values are taken from the ignition limit curves, defined in the EN 60079-11 standard. For the gas groups I, IIA, IIB and IIC, there are four ignition limit curves. The classification is done according to the ignition energy.

The ignition limit curves have been calculated by means of a spark tester, as described in the EN 60079-11 standard.

Subdivision of the type of protection „n“ Ex n in Europe

Symbol	Meaning	Comparable with	Method	Subdivision
A	Non-sparking	Ex e	Occurrence of electric arcs, sparks or hot surfaces is minimised	None
C	Sparking apparatus	Partially Ex d, Ex m	Enclosed switching device, non-explosive components hermetically closed, sealed or encapsulated devices	IIA, IIB, IIC
R	Vapour-tight enclosure	-	Penetration of explosive gases is reduced	None
L*	Energy limitation	Ex i	Energy limitation, so that neither sparks nor thermal effects can produce an ignition	IIA, IIB, IIC
P	Simplified pressurized enclosure	Ex p	Penetration of explosive gases is avoided by overpressure. The monitoring unit will not switch-off	None

*different in North-America and Europe

The basics of explosion protection

Electrical apparatus and associated apparatus

An intrinsically safe electric circuit contains at least one electrical apparatus and one associated apparatus.

The electric circuits of the electrical apparatus meet the requirements of the intrinsic safety. The electrical apparatus must only be connected to non-intrinsically safe circuits through associated apparatus. An associated apparatus possesses both intrinsically safe and non-intrinsically safe circuits. To separate the electric circuits, a zener diode or galvanic isolators are used. The EN 60079-11 describes this separation calls as a "safety barrier".

Intrinsically safe electrical apparatus and intrinsically safe components from associated equipment are classified in different levels of protection "ia", "ib" and "ic" according to EN 60079-11. This classification is included as of the 5th edition of the IEC Ex version.

The "ia" category basically offers the highest level of protection, "ib" a higher level of protection and "ic" a high level of protection.


The category "ia" or "ib" determines whether the protective circuit offers a single fault safety or a double fault safety. For protection level "ic", no fault analysis is performed.

Here the safety for normal operation is sufficient. Therefore, the standard EN 60079-14, chapter 12.3 recommends galvanic isolation for intrinsically safe circuits in zone 0, category "ia". For intrinsic safety, a fault analysis is performed to exclude explosion risks. However, no statement whatsoever is made with regard to the operational safety. This means that a functional total breakdown is, for the explosion protection standpoint, allowed.

The electrical apparatus may be used in zone 0 in accordance with the category. The associated apparatus are installed in the safe area, only the intrinsically safe electric circuits are installed in the potentially explosive area in accordance with the category.

Basically it is possible to apply further protection measures. So that the associated apparatus can be installed in zone 2 or even in zone 1.

Design of intrinsically safe electric circuits



Design of intrinsically safe electric circuits (typical values)

Resistance (back/forth)	0.5 mm ²	72 Ohm/km
	0.75 mm ²	48 Ohm/km
	1.5 mm ²	24 Ohm/km
Capacity		180-200 nF/km
Inductivity		0.8-1 mH/km

Simple electrical apparatus – intrinsic safety

Type	Condition	Example
Passive components	None	Switches, terminal/junction boxes (modular enclosures), resistance, simple semi-conductor components
Energy storage	Values must be observed during calculation	Capacitors, coils
Energy source	≤ 1,5 V ≤ 100 mA ≤ 25 mW	Thermocouple Photocell



Cables for zones 0, 1 and 2

The cables must be laid in such manner that they are protected against mechanical damages, corrosion, chemical and thermal influences. This is an obligatory requirement for the type of protection "intrinsic safety". The accumulation of potentially explosive atmospheres must be prevented in shafts, pits, ducts, conduits and trenches.

The propagation of flammable gases, vapours, liquids or combustible dusts through shafts, pits, ducts, conduits and trenches must be prevented as well.

If possible, cables and conductors must be laid without interruption in the potentially explosive area. If this is impossible, the connection of cables must be realised in an junction box with the appropriate explosion protection type for that zone. If deviation of this stipulation is required for installation reasons, the requirements of the EN 60079-14 standard must be observed.

Appropriate cables must be selected for intrinsically safe electric circuits. Furthermore, the following conditions apply to intrinsically safe electric circuits, also when they are installed outside of the potentially explosive area:

- Protection against the ingress of external energy.
- Protection against external electric or magnetic fields.

Possible cause: overhead highvoltage line or 1-phase highvoltage lines.

- The conductors of intrinsically safe and non-intrinsically safe electric circuits must not be laid in the same conduit.
- In case of armoured, metal sheathed or shielded cables, intrinsically safe and non-intrinsically safe electric circuits can be laid in the same conduit.

In the control cabinet, the intrinsically safe electric circuits must be clearly marked. The standard prescribes no uniform procedure and only points out that for the marking preferably a light blue colour should be used. However, the neutral conductors of energy cables are usually also marked with a blue colour. In order to avoid confusion, another marking should be used for the intrinsically safe electric circuits in this case. What is important, is a conveniently arranged layout and a spatial separation in the control cabinet.

Conductive shields must only be earthed at places located outside the potentially explosive atmosphere.

Cable	Requirement
Stationary apparatus	Enclosure
Mobile, transportable apparatus	External enclosure
flexible	Minimum section surface Design
	Thermoplastic, duroplast, elastomer or metal insulated with metal enclosure Heavy polychloroprene, synthetic elastomer, heavy rubber hose pipe or similar robust design 1.0 mm ² – Light rubber hose pipe with/without polychloroprene enclosure – Heavy rubber hose pipe with/without polychloroprene enclosure – Plastic-insulated cable, similar to heavy rubber hose pipe

Selection criteria for cables for the type of protection "intrinsic safety"

Criterion	Condition	Note
Insulated cables	Test voltage ≥ 500 VAC	Cable ground, cable shield and shield ground
Diameter of the individual conductors	$\geq 0,1$ mm	Also for flexible conductors
Flexible conductors	To be protected against splicing	e.g. by using conductor ferrules
Multi-wire cables	Acceptable	The requirements for the error analysis to EN 60079-14 must be observed
Parameters	(Cc and Lc) or (Cc and Lc/Rc)	In case of doubt: worst case



The basics of explosion protection

Mechanical explosion protection

The general requirements can be summarised as follows:

- The equipment must meet all stipulated application requirements (e.g. rough operation, humidity effects, ambient temperature and pressure fluctuations, influence of chemical agents, corrosion, vibrations) (refer to the operating instructions);
- Determination and evaluation of the ignition hazards – Apparatus interior (heating due to failure capable of causing ignition inside the device) – Dust deposits (friction between moving parts) – Evaluation of the surface temperature according to the category
- Documentation of the ignition hazard analysis
- Determine the maximum surface temperature for internal and external surfaces (for category 1 maximum 80 % of T1 ... T6)
- Prevention of mechanically generated sparks by friction, stroke and grinding processes (aluminium, magnesium, titan and zirconium portion in alloys and coatings to be limited in accordance with the category); All conductive parts must be grounded and protected against sparks produced by static electricity; disruptive discharge voltage of non-conductive layers on metallic surfaces smaller than 4 kV; surface resistance smaller than 10^9 Ohm
- Further detailed requirements depending on the equipment category and possible sources of ignition.

The maximum authorised mass portions for the material used for external parts in case an ignition hazard is present due to friction, stroke or friction sparks according to the ignition hazard evaluation, amount to:

- Category M1/M2: not more than 15% aluminium, magnesium, titan and zirconium in total as well as not more than 6% magnesium, titan and zirconium in total
- Category 1: not more than 10 % aluminium, magnesium, titan and zirconium in total as well as not more than 7.5 % magnesium, titan and zirconium in total
- Category 2: not more than 7.5 % magnesium,
- Category 3: no special requirements.

EN 13463-1, clause 5.2 "Evaluation of the ignition hazard" requires an assessment of the ignition hazards as well as a corresponding report in tabular form (example: refer to page 13). The ignition hazard assessment is used for the classification into equipment categories:

"If an equipment has been designed and built in accordance with good engineering practices and the assessment of the ignition hazards ensures that under normal operation, the equipment has no potential source of ignition, the equipment can be classified into the equipment category 3.

If the ignition hazard assessment ensures that the equipment has no potential source of ignition in case of expected or rare malfunctions, it can be classified into the equipment category 2 or 1".

Section 5.2.7 of the EN 13463-1 includes an assessment report for Group II equipment.

Constructional safety „c“

- Type of protection, in which constructional measures are applied to ensure protection against potential ignition by hot surfaces, sparks and adiabatic compressions generated by moving parts,
- Using proven technical principles,
- The probability of a dangerous failure is very low
- Observations with regard to the lifetime of ball and rolling bearings, distances between moving and fixed parts, rotation speeds higher than 1 m/s, electrostatic problem for belt transmissions.

Marking

- Basic requirement: the field of application of all EX-relevant equipment, protective systems and components must be identified.
- Marking example: ☺ II 1G c T4

Conditions for safe operation

- The special conditions for a safe application are described in the operating instructions manual of the individual Ex safety switchgear.

Assessment of the ignition hazard for equipment of Group II (EN 13463-1), gas

Potential ignition source (1)			Measures applied to prevent the source becoming effective (2)	Ignition protection used (3)
Normal operation (1b)	Expected malfunction (1b)	Rare malfunction (1c)		

Columns (1b) and (1c) are only required, when the definition of the equipment category of Group II requires that they must be protected in case of specific malfunctions, e.g. for equipment category 2 or 1.

The manufacturer of the equipment performs and documents the risk analysis of the ignition hazard. The user must also perform a risk analysis for the equipment, which was integrated in the machine at the time when it had to meet the requirements of the ATEX 1999/92/EC.

No.	Product designation												Resulting equipment category including all existing ignition hazards					
	1		2				3				4							
	Ignition hazard		a	b	a	b	c	d	e	a	b	c	a	b	c	d	e	f
No.	Potential ignition source								Reasons for assessment	Description	Description of the protective measurement (standards, technical rules, experimental results)	Proof (including relevant Ex features listed in column 1)						
		During normal operation		During expected malfunction		During rare malfunction		Not to be observed					During normal operation		During expected malfunction		During rare malfunction	
1																		
2																		
3																		

The basics of explosion protection

Safety relay modules



The safety relay modules of the PROTECT series SRB 101Exi (one safety release) and SRB 200Exi (two safety releases) are suitable for use in potentially explosive atmospheres or Ex zones. There are variants with monitored reset function (trailing edge) as well as with automatic or manual reset function. All these versions have a stop 0 safety release and optionally can be supplied with cross-wire short detection.

Content

SRB 101EXi-...	16
SRB 200EXi-...	18

SRB-EXi safety relay module

PROTECT SRB 101EXi-...



- 1 or 2 channel control
- 1 safety contact
- Suitable for signal processing of emergency stop control devices, interlocking equipment, etc.
- 1 additional signalling contact (auxiliary contacts must not be used in safety circuits)
- Trailing edge (version -1R)
- Automatic reset function (version -1A)
- Optionally cross-wire short recognition (through switch)
- Current and voltage limitation of the input circuits (intrinsically safe)
- Green LED indications for relays K1, K2, U_B, U_i and U_{Exi}
- DIN rail mounting to DIN EN 60715:2001
- Thermoplastic enclosure to UL-94-V-0, graphite black RAL 9011
- Certification to DIN EN ISO 13849-1:2007
- Certification to ATEX 94/9/EG
- Electric circuits up to zone 1/21
- Installation in zone 2 possible

Technical data

Equipment category, explosion protection type:	Gas: $\text{Ex II 3 G Ex nAnC IIC T5}$ (SRB in zone 2); Gas/dust: $\text{Ex II (2) GD [Ex ib] IIC/[Ex ibD]}$ $[\text{Ex ib}] \text{IIC}/[\text{Ex ibD}]$
Inputs (S11-S12, S21-S22, X1-X2/X3):	T5
Temperature class:	T5
Voltage U _o :	33.6 V
Current I _o :	57.0 mA
Capacity P _o :	478.8 mW (linear characteristic)
Maximum safety voltage U _m :	253 VAC
Isolation:	safe separation to EN 60079-11: Amplitude of the voltage 375 V
Rated operating voltage:	24 VDC $-15\%/+20\%$, residual ripple max. 10%
Recommended fuse for the operating voltage:	internal fuse F1: T 50 mA/250 V; internal fuse F2: T 100 mA/250 V
Protection class:	enclosure: IP40 Terminals: IP20 Wiring compartment: IP54
Power consumption:	max. 3.0 W
Switching capacity of the enabling paths:	230 V; 3 A ohmic (inductive with suitable protective circuit) AC-15: 230 VAC/3 A DC-13: 24 VDC/3 A
Recommended fuse for the enabling paths:	3.15 A slow blow
Min. switching capacity:	min. 10 V/10 mA
Contact resistance:	max. 100 m Ω in new state
Contact material/contacts:	AgSnO, self-cleaning, positive drive
Switching capacity of the auxiliary contacts (21-22):	24 VDC, 2 A
Recommended fuse for the auxiliary contacts:	2 A slow blow
Current and voltage at S11-S12, S21-S22:	24 VDC, 5 mA
Current limitation at S11-S12, S21-S22:	15 mA
Pull-in delay:	approx. 300 ms (Version -1A) approx. 20 ms (Version -1R)
Drop-out delay:	in case of emergency stop: approx. 20 ms; in case of voltage drop: approx. 20 ms
Bridging in case of voltage drops:	approx. 15 ms
Air clearances and creepage distances:	EN 60664-1:2003 (DIN VDE 0110-1), 4 kV/2; EN 60079-11:2007 (VDE 0170/0171 Part 7)
Max. total line resistance:	30 Ohm
Ambient operating:	-25 °C ... +60 °C
Storage temperature:	-40 °C ... +85 °C
EMV:	EN 61000-6-2:2005
Vibrations:	EN 60068-2-6:1996
Frequency:	10 ... 55 Hz
Amplitude:	0.35 mm
Climatic resistance:	EN 60068-2-3:1986
Mechanical life:	10 ⁷ operations
Weight:	230 g
Dimensions:	22.5 x 100 x 121 mm

Approvals



Ordering details

SRB 101EXi-1①		
No.	Option	Description
①	R	Trailing edge
	A	Automatic reset function

Classification

Safety parameters:	
Standards:	EN ISO 13849-1, IEC 61508, EN 60947-5-1
PL:	STOP 0: up to e
Category:	STOP 0: up to 4
PFH value:	STOP 0: $\leq 2.00 \times 10^{-8}/\text{h}$
SIL:	STOP 0: up to 3
Mission time:	20 years

The PFH value of $2.00 \times 10^{-8}/\text{h}$ applies to the combinations of contact load (current through enabling contacts) and number of switching cycles (n-op/y) mentioned in the table below. At 365 operating days per year and a 24-hours operation, this results in the below-mentioned switching cycle times (t-cycle) for the relay contacts. Diverging applications upon request.


Contact load	n-op/y	t-cycle
20 %	525,600	1.0 min
40 %	210,240	2.5 min
60 %	75,087	7.0 min
80 %	30,918	17.0 min
100 %	12,223	43.0 min

SRB-EXi safety relay module

Note

- 2-channel control, shown for a guard door monitor with two position switches where one has a positive break contact; with external reset button (R).
- Relay outputs: 2-channel control, suitable for contact reinforcement or multiplication by means of contactors or relays with positive-drive contacts.
- (H2) = Feedback circuit
- The control recognizes cable break, cross-wire shorts (switch in position "QS") and earth leakages in the monitoring circuit.
- The safety function is defined as the opening of release 13-14 when the inputs S11-S12 or S21-S22 are opened.

Wiring diagram



Gas zone (1), 2 / Dust zone (21), 22

Note

- Cable connections:
 - single strand: rigid or flexible (with or without conductor ferrules) 0.25 ... 2.5 mm²;
 - multi-strand with identical section: rigid or flexible (with conductor ferrules without plastic) 0.25 ... 2.5 mm²;
 - flexible (without or with TWIN conductor ferrules) 0.5 ... 1.5 mm²

Legend

- ① Sensor: Installation in zone 1/21
- ② SRB Exi: Installation in zone 2
- ③ Control

SRB-EXi safety relay module

PROTECT SRB 200EXi-...



- 1 or 2 channel control
- 2 safety contacts
- Suitable for signal processing of emergency stop control devices, interlocking equipment, etc.
- Trailing edge (version -1R)
- Automatic reset function (version -1A)
- Optionally cross-wire short recognition (through switch)
- Current and voltage limitation of the input circuits (intrinsically safe)
- Green LED indications for relays K1, K2, U_B, U_i and U_{EXi}
- DIN rail mounting to DIN EN 60715:2001
- Thermoplastic enclosure to UL-94-V-0, graphite black RAL 9011
- Certification to DIN EN ISO 13849-1:2007
- Certification to ATEX 94/9/EG
- Electric circuits up to zone 1/21
- Installation in zone 2 possible

Technical data

Equipment category, explosion protection type:	Gas: II 3 G Ex nAnC IIC T5 (SRB in zone 2) Gas/dust: II (2) GD [Ex ib] IIC/[Ex ibD] [Ex ib] IIC/[Ex ibD]	
Inputs (S11-S12, S21-S22, X1-X2/X3):	T5	
Temperature class:	T5	
Voltage U _o :	33.6 V	
Current I _o :	57.0 mA	
Capacity P _o :	478.8 mW (linear characteristic)	
Maximum safety voltage U _m :	253 VAC	
Isolation:	safe separation to EN 60079-11: Amplitude of the voltage 375 V	
Rated operating voltage:	24 VDC -15%/+20%, residual ripple max. 10%	
Recommended fuse for the operating voltage:	internal fuse F1: T 50 mA/250 V; internal fuse F2: T 100 mA/250 V	
Protection class:	IP40 Terminals: IP20 Wiring compartment: IP54	
Power consumption:	max. 3.0 W	
Switching capacity of the enabling paths:	230 V; 3 A ohmic (inductive with suitable protective circuit) AC-15: 230 VAC/3 A DC-13: 24 VDC/3 A	
Recommended fuse for the enabling paths:	3.15 A slow blow	
Min. switching capacity:	min. 10 V/10 mA	
Contact resistance:	max. 100 mΩ in new state	
Contact material/contacts:	AgSnO, self-cleaning, positive drive	
Current and voltage at S11-S12, S21-S22:	24 VDC, 5 mA	
Current limitation at S11-S12, S21-S22:	15 mA	
Pull-in delay:	approx. 300 ms (Version -1A) approx. 20 ms (Version -1R)	
Drop-out delay:	in case of emergency stop: approx. 20 ms; in case of voltage drop: approx. 20 ms	
Bridging in case of voltage drops:	approx. 15 ms	
Air clearances and creepage distances:	EN 60664-1:2003 (DIN VDE 0110-1), 4 kV/2; EN 60079-11:2007 (VDE 0170/0171 Part 7)	
Max. total line resistance:	30 Ohm	
Ambient operating:	-25 °C ... +60 °C	
Storage temperature:	-40 °C ... +85 °C	
EMV:	EN 61000-6-2:2005	
Vibrations:	EN 60068-2-6:1996	
Frequency:	10 ... 55 Hz	
Amplitude:	0.35 mm	
Climatic resistance:	EN 60068-2-3:1986	
Mechanical life:	10 ⁷ operations	
Weight:	230 g	
Dimensions:	22.5 x 100 x 121 mm	

Approvals



Ordering details

SRB 200EXi-1①		
No.	Option	Description
①	R	Trailing edge
	A	Automatic reset function

Classification

Safety parameters:	EN ISO 13849-1, IEC 61508, EN 60947-5-1
Standards:	
PL:	STOP 0: up to e
Category:	STOP 0: up to 4
PFH value:	STOP 0: $\leq 2.00 \times 10^{-8}/h$
SIL:	STOP 0: up to 3
Mission time:	20 years

The PFH value of $2.00 \times 10^{-8}/h$ applies to the combinations of contact load (current through enabling contacts) and number of switching cycles (n-op/y) mentioned in the table below. At 365 operating days per year and a 24-hours operation, this results in the below-mentioned switching cycle times (t-cycle) for the relay contacts.

Diverging applications upon request.


Contact load	n-op/y	t-cycle
20 %	525,600	1.0 min
40 %	210,240	2.5 min
60 %	75,087	7.0 min
80 %	30,918	17.0 min
100 %	12,223	43.0 min

SRB-EXi safety relay module

Note

- 2-channel control, shown for a guard door monitor with two position switches where one has a positive break contact; with external reset button (R).
- Relay outputs: 2-channel control, suitable for contact reinforcement or multiplication by means of contactors or relays with positive-drive contacts.
- (H2) = Feedback circuit
- The control recognizes cable break, cross-wire shorts (switch in position "QS") and earth leakages in the monitoring circuit.
- The safety function is defined as the opening of release 13-14 when the inputs S11-S12 or S21-S22 are opened.

Wiring diagram



Gas zone (1), 2 / Dust zone (21), 22

Note

- Cable connections:
 - single strand: rigid or flexible (with or without conductor ferrules) 0.25 ... 2.5 mm²;
 - multi-strand with identical section: rigid or flexible (with conductor ferrules without plastic) 0.25 ... 2.5 mm²;
 - flexible (without or with TWIN conductor ferrules) 0.5 ... 1.5 mm²

Legend

- ① Sensor: Installation in zone 1/21
- ② SRB Exi: Installation in zone 2
- ③ Control

Simple electric apparatus, type of protection "intrinsic safety"

For the classification of the protection type "intrinsic safety", an assessment of simple electrical apparatus to EN 60079-11 and EN 61241-11 must be executed.

As simple electrical apparatus within the meaning of intrinsic safety do not represent a potential source of ignition, the Directive 94/9/EC is not applicable. To demonstrate the intrinsic safety to EN 60079-14, a declaration of the manufacturer therefore can be used.

The devices classified as simple electrical apparatus can be used in the Zones 1 / 2 and 21 / 22.

On the basis of a valid declaration of the manufacturer with an assessment as simple electrical apparatus, the following devices can be used:

Series	Switch	Page
Safety switch	EX-AZ 16-...-3D	22
	EX-AZ 335-...-3D	25
	EX-AZ 355-...-3D	26
	EX-AZ 415-...-3D	28
	EX-AZ 3350-...-3D	30
Position switches	EX-Z/T 235-...-3D	44
	EX-Z/T 335-...-3D	54
Safety sensors	EX-BNS 33-...-3G/D, however without LED	94
	EX-BNS 120-...-3G/D, however without LED	96
	EX-BNS 180-...-3G/D	98
	EX-BNS 303-...-3G/D, however without LED	100
Magnetic reed switches	EX-BN 20-...-3G/D	106
Reset buttons	Ex-RDT	114
	Ex-RDM	114
Emergency stop control devices	Ex-RDRZ45	118

Safety switch with separate actuator




In the class 2 safety switches, the switching element and the actuator are not physically connected, but brought together or separated upon switching. When the safety guard is opened, the actuator is separated from the base unit. During this process, the NC contacts in the safety switch are positively opened and the NO contacts closed.

Content

EX-AZ 16-...-3D	22
EX-AZ 335-...-3D	25
EX-AZ 355-...-3D	26
EX-AZ 415-...-3D	28
EX-AZ 3350-...-3D	30

Safety switch with separate actuator

EX-AZ 16-...-3D




- Ex certified
 - Thermoplastic enclosure
 - Multiple coding
 - Long life
 - Double insulated X
 - 3 cable entries M16
 - Large wiring compartment
 - High level of contact reliability with low voltages and currents
 - Not sensitive to dirty conditions by virtue of patented roller system
 - Slotted holes for adjustment, circular holes for location
 - Including Ex-certified screwed cable gland and screw plug

Technical data


Equipment category:	Ex tD A22 IP67 T90°C X	II 3D
Ex protection:	EN 60947-5-1	
Standards:	EN 61241-0	
	EN 61241-1	
	BG-GS-ET-15	
Enclosure:	glass-fibre reinforced thermoplastic, self-extinguishing	
Max. impact energy:	1 J	
Actuating speed:	max. 1 m/s	
Actuator:	stainless steel 1.4301	
Protection class:	IP67 to EN 60529	
Contact material:	Silver	
Contact type:	change-over contact with double break, type Zb or 3 NC contacts, with galvanically separated contact bridges	
Switching system:	⊖ IEC 60947-5-1 slow action, NC contact with positive break	
Connection:	screw terminals	
Cable section:	max. 2.5 mm ²	
	(incl. conductor ferrules)	
Cable entry:	3 x M16	
U _{imp} :	6 kV	
U _i :	500 V	
I _{the} :	2.5 A	
Utilisation category:	AC-15 DC-13	
I _e /U _e :	2.5 A / 230 VAC	
	2.5 A / 24 VDC	
Max. fuse rating:	4 A gG D-fuse	
Positive break travel:	8 mm	
Positive break force:	10 N for each	
Ambient temperature:	- 20 °C ... + 70 °C	
Mechanical life:	> 1 million operations	
Latching force:	30 N for ordering suffix R	
Cable cross-section of the cable glands:	min. Ø 5 mm max. Ø 10 mm	
	⊖ II 2D	

Contact variants

1 NO / 2 NC



3 NC contacts



Approvals



Ordering details


EX-AZ16-①ZV②K-③-3D

Note

Actuators must be ordered separately.

No.	Option	Description
①	03	3 NC contact
	12	1NO/2NC contacts
②	R	Ejection force
③	2254	Latching force 30 N
	1762	Latching force 5 N
	1637	Front mounting
		Gold-plated contacts

Safety switch with separate actuator



Ordering details

Straight actuator with slot lip-seal	AZ 15/16-B1
with ball latch	AZ 15/16-B1-2024
with centering guide	AZ 15/16-B1-2053
	AZ 15/16-B1-2177

Ordering details

Straight actuator	AZ 15/16-B1-2245
Flexible actuator	AZ 15/16-B2
Flexible actuator	AZ 15/16-B3
Flexible actuator	AZ 15/16-B6

Ordering details


Mounting set	MS AZ 15/16
Slot sealing plug	AZ 15/16-1476
Ball catch	-2053-2
Front mounting with M5 nuts	-1762

Safety switch with separate actuator


System components



Tamperproof screws



EX-certified screwed cable gland



EX-certified screw plug

Ordering details

Tamperproof screws


M5 x 12	101135338
M5 x 16	101135339
M5 x 20	101135340

(Quantity 2 pcs)

EX-certified screwed cable gland	EX-KLE-M16x1,5
EX-certified screw plug	EX-VS-M16x1,5

Safety switch with separate actuator

EX-AZ 335-...-3D



- Ex certified
- Metal enclosure
- 3 contacts
- Long life
- High level of contact reliability with low voltages and currents
- Mounting details to EN 50041
- Actuator heads can be repositioned in steps 4 x 90°
- Can be mounted on a flat surface
- Slotted holes for adjustment, circular holes for location
- 1 Cable entry M20
- Including Ex-certified screwed cable gland

Technical data

Equipment category:	Ex II 3D
Ex protection:	Ex tD A22 IP67 T90°C X
Standards:	EN 60947-5-1 EN 61241-0 EN 61241-1 BG-GS-ET-15
Enclosure:	light-alloy diecast, paint finish
Actuator:	stainless steel 1.4301
Max. impact energy:	4 J
Actuating speed:	max. 1 m/s
Protection class:	IP67 to EN 60529
Contact material:	Silver
Contact type:	change-over with double break Zb, or 3 NC contacts, galvanically separated contact bridges
Switching system:	⊖ IEC 60947-5-1 slow action, NC contact with positive break
Connection:	screw terminals
Cable section:	max. 2.5 mm², min. 0.75 mm² (incl. conductor ferrules)
Cable entry:	M20
U _{imp} :	4 kV
U _i :	250 V
I _{the} :	10 A
Utilisation category:	AC-15, DC-13
I _e /U _e :	4 A / 230 VAC 4 A / 24 VDC 6 A gG D-fuse
Max. fuse rating:	10.7 mm
Positive break travel:	5 N for each
Positive break force:	- 20 °C ... + 60 °C
Ambient temperature:	10 million operations
Mechanical life:	30 N for ordering suffix R
Latching force:	min. Ø 7 mm max. Ø 12 mm
Cable cross-section of the cable glands:	⊖ II 2D

Contact variants

1 NO / 2 NC

13 -> 14
21 -> 22
31 -> 32

3 NC contacts

11 -> 12
21 -> 22
31 -> 32

Approvals




Ordering details

EX-AZ 335-①-**z**②k-③-3D

No.	Option	Description
①	03	3 NC contact
	12	1NO/2NC contacts
②	R	Latching force 5 N
	UE	Latching force 30 N
③	1637	With overlapping contacts Gold-plated contacts

Note




Note

Actuators must be ordered separately.

By turning the head in 90° steps, 8 actuating planes are possible. A Torx T10 screwdriver is required for this purpose.

Safety switch with separate actuator

EX-AZ 355-...-3D



- Ex certified
- Metal enclosure
- 3 contacts
- Long life
- High level of contact reliability with low voltages and currents
- Mounting details to EN 50041
- Actuator heads can be repositioned in steps 4 x 90°
- Can be mounted on a flat surface
- Transverse and longitudinal slotted holes
- 3 cable entries M20
- Including Ex-certified screwed cable gland and screw plug

Technical data

Equipment category:	Ex II 3D
Ex protection:	Ex tD A22 IP67 T90°C X
Standards:	EN 60947-5-1 EN 61241-0 EN 61241-1 BG-GS-ET-15
Enclosure:	light-alloy diecast, paint finish
Actuator:	stainless steel 1.4301
Max. impact energy:	1 J
Actuating speed:	max. 1 m/s
Protection class:	IP67 to EN 60529
Contact material:	Silver
Contact type:	change-over contact with double break, type Zb or 3 NC contacts, with galvanically separated contact bridges
Switching system:	⊖ IEC 60947-5-1 slow action, NC contact with positive break
Connection:	screw terminals
Cable section:	max. 2.5 mm², min. 0.75 mm² (incl. conductor ferrules)
Cable entry:	3 x M20
U_{imp} :	4 kV
U_i :	250 V
I_{the} :	10 A
Utilisation category:	AC-15, DC-13
I_e/U_e :	4 A / 230 VAC; 4 A / 24 VDC 6 A gG D-fuse
Max. fuse rating:	10.7 mm
Positive break travel:	5 N for each
Positive break force:	-20 °C ... +60 °C
Ambient temperature:	10 million operations
Mechanical life:	30 N for ordering suffix R
Latching force:	min. Ø 7 mm max. Ø 12 mm
Cable cross-section of the cable glands:	⊖ II 2D

Contact variants

1 NO / 2 NC

13 - 14
21 - 22
31 - 32

3 NC contacts

11 - 12
21 - 22
31 - 32

Approvals




Ordering details

EX-AZ 355-①-Z②K-③-3D

No.	Option	Description
①	03	3 NC contact
	12	1NO/2NC contacts
②	R	Latching force 5 N
	UE	Latching force 30 N
③	1637	With overlapping contacts Gold-plated contacts

Note




Actuators must be ordered separately.


By turning the head in 90° steps, 8 actuating planes are possible. A Torx T10 screwdriver is required for this purpose.

Safety switch with separate actuator

System components




Straight actuator B1




Flexible actuator B6


System components




Slot sealing plug AZ 335/355-1990




With rubber mountings B1-2245




Flexible actuator B6-Flex




Lockout tag SZ 16/335




Angled actuator B5



EX-certified screwed cable gland



Angled actuator B5-Flex



EX-certified screw plug M20

Ordering details

Straight actuator with rubber mounting	AZ 335/355-B1
Angled actuator	AZ 335/355-B5
Angled actuator	AZ 335/355-B5-Flex

Ordering details

Flexible actuator	AZ 335/355-B6
Flexible actuator	AZ 335/355-B6-Flex


Ordering details

Slot sealing plug	AZ 335/355-1990
Lockout tag	SZ 16/335

EX-certified screwed cable gland	EX-KLE-M20x1.5
EX-certified screw plug	EX-VS-M20x1.5

Safety switch with separate actuator

EX-AZ 415-...-3D



A: setting screw ball latch 30 - 500 N

- Ex certified
- Metal enclosure
- 2 switches with different actuating functions in a single enclosure
- Long life
- High level of contact reliability with low voltages and currents
- Adjustable ball latch to 500 N
- Spring-loaded actuators
- 2 cable entries M20
- Including Ex-certified screwed cable gland and screw plug

Technical data

Equipment category: \textcircled{S} II 3D
Ex protection: Ex tD A22 IP67 T60°C X
Standards: EN 60947-5-1
EN 61241-0
EN 61241-1
BG-GS-ET-15

Enclosure: light-alloy diecast, paint finish
Max. impact energy: 4 J
Actuating speed: max. 1 m/s
Actuator: zinc-plated brass / aluminium
Protection class: IP67 to EN 60529
Contact material: Silver
Contact type: change-over contact with double break, type Zb or 2 NC contacts, with galvanically separated contact bridges

Switching system: \ominus IEC 60947-5-1 slow action, NC contact with positive break


Connection: screw terminals
Cable section: max. 1.5 mm²
min. 0.75 mm²
(incl. conductor ferrules)

Cable entry: 2 x M20
 U_{imp} : 4 kV
 U_i : 250 V
 I_{the} : 6 A
Utilisation category: AC-15, DC-13
 I_e/U_e : 4 A / 230 VAC
4 A / 24 VDC


Max. fuse rating: 6 A gG D-fuse
Positive break travel: 3.8 mm
Positive break force: min. 31 N
Ambient temperature: -10 °C ... +50 °C
Mechanical life: > 1 million operations
Latching force: 30 - 500 N (adjustable)
Cable cross-section of the cable glands: min. Ø 7 mm
max. Ø 12 mm
 \textcircled{S} II 2D

Contact variants


11/11 1 NO contact / 1 NC contact
1 NO contact / 1 NC contact




02/11 2 NC contacts
1 NO contact / 1 NC contact



02/20 2 NO contacts
2 NC contacts



02/02 2 NC contacts
2 NC contacts



Approvals



Ordering details

Ex-AZ 415-①ZPK-②-3D

No. Option Description

①		S1 / S2
11/11	1NO 1NC	/ 1NO 1NC contact
02/11	2NC	/ 1NO 1NC contact
02/20	2NC	/ 2NO contact
02/02	2NC	/ 2NC contact
②	1637	Gold-plated contacts

Note


Actuators must be ordered separately.

Note


Contact symbols shown for the closed condition of the guard device.

Safety switch with separate actuator


System components



Straight actuator B1



EX-certified screwed cable gland





EX-certified screw plug M20

Ordering details


Straight actuator **AZ/AZM 415-B1**

EX-certified
screwed cable gland **EX-KLE-M20x1.5**
EX-certified
screw plug **EX-VS-M20x1.5**

Safety switch with separate actuator

EX-AZ 3350-...-3D


- Ex certified
- Metal enclosure
- Long life
- High level of contact reliability with low voltages and currents
- Shearing force 15,000 N
- Door handle latching
- Lockout tag against unintentional locking available
- Centring device available
- 1 Cable entry M20
- Including Ex-certified screwed cable gland
- Actuating head:




Approvals

Ordering details
EX-AZ 3350-①-②-③-3D

No.	Option	Description
①	03-ZK 12-ZUEK	3 NC contact 1NO/2NC contacts Gold-plated contacts
②	1637	Actuating head
③	U90	90° rotation Door hinge on the left-hand side
	U270	270° rotation Door hinge on the right-hand side

Technical data

Equipment category:	II 3D
Ex protection:	Ex tD A22 IP67 T90°C X
Standards:	EN 60947-5-1 EN 61241-0 EN 61241-1 BG-GS-ET-15
Enclosure:	light-alloy diecast, paint finish
Max. impact energy:	4 J
Actuating speed:	max. 1 m/s
Actuator:	brass, blue chrome-plated
Protection class:	IP67 to EN 60529
Contact material:	Silver
Contact type:	change-over with double break Zb, or 3 NC contacts, galvanically separated contact bridges
Switching system:	IEC 60947-5-1, BG-GS-ET-15, slow action, NC contact with positive break
Connection:	screw terminals
Cable section:	max. 1.5 mm ² (incl. conductor ferrules)
Cable entry:	1 x M20
U _{imp} :	4 kV
U _i :	250 V
I _{the} :	10 A
Utilisation category:	AC-15, DC-13
I _e /U _e :	4 A / 230 V 4 A / 24 VDC 6 A gG D-fuse 10.7 mm
Max. fuse rating:	6 A gG D-fuse 10.7 mm
Positive break travel:	Positive break force: 5 N for each
Positive break force:	Ambient temperature: Mechanical life: Cable cross-section of the cable glands:
Ambient temperature:	1 million operations min. Ø 7 mm max. Ø 12 mm II 2D

EX-AZ 3350-STS30-...

EX-AZ 3350-STS30-02/-04/-05/-07

EX-AZ 3350-STS30-01/-03/-06/-08
Ordering details

The drawings are always shown with a view to the switch.

When the TF. centering device is used, the maximum actuating speed for closing the safety guard is limited to 1 m/s.

Note
Included in delivery

- Mounting plate for safety switch
- Actuator incl. mounting plate
- Emergency handle (For variant -05 and -06 incl. mounting plate)


Ordering example

To order, first choose the desired safety switch and then the door handle system:
for example EX-AZ 3350-12-ZUEK-U90 and EX-AZ 3350-STS30-02


Safety switch with separate actuator

System variants


EX-AZ 3350-STS30-01




EX-AZ 3350-STS30-01




EX-AZ 3350-STS30-03




EX-AZ 3350-STS30-04




EX-AZ 3350-STS30-05



EX-AZ 3350-STS30-06



EX-AZ 3350-STS30-07




EX-AZ 3350-STS30-08




In all images, the guard door opens outwards.


System components




Lockout tag SZ 415-1/-2




EX-certified screwed cable gland



Lockout tag SZ 415-1/-2 -2477



Centring device TF.



Mounting plate MP TG-01

Ordering details

Mounting inside with emergency handle

- | | |
|------------------|----------------------------|
| Door hinge right | EX-AZ 3350-STS30-01 |
| Door hinge left | EX-AZ 3350-STS30-01 |

without emergency handle

- | | |
|------------------|----------------------------|
| Door hinge right | EX-AZ 3350-STS30-03 |
| Door hinge left | EX-AZ 3350-STS30-04 |

Mounting outside with emergency handle

- | | |
|------------------|----------------------------|
| Door hinge right | EX-AZ 3350-STS30-05 |
| Door hinge left | EX-AZ 3350-STS30-06 |

without emergency handle

- | | |
|------------------|----------------------------|
| Door hinge right | EX-AZ 3350-STS30-06 |
| Door hinge left | EX-AZ 3350-STS30-08 |

Ordering details

Lockout tag

- | | |
|-----------------------------|-----------------|
| for ...STS30-01/-03/-06/-08 | SZ 415-1 |
| for ...STS30-02/-04/-05/-07 | SZ 415-2 |

Lockout tag with 5 bore holes

- | | |
|-----------------------------|----------------------|
| for ...STS30-01/-03/-06/-08 | SZ 415-1-2177 |
| for ...STS30-02/-04/-05/-07 | SZ 415-2-2177 |

Centering device:

- | | |
|------------------|----------------|
| Mounting outside | TFA-010 |
|------------------|----------------|

- | | |
|-----------------|----------------|
| Mounting inside | TFI-010 |
|-----------------|----------------|

For product information and dimensions,
please refer to the Main Catalogue "Safety
Technology".

- | | |
|----------------|-----------------|
| Mounting plate | MP TG-01 |
|----------------|-----------------|

Ordering details

- EX-certified
screwed cable gland

EX-KLE-M20x1.5

More Details



Detailed technical information at:
www.schmersal.com

Solenoid interlocks




In the solenoid interlocks of the EX-AZM series, the switching element with interlocking device and the actuator are not physically connected, but brought together or separated upon switching. When the safety guard is opened in the unlocked condition, the actuator is separated from the base unit. During this process, the NC contacts are positively opened and the NO contacts closed. Interlocking is carried out by means of a blocking bolt / latching bolt. This latching bolt blocks the actuator so that it cannot be withdrawn from the interlock. The machine control is only enabled when the actuator has been inserted into the interlock and the latching bolt is in the blocking position. This is ensured by the contact monitoring of the latching bolt.

Content

EX-AZM 170-...-3G/D	34
EX-AZM 161-...-3D	36
EX-AZM 415-...-3D	40

Solenoid interlocks

EX-AZM 170-...-3G/D




- Ex certified
- Interlock with protection against incorrect locking
- Thermoplastic enclosure
- **cut clamp terminals**
- Compact design
- Manual release
- Long life
- Double insulated
- High holding force 1000 N
- Latching force 5 N or 30 N
- Power to unlock / Power to lock
- Individual coding available on request
- 1 cable entry M20
- Including Ex-certified screwed cable gland

Technical data


Equipment category:	Ex nC IIC T5 X
Ex protection:	Ex tD A22 IP67 T80°C X
Standards:	EN 60947-5-1 EN 61241-0 EN 61241-1 EN 60079-0 EN 60079-15 BG-GS-ET-19
Enclosure:	glass-fibre reinforced thermoplastic, self-extinguishing
Max. impact energy:	1 J
Actuating speed:	max. 1 m/s
Actuator and locking bolt:	stainless steel 1.4301
Protection class:	IP67 to EN 60529
Contact material:	Silver
Contact type:	change-over contact with double break, type Zb or 2 NC contacts, with galvanically separated contact bridges
Switching system:	⊕ EN 60947-5-1, slow action, positive break NC contact cut clamp terminals
Connection:	Cable section: 0.75 – 1.0 mm ² , flexible
U _{imp} :	4 kV
U _i :	250 V
I _{the} :	2 A
Utilisation category:	AC-15, DC-13
I _e /U _e :	2 A / 230 VAC 2 A / 24 VDC 2 A gG D-fuse
Max. fuse rating:	11 mm
Positive break travel:	6 N for each NC contact fitted
Positive break force:	Magnet: 100% ED U _s : 24 VAC/DC Power consumption: max. 10 W
	Ambient temperature: -15 °C ... +45 °C
	Mechanical life: > 1 million operations
F _{max} :	1000 N
Latching force:	30 N for ordering suffix R
Cable cross-section of the cable glands:	min. Ø 6.5 mm max. Ø 12 mm
	⊕ II 2D

Contact variants


Power to unlock 1 NO / 1 NC




2 NC contacts



Power to lock 1 NO / 1 NC



2 NC contacts



Approvals




Ordering details

EX-AZM 170-①Z②K③-24VAC/DC-④-3G/D

No.	Option	Description
①	11	1NO/1NC contacts
	02	2 NC contact
②	R	Latching force 5 N
		Latching force 30 N
③	A	Power to unlock
		Power to lock
④	1637	Manual release
		Gold-plated contacts

Note



Manual release (left)

- For manual release using M5 triangular key, available as accessory
- Included in standard version

Note

The contact 21-32 is actuated when A1-A2 is energised or de-energised.

At least one magnetic contact with positive break ⊕ must be integrated in the safety circuit.


Circuit diagrams show the de-energised condition with actuator inserted (0 in switch travel diagram).

Interlocks with the power to lock principle may only be used in special cases after a thorough evaluation of the accident risk, since the guarding device can immediately be opened on failure of the electrical power supply or when the main switch is opened.

Actuators must be ordered separately.


Solenoid interlocks

System components




Straight actuator B1

System components




Long straight actuator B11


System components




EX-certified screwed cable gland




With rubber mounting B1-2245



Long angled actuator B15



Angled actuator B5



Flexible actuator B6

Ordering details

Straight actuator with rubber mountings	AZ 17/170-B1
Angled actuator	AZ 17/170-B5
Flexible actuator	AZM 170-B6

Ordering details


Long straight actuator	AZ 17/170-B11
Long angled actuator	AZ 17/170-B15

Ordering details

EX-certified screwed cable gland	EX-KLE-M20x1.5
-------------------------------------	-----------------------

Solenoid interlocks

EX-AZM 161-...-3D



- Ex certified
- Interlock with protection against incorrect locking
- Thermoplastic enclosure
- 6 contacts
- Manual release
- Long life
- Double insulated
- High holding force 2000 N
- Large wiring compartment
- Power to unlock / Power to lock
- Cage clamps or screw terminals
- 4 cable entries M16
- Including Ex-certified screwed cable gland


Technical data

Equipment category:	II 3D
Ex protection:	Ex tD A22 IP67 T80°C X
Standards:	EN 60947-5-1 EN 61241-0 EN 61241-1 BG-GS-ET-19
Enclosure:	glass-fibre reinforced thermoplastic, self-extinguishing
Actuator and locking bolt:	stainless steel 1.4301
Protective cover:	Steel painted
Max. impact energy:	1 J 7 J (with AZM 161-ME) max. 1 m/s
Actuating speed:	7 J (with AZM 161-ME) max. 1 m/s
Protection class:	IP67
Contact material:	Silver
Contact type:	change-over contact with double break, type Zb, with galvanically separated contact bridges
Switching system:	EN 60947-5-1, slow action, positive break NC contact
Connection:	screw terminals or cage clamps max. 1.5 mm ² (incl. conductor ferrules)
Cable section:	4x M16
Cable entry:	U _{imp} : 4 kV U _i : 250 V I _{the} : 5 A
Utilisation category:	AC-15, DC-13
I _e /U _e :	4 A / 230 VAC 2.5 A / 24 VDC 6 A gG D-fuse
Max. fuse rating:	9.5 mm
Positive break travel:	10 N for each NC contact fitted
Positive break force:	24 VAC/DC 100% ED max. 10 W
U _s :	-15 °C ... +50 °C
Magnet:	max. 10 W
Power consumption:	> 1 million operations
Ambient temperature:	2000 N
Mechanical life:	30 N for ordering suffix R
F _{max} :	min. Ø 5 mm max. Ø 10 mm
Latching force:	Ø II 2D
Cable cross-section of the cable glands:	

Contact variants


2 NO contact / 4 NC contacts (12/12)

Power to unlock



13	14	21	22	41	42	51	52	63	64	71	72	A1	A2
----	----	----	----	----	----	----	----	----	----	----	----	----	----

Power to lock



13	14	21	22	41	42	51	52	63	64	71	72	A1	A2
----	----	----	----	----	----	----	----	----	----	----	----	----	----

Approvals




Ordering details

EX-AZM 161 ①-12/12-②K③-024-3D

No.	Option	Description
①	SK	Screw terminals
	CC	Cage clamps
②	R	Latching force 5 N
		Latching force 30 N
③	R	Power to unlock
	A	Power to lock

Note



Manual release

- For manual release using M5 triangular key, available as accessory
- For Maintenance purposes only.

Note

At least one magnetic contact with positive break ⊖ must be integrated in the safety circuit.


Contact variants are shown in the de-energised condition with the actuator inserted (0 in switch travel diagram).

Interlocks with the power to lock principle may only be used in special cases after a thorough evaluation of the accident risk, since the guarding device can immediately be opened on failure of the electrical power supply or when the main switch is opened.

Actuators and protective cover must be ordered separately.


Solenoid interlocks

System components




Straight actuator B1

System components




Actuator B1-2024 with slot lip-seal


System components




Shortened straight actuator B1S




Straight actuator B1E




Actuator B1-2053 with ball latch




Shortened straight actuator B1ES




Straight actuator B1F




Actuator B1-2177 with centering guide



Shortened angled actuator B6S



Flexible actuator B6



Actuator B6-2177 with centering guide

Ordering details

Straight actuator	AZM 161-B1
Straight actuator	AZM 161-B1E
Straight actuator	AZM 161-B1F
Flexible actuator	AZM 161-B6

Ordering details


Straight actuator with slot lip-seal	AZM 161-B1-2024
with ball latch	AZM 161-B1-2053
with centering guide	AZM 161-B1-2177
Flexible actuator with centering guide	AZM 161-B6-2177

Ordering details

Shortened straight actuator	AZM 161-B1S
Shortened straight actuator	AZM 161-B1ES
Shortened angled actuator	AZM 161-B6S


Solenoid interlocks

System components




Mounting set MS AZM 161 P


System components




Protective cover AZM 161-ME



Slot sealing plug AZM 161



EX-certified screwed cable gland



EX-certified screw plug

Ordering details

Mounting set	MS AZM 161 P
	MS AZM 161 R/P
Slot sealing plug AZM 161	101145379
Tamperproof screws with unidirectional slots (without drawing)	
M5 x 12	101135338
M5 x 16	101135339
M5 x 20	101135340
(Quantity 2 pcs)	
EX-certified	
screwed cable gland	EX-KLE-M16x1,5
EX-certified	
screw plug	EX-VS-M16x1,5

Ordering details

Protective cover	AZM 161-ME
------------------	-------------------


Download now



Data sheets, mounting and wiring instructions,
declaration of conformity and other information at:
www.schmersal.com

Solenoid interlocks

EX-AZM 415-...-3D



A: setting screw ball latch 30 - 400 N


- Ex certified
- Interlock with protection against incorrect locking
- Metal enclosure
- Two switches in one enclosure
- Problem-free opening of stressed doors by means of bell-crank system
- Robust design
- Long life
- High holding force 3500 N
- Adjustable ball latch to 400 N
- Power to unlock / Power to lock
- 2 cable entries M20
- Including Ex-certified screwed cable gland and screw plug

Technical data


Equipment category:	Ex II 3D
Ex protection:	Ex tD A22 IP67 T90°C X
Standards:	EN 60947-5-1 EN 61241-0 EN 61241-1 BG-GS-ET-19
Enclosure:	light-alloy die-cast, enamel finish
Max. impact energy:	4 J
Actuating speed:	max. 1 m/s
Actuator:	zinc-plated brass/aluminium
Protection class:	IP67 to EN 60529
Contact material:	Silver
Contact type:	change-over contact with double break, type Zb, with galvanically separated contact bridges ⊕ EN 60947-5-1, slow action, positive break NC contact
Switching system:	Screw terminals max. 2.5 mm ² (incl. conductor ferrules)
Connection:	2 x M20 4 kV 250 V 6 A AC-15
Cable section:	4 A / 230 VAC 6 A gG D-fuse
Cable entry:	Positive break travel: 5 mm
U _{imp} :	Positive break force: min. 15 N (depending on the setting of the ball latch)
U _i :	Magnet: 100% ED
I _{the} :	24 VAC/DC max. 10 W
Utilisation category:	Ambient temperature: - 10 °C ... + 50 °C
I _e /U _e :	Mechanical life: > 1 million operations
Max. fuse rating:	F _{max} : 3500 N
Positive break travel:	Latching force: 30 - 400 N (adjustable)
Positive break force:	Cable cross-section of the cable glands: min. Ø 7 mm max. Ø 12 mm
Magnet:	⊕ II 2D
U _s :	
Power consumption:	
Ambient temperature:	
Mechanical life:	
F _{max} :	
Latching force:	
Cable cross-section of the cable glands:	

Contact variants


Power to unlock 11/11 2NC/2NO




02/11 3NC/1NO



02/02 4NC



02/20 2NC/2NO



Approvals



Ordering details

EX-AZM 415-①ZPK③-24VAC/DC-3D

No.	Option	Description
①	11/11	2NC/2NO
	02/11	3NC/1NO
	02/20	2NC/2NO
	02/02	4NC
②	Power to unlock	
	A	Power to lock
③	1637	Gold-plated contacts

Note

Actuators must be ordered separately.

Note

Contact symbols are shown for the closed condition of the guard device.

The contacts 11-12 and 23-24 are actuated when the solenoid A1-A2 is energised or de-energised.


At least one magnetic contact with positive break ⊕ must be integrated in the safety circuit.

Solenoid interlocks


Contact variants

Power to lock


11/11 2NC/2NO




02/11 3NC/1NO




02/02 4NC




02/20 2NC/2NO




System components



Straight actuator B1



EX-certified screwed cable gland



EX-certified screw plug M20

Note

Interlocks with the power to lock principle may only be used in special cases after a thorough evaluation of the accident risk, since the guarding device can immediately be opened on failure of the electrical power supply or when the main switch is opened.

Ordering details

Straight actuator

AZ/AZM 415-B1

EX-certified

screwed cable gland

EX-KLE-M20x1.5

EX-certified

screw plug

EX-VS-M20x1.5

More Details



Detailed technical information at:
www.schmersal.com

Position switches with safety function



The position switches with safety function are suitable for sliding and hinged guards, which need to be closed in order to ensure the required operational safety.

Content

EX-Z/T 235-...-3D	44
EX-Z/T 335-...-3G/D	54
EX-Z/T 355-...-3G/D	55
EX-MAF 330-...-3D	60
EX-T 335-...	62
EX-T/M 441-...	68
EX-T/M 250-...	69
EX-TS 064-...	70
EX-MS 064-...	71
EX-T. 064-...	73
EX-M. 064 R	74
EX-M. 064 L	75

Position switches with safety function


EX-Z/T 235-....-3D




Technical data

Equipment category:	Ex II 3D
Ex protection:	Ex tD A22 IP67 T90°C X
Standards:	EN 60947-5-1 EN 61241-0 EN 61241-1 BG-GS-ET-15
Design:	fixings to EN 50047
Enclosure:	zinc die-cast, enamel finish
Max. impact energy:	1 J
Actuating speed:	max. 1 m/s
Protection class:	IP67 to EN 60529
Contact material:	Silver
Contact type:	change-over contact with double break, type Zb or 2 NC contacts, with galvanically separated contact bridges
Switching system:	⊖ IEC 60947-5-1 slow or snap action, NC contacts with positive break
Connection:	screw terminals
Cable section:	max. 2.5 mm ² , min. 0.75 mm ² (including conductor ferrules)
Cable entry:	M20
U _{imp} :	6 kV
U _i :	500 V
I _{the} :	6 A
Utilisation category:	AC-15, DC-13
I _e /U _e :	4 A / 230 VAC 1 A / 24 VDC
Max. fuse rating:	6 A gG D-fuse
Ambient temperature:	-20 °C ... +60 °C
Mechanical life:	20 million operations
Switching frequency:	max. 5000/h
Bounce duration:	Snap action: < 3 ms; Slow action: in accordance with the actuating speed
Switchover time:	Snap action: > 5.5 ms; Slow action: in accordance with the actuating speed
Cable cross-section of the cable glands:	min. Ø 7 mm max. Ø 12 mm Ex II 2D

System components



EX-certified screwed cable gland



- Ex certified
- Mounting details to EN 50047
- Metal enclosure
- Available with 2 positive break NC contacts
- Snap action with constant contact pressure up to switching point
- Slow action available with overlapping or staggered contacts
- Wiring compartment
- Wide range of alternative actuators
- Actuator heads can be repositioned by 4 x 90°
- Angle of roller lever adjustable in 10° steps
- Good resistance to oil and petroleum spirit
- Metal roller available on request
- 1 cable entry M20
- incl. Ex-certified cable gland

Approvals



Ordering details

EX-①② 235-③Z④-⑤-⑥-⑦-3D

No.	Option	Description
①	Z	Snap action ⊖
	T	Slow action ⊖
②		For the appropriate actuator: see page 47
③	02	2 NC contacts
	11	1 NO contact / 1 NC contact
	20	2 NO contacts
④	H	Slow action with staggered contacts
	UE	with overlapping contacts
⑤	1297	Enclosure with transverse slotted holes
⑥	2138	Roller lever 7H for safety duties
⑦	1637	Gold-plated contacts

Ordering details

* Switches with 2 NO contacts are only suitable for positioning tasks!


Ordering details

Ex-certified
screwed cable gland

EX-KLE-M20x1.5

Position switches with safety function

Plunger S




- Actuator type B to EN 50047
- Actuating force: Min. 9 N
- Positive break force: 19 N
- Actuating speed with actuating angle 0° to switch axis
Snap action: Min. 10 mm/min, max. 1 m/s
Slow action: Min. 60 mm/min, max. 1 m/s

Contact variants

Contacts/ Switch travel	Snap action	Slow action	Slow action with overlapping contacts	Slow action with staggered contacts
1 NO / 1 NC	EX-ZS 235-11Z-3D	EX-TS 235-11Z-3D	EX-TS 235-11ZUE-3D	
2 NC	EX-ZS 235-02Z-3D	EX-TS 235-02Z-3D		EX-TS 235-02ZH-3D
2 NO		EX-TS 235-20Z-3D		EX-TS 235-20ZH-3D

Roller plunger R




- Actuator type C to EN 50047
- Actuating force: Min. 9 N
- Positive break force: 19 N
- Actuating speed with actuating angle 30° to switch axis
Snap action: Min. 20 mm/min, max. 1 m/s
Slow action: Min. 120 mm/min, max. 1 m/s

Contact variants

Contacts/ Switch travel	Snap action	Slow action	Slow action with overlapping contacts	Slow action with staggered contacts
1 NO / 1 NC	EX-ZR 235-11Z-3D	EX-TR 235-11Z-3D	EX-TR 235-11ZUE-3D	
2 NC	EX-ZR 235-02Z-3D	EX-TR 235-02Z-3D		EX-TR 235-02ZH-3D
2 NO		EX-TR 235-20Z-3D		EX-TR 235-20ZH-3D

Position switches with safety function

Plunger 4S




- Actuating force: Min. 9 N
- Positive break force: 19 N
- Actuating speed with actuating angle 0° to switch axis
- Snap action: Min. 10 mm/min, max. 1 m/s
- Slow action: Min. 60 mm/min, max. 1 m/s

Contact variants

Contacts/ Switch travel	Snap action	Slow action	Slow action with overlapping contacts	Slow action with staggered contacts
1 NO / 1 NC	EX-Z4S 235-11Z-3D	EX-T4S 235-11Z-3D	EX-T4S 235-11ZUE-3D	
2 NC	EX-Z4S 235-02Z-3D	EX-T4S 235-02Z-3D		EX-T4S 235-02ZH-3D
2 NO		EX-T4S 235-20Z-3D		EX-T4S 235-20ZH-3D

Roller plunger 4R




- Actuating force: Min. 9 N
- Positive break force: 19 N
- Actuating speed with actuating angle 30° to switch axis
- Snap action: Min. 20 mm/min, max. 1 m/s
- Slow action: Min. 120 mm/min, max. 1 m/s

Contact variants

Contacts/ Switch travel	Snap action	Slow action	Slow action with overlapping contacts	Slow action with staggered contacts
1 NO / 1 NC	EX-Z4R 235-11Z-3D	EX-T4R 235-11Z-3D	EX-T4R 235-11ZUE-3D	
2 NC	EX-Z4R 235-02Z-3D	EX-T4R 235-02Z-3D		EX-T4R 235-02ZH-3D
2 NO		EX-T4R 235-20Z-3D		EX-T4R 235-20ZH-3D

Position switches with safety function

Offset roller lever 1R




- Actuating force: Min. 9 N
 - Positive break force: 19 N
 - Actuating speed with actuating angle 30° to switch axis
- Snap action: Min. 27 mm/min, max. 1 m/s
Slow action: Min. 160 mm/min, max. 1 m/s

Contact variants

Contacts/ Switch travel	Snap action	Slow action	Slow action with overlapping contacts
1 NO / 1 NC	EX-Z1R 235-11Z-3D	EX-T1R 235-11Z-3D	EX-T1R 235-11ZUE-3D
2 NC	EX-Z1R 235-02z-3D	EX-T1R 235-02Z-3D	
2 NO		EX-T1R 235-20Z-3D	

Offset roller lever K




- Actuator type E to EN 50047
 - Actuating force: Min. 9 N
 - Positive break force: 19 N
 - Actuating speed with actuating angle 30° to switch axis
- Snap action: Min. 24 mm/min, max. 1 m/s
Slow action: Min. 240 mm/min, max. 1 m/s

Contact variants

Contacts/ Switch travel	Snap action	Slow action	Slow action with overlapping contacts	Slow action with staggered contacts
1 NO / 1 NC	EX-ZK 235-11Z-3D	EX-TK 235-11Z-3D	EX-TK 235-11ZUE-3D	
2 NC	EX-ZK 235-02Z-3D	EX-TK 235-02Z-3D		EX-TK 235-02ZH-3D
2 NO		EX-TK 235-20Z-3D		EX-TK 235-20ZH-3D

Position switches with safety function

Angle roller lever 3K




- Actuating force: Min. 9 N
- Positive break force: 19 N
- Actuating speed with actuating angle 30° to switch axis
Snap action: Min. 27 mm/min, max. 1 m/s
Slow action: Min. 160 mm/min, max. 1 m/s
- Actuation from bottom parallel to the switch, therefore only suitable for small housings (Z/T 235 and Z/T 236)

Contact variants

Contacts/ Switch travel	Snap action	Slow action	Slow action with overlapping contacts	Slow action with staggered contacts
1 NO / 1 NC	EX-Z3K 235-11Z-3D	EX-T3K 235-11Z-3D	EX-T3K 235-11ZUE-3D	
2 NC	EX-Z3K 235-02Z-3D	EX-T3K 235-02Z-3D		EX-T3K 235-02ZH-3D
2 NO		EX-T3K 235-20Z-3D		EX-T3K 235-20ZH-3D

Angle roller lever 4K




- Actuating force: Min. 6 N
- Positive break force: 16 N
- Actuating speed with actuating angle 30° to switch axis
Snap action: Min. 44 mm/min, max. 1 m/s
Slow action: Min. 264 mm/min, max. 1 m/s
- Actuation from bottom parallel to the switch, therefore only suitable for small housings (Z/T 235 and Z/T 236)

Contact variants

Contacts/ Switch travel	Snap action	Slow action	Slow action with overlapping contacts	Slow action with staggered contacts
1 NO / 1 NC	EX-Z4K 235-11Z-3D	EX-T4K 235-11Z-3D	EX-T4K 235-11ZUE-3D	
2 NC	EX-Z4K 235-02Z-3D	EX-T4K 235-02Z-3D		EX-T4K 235-02ZH-3D
2 NO		EX-T4K 235-20Z-3D		EX-T4K 235-20ZH-3D

Position switches with safety function

Angle roller lever K4




- Actuating force: Min. 6 N
- Positive break force: 16 N
- Actuating speed with actuating angle 30° to switch axis
- Snap action: Min. 56 mm/min, max. 1 m/s
- Slow action: Min. 336 mm/min, max. 1 m/s

Contact variants

Contacts/ Switch travel	Snap action	Slow action	Slow action with overlapping contacts	Slow action with staggered contacts
1 NO / 1 NC	EX-ZK4 235-11Z-3D	EX-TK4 235-11Z-3D	EX-TK4 235-11ZUE-3D	
2 NC	EX-ZK4 235-02Z-3D	EX-TK4 235-02Z-3D		EX-TK4 235-02ZH-3D
2 NO			EX-TK4 235-20Z-3D	EX-TK4 235-20ZH-3D

Roller lever 1H




- Plastic lever
- Actuator type A to EN 50047
- Angle of roller lever adjustable in 10° steps
- Actuating torque: Min. 15 Ncm
- Positive break torque: 18.5 Ncm
- Actuating speed with actuating angle 30° to switch axis
- Snap action: Min. 92 mm/min, max. 1 m/s
- Slow action: Min. 492 mm/min, max. 1 m/s
- Actuator head gasket, ordering suffix -Z

Contact variants

Contacts/ Switch travel	Snap action	Slow action	Slow action with overlapping contacts	Slow action with staggered contacts
1 NO / 1 NC	EX-ZV1H 235-11Z-3D	EX-TV1H 235-11Z-3D	EX-TV1H 235-11ZUE-3D	
2 NC	EX-ZV1H 235-02Z-3D	EX-TV1H 235-02Z-3D		EX-TV1H 235-02ZH-3D
2 NO			EX-TV1H 235-20Z-3D	EX-TV1H 235-20ZH-3D

Position switches with safety function

Roller lever 7H




• only for positioning tasks

- Angle of roller lever adjustable in 10° steps
- Actuating torque: Min. 15 Ncm
- Actuating speed with actuating angle 30° to switch axis
Snap action: Min. 240 mm/min, max. 1 m/s
Slow action: Min. 1440 mm/min, max. 1 m/s
- Actuator head gasket, ordering suffix -Z

Contact variants

Contacts/ Switch travel	Snap action	Slow action	Slow action with overlapping contacts	Slow action with staggered contacts
1 NO / 1 NC	EX-ZV7H 235-11Z-3D	EX-TV7H 235-11Z-3D	EX-TV7H 235-11ZUE-3D	
2 NC	EX-ZV7H 235-02Z-3D	EX-TV7H 235-02Z-3D		EX-TV7H 235-02ZH-3D
2 NO		EX-TV7H 235-20Z-3D		EX-TV7H 235-20ZH-3D

7H-2138




- Angle of roller lever adjustable in 10° steps
- Actuating torque: Min. 15 Ncm
- Positive break torque: 18.5 Ncm
- Actuating speed with actuating angle 30° to switch axis
Snap action: Min. 240 mm/min, max. 1 m/s
Slow action: Min. 1440 mm/min, max. 1 m/s
- Actuator head gasket, ordering suffix -Z

Contact variants

Contacts/ Switch travel	Snap action	Slow action	Slow action with overlapping contacts	Slow action with staggered contacts
1 NO / 1 NC	EX-ZV7H 235-11Z-2138-3D	EX-TV7H 235-11Z-2138-3D	EX-TV7H 235-11ZUE-2138-3D	
2 NC	EX-ZV7H 235-02Z-2138-3D	EX-TV7H 235-02Z-2138-3D		EX-TV7H 235-02ZH-2138-3D
2 NO		EX-TV7H 235-20Z-2138-3D		EX-TV7H 235-20ZH-2138-3D

Position switches with safety function

Rod lever 10H




• only for positioning tasks

- Angle of roller lever adjustable in 10° steps
- Plastic rod
- Actuating torque: Min. 15 Ncm
- Actuating speed with actuating angle 30° to switch axis
- Snap action: Min. 687 mm/min, max. 1 m/s
- Slow action: Min. 4122 mm/min, max. 1 m/s
- Actuator head gasket, ordering suffix -Z
- Aluminium rod, ordering suffix -1183

Contact variants

Contacts/ Switch travel	Snap action	Slow action	Slow action with overlapping contacts	Slow action with staggered contacts
1 NO / 1 NC	EX-ZV10H 235-11Z-3D	EX-TV10H 235-11Z-3D	EX-TV10H 235-11ZUE-3D	
2 NC	EX-ZV10H 235-02Z-3D	EX-TV10H 235-02Z-3D		EX-TV10H 235-02ZH-3D
2 NO			EX-TV10H 235-20Z-3D	EX-TV10H 235-20ZH-3D

Roller lever 12H



- Metal lever with plastic roller
- Actuator type A to EN 50047
- Angle of roller lever adjustable in 10° steps
- Actuating torque: Min. 15 Ncm
- Positive break torque: 18.5 Ncm
- Actuating speed with actuating angle 30° to switch axis
- Snap action: Min. 687 mm/min, max. 1 m/s
- Slow action: Min. 4122 mm/min, max. 1 m/s
- Actuator head gasket, ordering suffix -Z
- Available with metal roller, ordering suffix -RMS

Contact variants

Contacts/ Switch travel	Snap action	Slow action	Slow action with overlapping contacts	Slow action with staggered contacts
1 NO / 1 NC	EX-ZV12H 235-11Z-3D	EX-TV12H 235-11Z-3D	EX-TV12H 235-11ZUE-3D	
2 NC	EX-ZV12H 235-02Z-3D	EX-TV12H 235-02Z-3D		EX-TV12H 235-02ZH-3D
2 NO			EX-TV12H 235-20Z-3D	EX-TV12H 235-20ZH-3D

Position switches with safety function

Roller lever 14H		Contact variants			
Contacts/ Switch travel	Snap action	Slow action	Slow action with overlapping contacts	Slow action with staggered contacts	
1 NO / 1 NC	EX-ZV14H 235-11Z-3D	EX-TV14H 235-11Z-3D	EX-TV14H 235-11ZUE-3D		
2 NC	EX-ZV14H 235-02Z-3D	EX-TV14H 235-02Z-3D		EX-TV14H 235-02ZH-3D	
2 NO		EX-TV14H 235-20Z-3D		EX-TV14H 235-20ZH-3D	

- Metal lever with plastic roller
- Angle of roller lever adjustable in 10° steps
- Actuating torque: Min. 15 Ncm
- Positive break torque: 18.5 Ncm
- Actuating speed with actuating angle 30° to switch axis
- Snap action: Min. 687 mm/min, max. 1 m/s
- Slow action: Min. 4122 mm/min, max. 1 m/s
- Actuator head gasket, ordering suffix -Z
- Available with metal roller, ordering suffix -RMS

More Details

Datenblatt - SLB 400-E50-21P Sender - 1138898 - eclass 27272701 27-27-27-01 - Windows Internet Explorer

http://www.schmersal.net/cst?lang=de&produkt=gbk733230uwfvpg5gb45529cyfvb8

Datei Bearbeiten Ansicht Favoriten Extras 2

Datenblatt - SLB 400-E50-21P Sender - 1138898 - ed... Seite Extras

Sicheres Schalten und Erfassen Sicherere Signalverarbeitung Automatisierungstechnik Ex-Schaltgeräte Aufzugsschaltgeräte Weitere Produkte und Programmergänzungen

Home > Sicherheits-Lichtschranken > SLB 400 > SLB 400-E50-21P Sender

SLB 400-E50-21P Sender

Daten Dokumente CAD Abbildungen

Bestelldaten

Produkt-Typbezeichnung	SLB 400-E50-21P Sender
Artikelnummer	1138898
EAN Code	4030661281544

Zulassung

Zulassung	BG
-----------	----

Allgemeine Daten

Produkt-Name	SLB 400
Vorschriften	ECEN 61496
Richtlinienkonformität (J/N)	CE
Betriebsmittel-Schutzklasse	Ja
Sicherheitstyp gemäß IEC 61496-1	keine
Werkstoffe	
- Werkstoff des Gehäuses	Kunststoff
Gewicht	42 g
Reichweite des Schutzfeldes	15000 mm
min. Objektgröße	Ø 13 mm
Reaktionszeit	25 ms (Nur in Verbindung mit einem Sicherheitsbaustein)
Wellenlänge des Sensors	880 nm
Abstrahlwinkel	± 2°

Fertig


Produkt hierarchie

- Sicheres Schalten und Erfassen
 - Sicherheitsschalter mit getrenntem Betätiger
 - Sicherheitszuhaltung
 - Positionsschalter
 - Sicherheitsschalter für drehbare Schutzeinrichtungen
 - Sicherheits-Sensoren
 - Selzugs-Notschalter
 - NOT-HALT-Taste
 - Sicherheitsgerichteter Laserscanner
 - Sicherheits-Lichtschranken
 - SLB 200
 - SLB 400
 - SLB 400-E50-21P Sender
 - SLB 400-R50-21P Empfänger
 - Zubehör
 - Sicherheitsbausteine zur Überwachung von Sicherheits-Lichtschranken
 - Sicherheits-Lichtvorhänge, Sicherheits-Lichtgitter
 - Zweihandbedienelemente
 - Türgriffschalter
 - Zustimmungsschalter
 - Sicherheitsgerichteter taktiler Sensor
 - Fußschalter
 - AS-Interface Safety at Work

Detailed technical information at:
www.schmersal.net

Position switches with safety function

EX-Z/T 335-....-3G/D




- Ex certified
- Mounting details to EN 50041
- Metal enclosure
- Snap action with constant contact pressure up to switching point
- Slow or snap action available with 2 positive break NC contacts to EN 60947-5-1
- Slow action available with overlapping or staggered contacts
- Wide range of alternative actuators
- Actuator heads can be repositioned by 4 x 90°
- Angle of roller lever adjustable in 10° steps
- Good resistance to oil and petroleum spirit
- 1 cable entry M20
- incl. Ex-certified cable gland

Technical data

Equipment category:	Ex II 3GD
Ex protection:	Ex nC IIC T5 X
Standards:	Ex tD A22 IP67 T90°C X EN 60947-5-1 EN 61241-0 EN 61241-1 EN 60079-0 EN 60079-15 BG-GS-ET-15 DIN EN 50041
Design:	light-alloy diecast, paint finish
Enclosure:	
Max. impact energy:	4 J
Actuating speed:	max. 1 m/s
Protection class:	IP67 to EN 60529
Contact material:	Silver
Contact type:	Change-over contact with double break, type Zb or 2 NC contacts, with galvanically separated contact bridges
Switching system:	⊖ EN 60947-5-1, slow action or snap action, positive break NC contact
Connection:	screw terminals
Cable section:	max. 2.5 mm ² (including conductor ferrules)
Cable entry:	M20
U_{imp} :	6 kV
U_i :	-03Z, -12Z: 4kV 500 V
I_{the} :	10 A
Utilisation category:	AC-15, DC-13
I_e/U_e :	4 A / 230 VAC 4 A / 24VDC
Max. fuse rating:	6 A gG D-fuse
Ambient temperature:	-20 °C ... +60 °C
Mechanical life:	30 million operations
Switching frequency:	max. 5000/h
Bounce duration:	Snap action: in accordance with actuating speed; Slow action: < 2ms
Switchover time:	Snap action: < 2 ms; Slow action: in accordance with actuating speed
Cable cross-section of the cable glands:	min. Ø 7 mm max. Ø 12 mm
	⊖ II 2D

System components



EX-certified screwed cable gland

Approvals



Ordering details

EX-①② 335-③Z④-⑤-⑥-⑦-3G/D

No.	Option	Description
①	Z	Snap action ⊖
	T	Slow action ⊖
②	For the appropriate actuator: see page 58	
③	11	1 NO contact / 1 NC contact
	02	2 NC contacts
	20	2 NO contacts*
01/01		1 NC contact to the left/ 1 NC contact to the right
12		1 NO contact / 2 NC contacts
03		3 NC contacts
④	H	Slow action with staggered contacts
	UE	with overlapping contacts

No.	Option	Description
⑤	1297	Enclosure with transverse slotted holes
⑥	2138	Roller lever 7H for safety duties
⑦	1637	Gold-plated contacts

* Switches with 2 NO contacts are only suitable for positioning tasks!


Ordering details

EX-certified
screwed cable gland

EX-KLE-M20x1.5

Position switches with safety function

EX-Z/T 355-....-3G/D



- Ex certified
- Mounting details to EN 50041
- Metal enclosure
- Snap action with constant contact pressure up to switching point
- Slow or snap action available with 2 positive break NC contacts to EN 60947-5-1
- Slow action available with overlapping or staggered contacts
- Wide range of alternative actuators
- Actuator heads can be repositioned by 4 x 90°
- Angle of roller lever adjustable in 10° steps
- Good resistance to oil and petroleum spirit
- 3 cable entries M20
- Including EX-certified screwed cable gland

Approvals



Ordering details


EX-①② 355-③Z④-⑤-⑥-⑦-3G/D

No.	Option	Description
①	Z	Snap action ⊖
	T	Slow action ⊖
②	For the appropriate actuator: see page 58	
③	11	1 NO contact / 1 NC contact
	02	2 NC contacts
	20	2 NO contacts*
	01/01	1 NC contact to the left/ 1 NC contact to the right
	12	1 NO contact / 2 NC contacts
	03	3 NC contacts
④	H	Slow action with staggered contacts
	UE	with overlapping contacts


Technical data

Equipment category:	Ex II 3GD
Ex protection:	Ex nC IIC T5 X
Standards:	Ex tD A22 IP67 T90°C X EN 60947-5-1 EN 61241-0 EN 61241-1 EN 60079-0 EN 60079-15 BG-GS-ET-15 DIN EN 50041
Design:	
Enclosure:	light-alloy diecast, paint finish
Max. impact energy:	1 J
Actuating speed:	max. 1 m/s
Protection class:	IP67 to EN 60529
Contact material:	Silver
Contact type:	Change-over contact with double break, type Zb or 2 NC contacts, with galvanically separated contact bridges
Switching system:	⊖ EN 60947-5-1, slow action or snap action, positive break NC contact screw terminals max. 2.5 mm ² (including conductor ferrules)
Connection:	
Cable section:	3 x M 20 6 kV
Cable entry:	-03z, -12z: 4kV
U _{imp} :	500 V
U _i :	-03z, -12z: 250 V
I _{the} :	10 A
Utilisation category:	AC-15, DC-13
I _e /U _e :	4 A / 230 VAC 4 A / 24VDC
Max. fuse rating:	6 A gG D-fuse
Ambient temperature:	-20 °C ... + 60 °C
Mechanical life:	30 million operations
Switching frequency:	max. 5000/h
Bounce duration:	
Bounce duration:	Snap action: in accordance with actuating speed; Slow action: < 2ms
Switchover time:	Snap action: < 2 ms; Slow action: in accordance with actuating speed
Cable cross-section of the cable glands:	min. Ø 7 mm max. Ø 12 mm ⊖ II 2D

System components



EX-certified screwed cable gland



EX-certified screw plug M20

Ordering details

Ordering details

EX-certified
screwed cable gland
EX-certified
screw plug


EX-KLE-M20x1.5
EX-VS-M20x1.5

No.	Option	Description
⑤	1297	Enclosure with transversely slotted mounting holes
⑥	2138	Roller lever 7H for safety duties
⑦	1637	Gold-plated contacts

* Switches with 2 NO contacts are only
suitable for positioning tasks!

Position switches with safety function

Plunger S




- Actuator type B to EN 50041
- Required actuating force
Snap action: 12 N
Slow action: 17 N
- Actuating speed with actuating angle 0° to switch axis: max. 0.5 m/s

Contact variants

Contacts/ Switch travel	Snap action	Slow action	Slow action with overlapping contacts	Slow action with staggered contacts
1 NO / 1 NC	EX-ZS 3..-11Z-3G/D	EX-TS 3..-11Z-3G/D	EX-TS 3..-11ZUE-3G/D	
2 NC	EX-ZS 3..-02Z-3G/D	EX-TS 3..-02Z-3G/D		EX-TS 3..-02ZH-3G/D
2 NO		EX-TS 3..-20Z-3G/D		EX-TS 3..-20ZH-3G/D
1 NO / 2 NC		EX-TS 3..-12Z-3G/D	EX-TS 3..-12ZUE-3G/D	
3 NC		EX-TS 3..-03Z-3G/D		EX-TS 3..-03ZH-3G/D

Roller plunger R




- Actuator type C to EN 50041
- Required actuating force
Snap action: 12 N
Slow action: 17 N
- Actuating speed with actuating angle 30° to switch axis: max. 0.5 m/s

Contact variants

Contacts/ Switch travel	Snap action	Slow action	Slow action with overlapping contacts	Slow action with staggered contacts
1 NO / 1 NC	EX-ZR 3..-11Z-3G/D	EX-TR 3..-11Z-3G/D	EX-TR 3..-11ZUE-3G/D	
2 NC	EX-ZR 3..-02Z-3G/D	EX-TR 3..-02Z-3G/D		EX-TR 3..-02ZH-3G/D
2 NO		EX-TR 3..-20Z-3G/D		EX-TR 3..-20ZH-3G/D
1 NO / 2 NC		EX-TR 3..-12Z-3G/D	EX-TR 3..-12ZUE-3G/D	
3 NC		EX-TR 3..-03Z-3G/D		EX-TR 3..-03ZH-3G/D

Position switches with safety function

Roller lever H




- Actuator type A to EN 50041
- Required actuating torque
Snap action: 26 Ncm
Slow action: 31 Ncm
- Actuating speed with actuating angle 30° to switch axis: max. 2.5 m/s
- also available with plastic roller, ordering suffix: 1H
- Available with metal roller, ordering suffix -RMS

On version EX-TVH ...-01/01Z positive break only to one side.

Contact variants

Contacts/ Switch travel	Snap action	Slow action	Slow action with overlapping contacts	Slow action with staggered contacts
1 NO / 1 NC	EX-Z4VH 3..-11Z-3G/D 80° 24° 0 24° 80° 13-14 21-22 12° 12° 13-14 21-22	EX-T4VH 3..-11Z-3G/D 80° 36° 0 36° 80° 13-14 21-22 24° 24° 13-14 21-22	EX-T4VH 3..-11Z-3G/D 80° 36° 0 36° 80° 13-14 21-22 45° 45° 13-14 21-22	EX-T4VH 3..-11Z-3G/D 80° 36° 0 36° 80° 13-14 21-22 45° 45° 13-14 21-22
2 NC	EX-Z4VH 3..-02Z-3G/D 80° 45° 0 45° 80° 11-12 21-22 12° 12° 11-12 21-22	EX-T4VH 3..-02Z-3G/D 80° 36° 0 36° 80° 11-12 21-22 24° 24° 11-12 21-22		EX-T4VH 3..-02ZH-3G/D 80° 45° 0 45° 80° 11-12 21-22 24° 24° 11-12 21-22
2 NO		EX-T4VH 3..-20Z-3G/D 80° 36° 0 36° 80° 13-14 23-24 36° 36° 13-14 23-24		EX-T4VH 3..-20ZH-3G/D 80° 36° 0 36° 80° 13-14 23-24 16° 16° 13-14 23-24
1 NC left 1 NC right			EX-T4VH 3..-01701Z-3G/D 80° 0 24° 58° 11-12 21-22 24° 24° 11-12 21-22	
1 NO / 2 NC		EX-T4VH 3..-12Z-3G/D 80° 36° 0 36° 80° 13-14 21-22 24° 24° 13-14 31-32	EX-T4VH 3..-12ZUE-3G/D 80° 36° 0 36° 80° 13-14 21-22 45° 45° 13-14 31-32	
3 NC		EX-T4VH 3..-03Z-3G/D 80° 24° 0 24° 80° 11-12 21-22 36° 36° 11-12 31-32		EX-T4VH 3..-03ZH-3G/D 80° 24° 0 24° 80° 11-12 21-22 45° 45° 11-12 31-32

Rod lever 10H




- only for positioning tasks
- Actuator type D to EN 50041
- Plastic rod
- Required actuating torque
Snap action: 26 Ncm
Slow action: 31 Ncm
- Actuating speed with actuating angle 30° to switch axis: max. 2.5 m/s
- Aluminium rod, ordering suffix -1183

Contact variants

Contacts/ Switch travel	Snap action	Slow action	Slow action with overlapping contacts	Slow action with staggered contacts
1 NO / 1 NC	EX-Z4V10H 3..-11Z-3G/D 80° 24° 0 24° 80° 13-14 21-22 12° 12° 13-14 21-22	EX-T4V10H 3..-11Z-3G/D 80° 36° 0 36° 80° 13-14 21-22 24° 24° 13-14 21-22	EX-T4V10H 3..-11ZUE-3G/D 80° 36° 0 36° 80° 13-14 21-22 45° 45° 13-14 21-22	
2 NC	EX-Z4V10H 3..-02Z-3G/D 80° 45° 0 45° 80° 11-12 21-22 12° 12° 11-12 21-22	EX-T4V10H 3..-02Z-3G/D 80° 36° 0 36° 80° 11-12 21-22 24° 24° 11-12 21-22		EX-T4V10H 3..-02ZH-3G/D 80° 45° 0 45° 80° 11-12 21-22 24° 24° 11-12 21-22
2 NO		EX-T4V10H 3..-20Z-3G/D 80° 36° 0 36° 80° 13-14 23-24 36° 36° 13-14 23-24		EX-T4V10H 3..-20ZH-3G/D 80° 36° 0 36° 80° 13-14 23-24 16° 16° 13-14 23-24
1 NC left 1 NC right			EX-TV10H 3..-0101Z-3G/D 80° 0 24° 58° 11-12 21-22 24° 24° 11-12 21-22	
1 NO / 2 NC		EX-T4V10H 3..-12Z-3G/D 80° 36° 0 36° 80° 13-14 21-22 24° 24° 13-14 31-32	EX-T4V10H 3..-12ZUE-3G/D 80° 36° 0 36° 80° 13-14 21-22 45° 45° 13-14 31-32	
3 NC		EX-T4V10H 3..-03Z-3G/D 80° 24° 0 24° 80° 11-12 21-22 36° 36° 11-12 31-32		EX-T4V10H 3..-03ZH-3G/D 80° 24° 0 24° 80° 11-12 21-22 45° 45° 11-12 31-32

Position switches with safety function

Roller lever 7H




• only for positioning tasks

- Required actuating torque
- Snap action: 26 Ncm
- Slow action: 31 Ncm
- Actuating speed with actuating angle 30° to switch axis: max. 2.5 m/s

Contact variants

Contacts/ Switch travel	Snap action	Slow action	Slow action with overlapping contacts	Slow action with staggered contacts
1 NO / 1 NC	EX-Z4V7H 3..-11Z-3G/D 	EX-T4V7H 3..-11Z-3G/D 	EX-T4V7H 3..-11ZUE-3G/D 	
2 NC	EX-Z4V7H 3..-02Z-3G/D 	EX-T4V7H 3..-02Z-3G/D 		EX-T4V7H 3..-02ZH-3G/D
2 NO		EX-T4V7H 3..-20Z-3G/D 		EX-T4V7H 3..-20ZH-3G/D
1 NC left 1 NC right		EX-TV7H 3..-01/01Z-3G/D 		
1 NO / 2 NC		EX-T4V7H 3..-12Z-3G/D 	EX-T4V7H 3..-12ZUE-3G/D 	
3 NC		EX-T4V7H 3..-03Z-3G/D 		EX-T4V7H 3..-03ZH-3G/D

7H-2138



- for safety duties A
- Required actuating torque
- Snap action: 26 Ncm
- Slow action: 31 Ncm
- Actuating speed with actuating angle 30° to switch axis: max. 2.5 m/s


On version TVH ...-01/01Z positive break only to one side.

Contact variants

Contacts/ Switch travel	Snap action	Slow action	Slow action with overlapping contacts	Slow action with staggered contacts
1 NO / 1 NC	EX-Z4V7H 3..-11Z-2138-3G/D 	EX-T4V7H 3..-11Z-2138-3G/D 	EX-T4V7H 3..-11ZUE-2138-3G/D 	
2 NC	EX-Z4V7H 3..-02Z-2138-3G/D 	EX-T4V7H 3..-02Z-2138-3G/D 		EX-T4V7H 3..-02ZH-2138-3G/D
2 NO		EX-T4V7H 3..-20Z-2138-3G/D 		EX-T4V7H 3..-20ZH-2138-3G/D
1 NC left 1 NC right		EX-TV7H 3..-01/01Z-2138-3G/D 		
1 NO / 2 NC		EX-T4V7H 3..-12Z-2138-3G/D 	EX-T4V7H 3..-12ZUE-2138-3G/D 	
3 NC		EX-T4V7H 3..-03Z-2138-3G/D 		EX-T4V7H 3..-03ZH-2138-3G/D

Position switches with safety function

Offset roller lever 1K




- Required actuating force
Snap action: 12 N
Slow action: 17 N
- Actuating speed with actuating angle 30° to switch axis: max. 0.5 m/s

Contact variants

Contacts/ Switch travel	Snap action	Slow action	Slow action with overlapping contacts	Slow action with staggered contacts
1 NO / 1 NC	EX-Z1K 3..-11Z-3G/D	EX-T1K 3..-11Z-3G/D	EX-T1K 3..-11ZUE-3G/D	
2 NC	EX-Z1K 3..-02Z-3G/D	EX-T1K 3..-02Z-3G/D		EX-T1K 3..-02ZH-3G/D
2 NO		EX-T1K 3..-20Z-3G/D		EX-T1K 3..-20ZH-3G/D
1 NO / 2 NC		EX-T1K 3..-12Z-3G/D	EX-T1K 3..-12ZUE-3G/D	
3 NC		EX-T1K 3..-03Z-3G/D		EX-T1K 3..-03ZH-3G/D

Angle roller lever 3K




- Required actuating force
Snap action: 12 N
Slow action: 17 N
- Actuating speed with actuating angle 30° to switch axis: max. 0.5 m/s
- Actuation parallel to axis of switch from below

Contact variants

Contacts/ Switch travel	Snap action	Slow action	Slow action with overlapping contacts	Slow action with staggered contacts
1 NO / 1 NC	EX-Z3K 3..-11Z-3G/D	EX-T3K 3..-11Z-3G/D	EX-T3K 3..-11ZUE-3G/D	
2 NC	EX-Z3K 3..-02Z-3G/D	EX-T3K 3..-02Z-3G/D		EX-T3K 3..-02ZH-3G/D
2 NO		EX-T3K 3..-20Z-3G/D		EX-T3K 3..-20ZH-3G/D
1 NO / 2 NC		EX-T3K 3..-12Z-3G/D	EX-T3K 3..-12ZUE-3G/D	
3 NC		EX-T3K 3..-03Z-3G/D		EX-T3K 3..-03ZH-3G/D

Position switches

EX-MAF 330-...-3D



- Ex certified
- Metal enclosure
- Snap action with self-cleaning contacts, change-over contact with double break, silver contacts
- type Zb, with galvanically separated contact bridges
- Suitable for low actuating speeds
- 3 contacts
- Long life
- High level of contact reliability with low voltages and currents
- Mounting details to EN 50041
- Actuator heads can be repositioned in steps 4 x 90°
- Can be mounted on a flat surface
- Slotted holes for adjustment, circular holes for location
- 1 cable entry M20
- Including Ex-certified screwed cable gland
- Actuating speed min. 10 mm/min related to the plunger

Approvals



Ordering details

EX-MAF 330-11Y-①-②


No. Option Description

①		without LED
②	AuNi	Gold-nickel alloy contacts

Technical data

Equipment category:	II 3D
Ex protection:	Ex tD A22 IP65 T100°C X
Standards:	EN 60947-5-1 EN 61241-0 EN 61241-1 BG-GS-ET-15
Enclosure:	light-alloy diecast, paint finish
Actuator:	stainless steel 1.4301
Max. impact energy:	4 J
Actuating speed:	max. 1 m/s
Protection class:	IP65 to EN 60529
Contact material:	Silver
Contact type:	Change-over contact with double break type Zb, 3 NC contacts with galvanically separated contact bridges
Switching system:	EN 60947-5-1, slow action, positive break NC contact
Connection:	screw terminals
Cable section:	max. 2.5 mm ² min. 0.75 mm ² (including conductor ferrules)
Cable entry:	M20
U _{imp} :	4 kV
U _i :	250 V
I _{the} :	10 A
Utilisation category:	AC-15, DC-13
I _e /U _e :	4 A / 230 VAC 4 A / 24 VDC
Max. fuse rating:	6 A gG D-fuse
Positive break travel:	10.7 mm
Positive break force:	each NC contact 5 N
Ambient temperature:	-15 °C ... +80 °C
Mechanical life:	10 million operations
Latching force:	30 N for ordering suffix R
Cable cross-section of the cable glands:	min. Ø 7 mm max. Ø 12 mm II 2D


System components



EX-certified screwed cable gland

Position switches

Spring rod lever AF




Contact variants

Contacts/
Switch travel

Snap action

1 NO / 1 NC


MAF 330-11y



- Required actuating force 9.0 N
- can be deflected in any direction
- Elasticity of the spring allows for deflection above the max. switching angle of 15°

Position switches

EX-T 335-...




- Ex certified
- Mounting details to EN 50041
- Metal enclosure
- Slow action with 2 positive-break NC contacts to EN 60947-5-1 available
- Slow action available with overlapping contacts
- Wide range of alternative actuators
- Actuator heads can be repositioned by 4 x 90°
- Angle of roller lever adjustable in 10° steps
- Good resistance to oil and petroleum spirit
- 1 cable entry M20
- Including Ex-certified screwed cable gland

Technical data

Equipment category:	Ex II 2GD
Ex protection:	Ex de IIC T6
Standards:	Ex tD A21 IP65 T80°C EN 60947-5-1 EN 61241-0 EN 61241-1 EN 60079-0 EN 60079-1 BG-GS-ET-15 DIN EN 50041
Design:	zinc die-cast, paint finish
Enclosure:	
Max. impact energy:	7 J
Actuating speed:	max. 1 m/s
Protection class:	IP65, IP67 to EN 60529
Contact material:	Silver
Contact type:	Change-over contact with double break, type Zb or 2 NC contacts, with galvanically separated contact bridges
Switching system:	⊕ EN 60947-5-1, slow action, positive break NC contact
Connection:	screw terminals
Cable section:	1 mm² ... 2.5 mm² (including conductor ferrules)
Cable entry:	M20
U_{imp} :	4 kV
U_i :	250 V
I_{the} :	5 A
Utilisation category:	AC-1
Max. fuse rating:	6 A gG D-fuse
Ambient temperature:	- 20 °C ... + 55 °C - 20 °C ... + 50 °C
- cable section 2.5 mm²	
- cable section 1 mm²	
Mechanical life:	> 1 million operations
Switching frequency:	max. 1800/h
Bounce duration:	< 3 ms
Switchover time:	in accordance with actuating speed
Cable cross-section of the cable glands:	min. Ø 7 mm max. Ø 12 mm Ex II 2D

System components



EX-certified screwed cable gland

Approvals



Ordering details

EX-T① 335-②Y③-④

No.	Option	Description
-----	--------	-------------

- | | | |
|---|---|--|
| ① | For the appropriate actuator: see page 65 | |
| ② | 11 | 1 NO contact / 1 NC contact |
| | 02 | 2 NC contacts |
| | 20 | 2 NO contacts* |
| ③ | UE | with overlapping contacts
with staggered contacts |
| ④ | 2138 | Roller lever 7H
for safety duties |

* Switches with 2 NO contacts are only suitable
for positioning tasks!


Ordering details

Ex-certified
screwed cable gland

EX-KLE-M20x1.5

Position switches

Plunger S




- Actuator type B to EN 50041
- Required actuating force
Slow action: 17 N
- Actuating speed with actuating angle 0°
to switch axis: max. 0.5 m/s

Contact variants

Contacts/ Switch travel	Slow action	Slow action with overlapping contacts
1 NO / 1 NC	EX-TS 335-11Y	EX-TS 335-11YUE
2 NC	EX-TS 335-02Y	
2 NO	EX-TS 335-20Y	

Roller plunger R




- Actuator type C to EN 50041
- Required actuating force
Slow action: 17 N
- Actuating speed with actuating angle 30°
to switch axis: max. 0.5 m/s

Contact variants

Contacts/ Switch travel	Slow action	Slow action with overlapping contacts
1 NO / 1 NC	EX-TR 335-11Y	EX-TR 335-11YUE
2 NC	EX-TR 335-02Y	
2 NO	EX-TR 335-20Y	

Position switches

Roller lever H



- Actuator type A to EN 50041
- Required actuating torque
Slow action: 31 Ncm
- Actuating speed with actuating angle 30°
to switch axis: max. 2.5 m/s

Contact variants

Contacts/ Switch travel	Slow action	Slow action with overlapping contacts
1 NO / 1 NC	EX-T4VH 335-11Y	EX-T4VH 335-11YUE
2 NC	EX-T4VH 335-02Y	
2 NO	EX-T4VH 335-20Y	

EX-T4VH 335-11Y





EX-T4VH 335-02Y

EX-T4VH 335-20Y


EX-T4VH 335-11YUE

EX-T4VH 335-02Y

EX-T4VH 335-20Y



Rod lever 10H



- **only for positioning tasks**
- Actuator type D to EN 50041
- Plastic rod
- Required actuating torque
Slow action: 31 Ncm
- Actuating speed with actuating angle 30°
to switch axis: max. 2.5 m/s

Contact variants




Contacts/ Switch travel	Slow action	Slow action with overlapping contacts
1 NO / 1 NC	EX-T4V10H 335-11Y	EX-T4V10H 335-11YUE
2 NC	EX-T4V10H 335-02Y	
2 NO	EX-T4V10H 335-20Y	

EX-T4V10H 335-11Y

EX-T4V10H 335-02Y


EX-T4V10H 335-20Y

EX-T4V10H 335-11YUE



Position switches

Roller lever 7H




• only for positioning tasks

- Required actuating torque
- Slow action: 31 Ncm
- Actuating speed with actuating angle 30° to switch axis: max. 2.5 m/s

Contact variants

Contacts/ Switch travel	Slow action	Slow action with overlapping contacts
1 NO / 1 NC	EX-T4V7H 335-11Y	EX-T4V7H 335-11YUE
2 NC	EX-T4V7H 335-02Y	
2 NO	EX-T4V7H 335-20Y	

7H-2138



• for safety duties ⊖


- Required actuating torque
- Slow action: 31 Ncm
- Actuating speed with actuating angle 30° to switch axis: max. 2.5 m/s

Contact variants

Contacts/ Switch travel	Slow action	Slow action with overlapping contacts
1 NO / 1 NC	EX-T4V7H 335-11Y- -2138	EX-T4V7H 335-11YUE- -2138
2 NC	EX-T4V7H 335-02Y- -2138	
2 NO	EX-T4V7H 335-20Y- -2138	

Position switches

Offset roller lever 1K




- Required actuating force
Slow action: 17 N
- Actuating speed with actuating angle 30° to switch axis: max. 0.5 m/s

Contact variants

Contacts/ Switch travel	Slow action	Slow action with overlapping contacts
1 NO / 1 NC	EX-T1K 335-11Y	EX-T1K 335-11YUE
2 NC	EX-T1K 335-02Y	
2 NO	EX-T1K 335-20Y	

Angle roller lever 3K



- Required actuating force
Slow action: 17 N
- Actuating speed with actuating angle 30° to switch axis: max. 0.5 m/s
- Actuation parallel to axis of switch from below

Contact variants

Contacts/ Switch travel	Slow action	Slow action with overlapping contacts
1 NO / 1 NC	EX-T3K 335-11Y	EX-T3K 335-11YUE
2 NC	EX-T3K 335-02Y	
2 NO	EX-T3K 335-20Y	

More Details

The screenshot shows a product detail page for the ZV1H 235-02z safety switch. The page includes a navigation bar, a sidebar with a product hierarchy tree, and detailed technical information sections.

Datenblatt - ZV1H 235-02z - 1145025 - eclass 21272601 27-27-26-01 - Windows Internet Explorer

<http://www.schmersal.net/cat?lang=de&produkt=qo7331340wqx5eej50775240av&>

Daten Bearbeiten Ansicht Favoriten Extras ?

Sicherheits-Schalten und Erfassen Sicherere Signalverarbeitung Automatisierungstechnik Ex-Schaltgeräte Aufzugsschaltgeräte Weitere Produkte und Programmierungen

Home > Positionsschalter > 235 Metallgehäuse - DIN EN 50047 mit Betätigern > 235 Rollenschwenkhebel 1H > ZV1H 235-02z

ZV1H 235-02z

Datenblatt

- Metallgehäuse
- große Auswahl an Betätigungslementen
- wetigehend öl- und benzinsbeständig
- 30 mm x 63,5 mm x 30 mm
- Sprungschatzung mit konstanter Kontaktfunktion bis zum Schaltpunkt
- Betätigungslemente um 4 x 90° umsetzbar
- Befestigungsmasse nach EN 50047
- Befestigungsmasse M 20 x 1,5
- Leitungsführung M 20 x 1,5
- Betätigern in 10° Schritten einstellbar

Daten Dokumente CAD Abbildungen

Bestelldaten

Produkt-Typebezeichnung	ZV1H 235-02z
Artikelnummer	1145025
EAN Code	4030681135427

Zulassung

Sicherheitsbetrachtung

Vorschriften	EN ISO 13849-1
B10x Öffner (NC)	20 Millionen Schaltspiele
Gebrauchsduauer T1M	20 Jahre

Allgemeine Daten

Produkt-Name	Z 235 Rollenschwenkhebel 1H
Vorschriften	IEC/EN 60947-5-1 BG-GS-ET-15
Richtlinienkonformität (J/N)	Ja
für Sicherheitsfunktionen geeignet (J/N)	Ja
Antriebsform	A nach DIN EN 50047
Werkstoffe	

<http://www.schmersal.net/cat?lang=de&produkt=lpv733134m56nffzd50816q0chqv&>


Produkt hierarchie

- Sicheres Schalten und Erfassen
 - Sicherheitsschalter mit getrenntem Betätigern
 - Positionsschalter
 - 95 Kunststoffgehäuse - DIN EN 50047 mit Betätigern
 - 332 Metallgehäuse - DIN EN 50047 mit Betätigern
 - 235 Metallgehäuse - DIN EN 50047 mit Betätigern
 - 235 Druckbolzen S
 - 235 Rollendruckbolzen r
 - 235 Druckbolzen mit Zentralbefestigung 4S
 - 235 Rollendruckbolzen mit Zentralbefestigung 4r
 - 235 Rollenhebel 1r
 - 235 Rollenhebel K
 - 235 Winkelhebel 3K
 - 235 Winkelhebel 4K
 - 235 Winkelhebel K4
 - 235 Rollenschwenkhebel 1H
 - ZV1H 235-02z
 - ZV1H 235-11z
 - TV1H 235-02z
 - TV1H 235-02zh
 - TV1H 235-11z
 - TV1H 235-11zD
 - TV1H 235-20z
 - TV1H 235-20zh
 - 235 Rollenschwenkhebel 7H
 - 235 Rollenschwenkhebel 7H-2138
 - 235 Stabschwenkhebel 10H
 - 235 Rollenschwenkhebel 12H
 - 235 Rollenschwenkhebel 14H
 - 238 Kunststoffgehäuse - DIN EN 50047 mit Betätigern
 - 255 Metallgehäuse - DIN EN 50047 mit Betätigern
 - 256 Kunststoffgehäuse - DIN EN 50047 mit Betätigern
 - 335 Metallgehäuse - DIN EN 50047 mit Betätigern
 - 336 Kunststoffgehäuse - DIN EN 50047 mit Betätigern
 - 355 Metallgehäuse - DIN EN 50047 mit Betätigern
 - Sicherheitsschalter für drehbare Schutzeinrichtungen
 - Sicherheits-Sensoren
 - Seilzug-Notschalter
 - NOT-HALT-Taster
 - Sicherheitsgerichteter Laserscanner
 - Sicherheits-Lichtschranken
 - Sicherheits-Lichtvorhänge, Sicherheits-Lichtgitter
 - Zweihandbedienelemente
 - Turgriffschalter
 - Zustimmungsschalter

Detailed technical information at:
www.schmersal.net

Position switches

EX-T/M 441-...



- Ex certified
- Metal enclosure
- Slow action, change-over contact with double break
- Snap action, change-over contact with double break
- 2 cable entries M20
- Protection class IP65, IP66 and IP67
- Suitable for heavy duty


Technical data

Equipment category:	L II 2D
Ex protection:	Ex tD A21 IP65 T90°C X
Standards:	EN 60947-5-1; EN 61241-0, EN 61241-1
Enclosure:	Grey cast iron, galvanized and painted
Protection class:	IP65, IP66 and IP67 to EN 60529
Contact material:	silver, gold-flashed
Switching system:	Snap- and slow action with double break
Contact type:	Slow action: positive break NC contact A double break of 2 separated contact bridges
Connection:	screw terminals M 4 max. 2.5 mm ² (incl. conductor ferrules)
Cable section:	
U_{imp} :	Snap action: 4 kV; Slow action: 6 kV
U_i :	Slow action: 250 V; Snap action: 400 V
I_{the} :	16 A
I_e/U_e :	Snap action: 4 A / 230 V; Slow action: 4 A / 400 V
Utilisation category:	AC-15
Max. fuse rating:	16 A gG D-fuse
Contact break:	Snap action: max. 2 × 2.5 mm Slow action: max. 2 × 6.0 mm
Switchover time:	Snap action: 35 ms
Bounce duration:	Snap action: 5 ms
Ambient temperature:	-20 °C ... +60 °C
Mechanical life:	10 million operations
Switching frequency:	max. 3000/h
Cable cross-section of the cable glands:	min. Ø 7 mm max. Ø 12 mm
	L II 2D

Contact variants

1 NO / 1 NC contacts

Snap action



Slow action



Approvals



Ordering details

EX-①441-11Y-②-1276-2

N°	Option	Description
①	M.	Snap action
	T.	Slow action
②	UE	Slow action with overlapping contacts

Ordering details


see page 84	
EX-certified	
screwed cable gland	EX-KLE-M20x1.5
EX-certified	
screwed cable gland	EX-KLE-M25x1.5
EX-certified	
screw plug	EX-VS-M20x1.5
EX-certified	
screw plug	EX-VS-M25x1.5

see page 76

Actuator selection (actuators must be ordered separately)

Position switches

EX-T/M 250-...



- Ex certified
- Metal enclosure
- Slow action, change-over contact with double break
- Snap action, change-over contact with double break
- 2 cable entries M25
- Protection class IP65, IP66 and IP67
- Suitable for heavy duty


Technical data

Equipment category:	II 2D
Ex protection:	Ex tD A21 IP67 T90°C
Standards:	EN 60947-5-1; EN 61241-0, EN 61241-1
Enclosure:	Grey cast iron, galvanized and painted
Protection class:	IP65, IP66 and IP67 to EN 60529
Contact material:	silver, gold-flashed
Contact type:	snap action, change-over contact, slow action positive break NC contact \ominus double break with 2 separate contact bridges
Switching system:	Snap- and slow action screw terminals M 4 max. 2.5 mm ² (incl. conductor ferrules)
Connection:	6 kV
Cable section:	500 V
U_{imp} :	16 A
U_i :	4 A / 400 VAC
I_{the} :	AC-15
I_e/U_e :	16 A gG D-fuse
Utilisation category:	Snap action: max. 2 \times 2.5 mm
Max. fuse rating:	Slow action: max. 2 \times 2 mm
Contact break:	35 ms
Switchover time:	5 ms
Bounce duration:	- 20 °C ... + 60 °C
Ambient temperature:	10 million operations
Mechanical life:	max. 3000/h
Switching frequency:	min. Ø 14 mm
Cable cross-section of the cable glands:	max. Ø 18 mm
	II 2D


Contact variants

1 NO / 1 NC contacts

Snap action




Slow action




2 NO / 2 NC contacts

Snap action



Slow action



Approvals



Ordering details

EX-①250-②Z-1276-2

No.	Option	Description
①	M. T.	Snap action Slow action
②	11 22	1 NO/1 NC contacts 2 NO/2 NC

Ordering details


see page 84	
EX-certified	
screwed cable gland	EX-KLE-M20x1.5
EX-certified	
screwed cable gland	EX-KLE-M25x1.5
EX-certified	
screw plug	EX-VS-M20x1.5
EX-certified	
screw plug	EX-VS-M25x1.5

see page 76

Actuator selection (actuators must be ordered separately)

Position switches

EX-TS 064-...



- Ex certified
- Metal enclosure
- 3 or 4 contact, slow action \ominus
- Roller levers J and X can be subsequently fitted at plunger S
- Actuator head can be repositioned in steps $4 \times 90^\circ$
- 2 cable entries M25
- Protection class IP65, IP66 and IP67

Actuation from the side of the plunger should be avoided, since this reduces the mechanical life of the position switch. Recommendation: use roller lever


Technical data

Equipment category:	\textcircled{S} II 2D
Ex protection:	Ex tD A21 IP65 T90°C X
Standards:	EN 60947-5-1, EN 61241-0, EN 61241-1
Enclosure:	Grey cast iron, galvanized and painted
Actuating speed:	max. 1 m/s, min. 0.01 m/s at the plunger
Protection class:	IP65, IP66 and IP67 to EN 60529
Contact material:	silver, gold-flashed
Switching system:	slow action with double break
Contact type:	NC contact positive break \ominus
Connection:	screw terminals M 5
Cable section:	max. 4 mm ² (incl. conductor ferrules)
U_{imp} :	6 kV
U_i :	500 V
I_{the} :	25 A
I_e/U_e :	25 A / 400 VAC AC-15
Utilisation category:	16 A gG D-fuse at 400 V
Max. fuse rating:	3-phase 5.5 kW (squirrel-cage rotor n = 1500 rpm)
Allowed horsepower:	max. 2 x 4 mm
Contact break:	- 20 °C ... + 60 °C
Ambient temperature:	1 million operations
Mechanical life:	max. 1000/h
Switching frequency:	max. 20°
Actuating angle:	approx. 3.2 kg
Weight:	min. Ø 14 mm max. Ø 18 mm
Cable cross-section of the cable glands:	\textcircled{S} II 2D

Contact variants


Plunger S

1 NO contact / 1 NC contact




Offset roller lever J

1 NO contact / 1 NC contact



Offset roller lever X

1 NO contact / 1 NC contact



Approvals




Ordering details

EX-T₁ 064-₂Y-₃1276-2

N°	Option	Description
①	For the appropriate actuator: see page 72	
②	03	3 NC contacts
	12	1 NO/2 NC
	21	2 NO/1 NC
	30	3 NO contacts
	04	4 NC contacts
	13	1 NO/3 NC
	22	2 NO/2 NC
	31	3 NO/1 NC
	40	4 NO contacts
③	UE	Slow action with overlapping contacts with staggered contacts
	H	

Force-travel diagram



Ordering details


EX-certified
screwed cable gland
EX-certified
screw plug

EX-KLE-M25x1.5

EX-VS-M25x1.5

Position switches

EX-MS 064-...



- Ex certified
- Metal enclosure
- 3 or 4 contact, snap action with double break
- Roller levers J and X can be subsequently fitted at plunger S
- Actuator head can be repositioned in steps 4 x 90°
- 2 cable entries M25
- Protection class IP65, IP66 and IP67

Actuation from the side of the plunger should be avoided, since this reduces the mechanical life of the position switch. Recommendation: use roller lever


Technical data

Equipment category:	II 2 D
Ex protection:	Ex tD A21 IP65 T90°C X
Standards:	EN 60947-5-1, EN 61241-0, EN 61241-1
Enclosure:	Grey cast iron, galvanized and painted
Protection class:	IP65, IP66 and IP67
Contact material:	silver, gold-flashed
Switching system:	snap action with double break
Contact type:	change-over contact, galvanically separated
Connection:	contact bridges
Cable section:	screw terminals M 5 max. 4 mm²
U _{imp} :	6 kV
U _i :	500 V
I _{the} :	25 A
I _e /U _e :	25 A / 400 VAC AC-15
Utilisation category:	25 A gG D-fuse at 400 V
Max. fuse rating:	3-phase 5.5 kW
Allowed horsepower:	(squirrel-cage rotor n = 1500 rpm) max. 2 x 4 mm
Contact break:	- 20 °C ... + 60 °C
Ambient temperature:	30000 operations
Mechanical life:	max. 1000/h
Switching frequency:	max. 1 m/s, min. 0.01 m/s
Actuating speed:	at the plunger max. 20°
Actuating angle:	approx. 3.6 kg
Weight:	min. Ø 14 mm max. Ø 18 mm
Cable cross-section of the cable glands:	II 2 D


Contact variants

Plunger S

1 NC contact



1 NO contact




Offset roller lever J

1 NC contact



1 NO contact




Offset roller lever X

1 NC contact



1 NO contact



Approvals




Ordering details

EX-M① 064-②Y-1276-2

No.	Option	Description
①		For the appropriate actuator: see page 72
②	03	3 NC contacts
	12	1 NO/2 NC
	21	2 NO/1 NC
	30	3 NO contacts
	04	4 NC contacts
	13	1 NO/3 NC
	22	2 NO/2 NC
	31	3 NO/1 NC
	40	4 NO contacts

Force-travel diagram



Ordering details


EX-certified
screwed cable gland
EX-certified
screw plug

EX-KLE-M25x1.5


EX-VS-M25x1.5

Position switches

System components




EX-certified screwed cable gland



EX-certified screw plug


Plunger S



- Actuating speed 1 m/s with an actuating angle of max. 20°
- Roller levers J and X can be subsequently fitted at plunger S

Actuation from the side of the plunger should be avoided, since this reduces the mechanical life of the position switch.
Recommendation: use roller lever


Offset roller lever X



- Actuating speed max. 0.5 m/s with an actuating angle of $\alpha = 45^\circ$ and $\beta = 30^\circ$
- Plastic roller (metal roller on request)
- Actuator head can be repositioned in steps 4 x 90°

Actuation from the right side of the plunger should be avoided, since this reduces the mechanical life of the position switch.

Offset roller lever J



- Actuating speed max. 0.5 m/s with an actuating angle of $a = 45^\circ$ and $b = 30^\circ$
- Plastic roller (metal roller on request)
- Actuator head can be repositioned in steps 4 x 90°
- Available with rubber roller, ordering suffix -1

Actuation from the right side of the plunger should be avoided, since this reduces the mechanical life of the position switch.

Note

Legend

α : Actuating angle from right of switch axis
 β : Actuating angle from left of switch axis


Ordering details

EX-certified
screwed cable gland
EX-certified
screw plug

EX-KLE-M25x1,5
EX-VS-M25x1,5

Position switches

EX-T. 064-...



- Ex certified
- Metal enclosure
- 3 contact, slow action \ominus
- Actuating direction, each time 90° right-hand side and left-hand side rotation
- 2 cable entries M25
- Protection class IP65, IP66 and IP67
- Splined shaft and lever available with 10° toothing

Technical data


Equipment category:	II 2D
Ex protection:	Ex tD A21 IP65 T90°C X
Standards:	EN 60947-5-1, EN 61241-0, EN 61241-1
Enclosure:	Grey cast iron, galvanized and painted
Protection class:	IP65, IP66 and IP67 to EN 60529
Contact material:	silver, gold-flashed
Switching system:	slow action with double break
Contact type:	NC contact positive break \ominus
Connection:	screw terminals M 5
Cable section:	max. 4 mm ² (incl. conductor ferrules)
U_{imp} :	6 kV
U_i :	500 V
I_{the} :	25 A
I_e/U_e :	25 A / 400 VAC AC-15
Utilisation category:	Max. fuse rating: 16 A gG D-fuse at 400 V
Max. fuse rating:	Allowed horsepower: 3-phase 5.5 kW (squirrel-cage rotor n = 1500 rpm)
Allowed horsepower:	Contact break: max. 2 x 4 mm
	Ambient temperature: -20 °C ... +60 °C
	Mechanical life: 1 million operations
	Switching frequency: max. 1000/h
	Actuating speed: max. 3 m/s, min. 0.05 m/s
	Actuating angle: max. 30°
	Weight: approx. 3.5 kg
	Cable cross-section of the cable glands: min. Ø 14 mm max. Ø 18 mm
	Approvals: Ex II 2D

Contact variants


Roller lever

1 NO contact


1 NC contacts



only NO contacts



only NC contacts



Approvals




Ordering details

EX-T. 064-①Y-②-1276-③

No.	Option	Description
①	03	3 NC contacts
	12	1 NO/2 NC
	21	2 NO/1 NC
	30	3 NO contacts
01/02		1 NC to the left/2 NC to the right
02/01		2 NC to the left/1 NC to the right
10/20		1 NC to the left/2 NC to the right
20/10		2 NC to the left/1 NC to the right
②	H	with staggered contacts
	R	Latching 2 x 45°
③	1877	Toothed shaft

Force-travel diagram



Ordering details

see page 72

EX-certified

screwed cable gland

EX-certified

screw plug

EX-KLE-M25x1.5


EX-VS-M25x1.5

see page 76

Actuator selection (actuators must be ordered separately)

Position switches

EX-M. 064 R



- Ex certified
- Metal enclosure
- 3 or 4 contact, snap action with double break
- Actuating direction always 50° right-hand side rotation
- 2 cable entries M25
- Protection class IP65, IP66 and IP67
- Splined shaft and lever available with 10° toothed


Technical data

Equipment category:	II 2D
Ex protection:	Ex tD A21 IP65 T90°C X
Standards:	EN 60947-5-1, EN 61241-0, EN 61241-1
Enclosure:	Grey cast iron, galvanized and painted
Protection class:	IP65, IP66 and IP67 to EN 60529
Contact material:	silver, gold-flashed
Switching system:	snap action with double break
Contact type:	change-over contact, galvanically separated
Connection:	contact bridges
Cable section:	screw terminals M 5 max. 4 mm ² (incl. conductor ferrules)
U_{imp} :	6 kV
U_i :	500 V
I_{the} :	25 A
I_e/U_e :	25 A / 400 VAC AC-15
Utilisation category:	25 A gG D-fuse
Max. fuse rating:	bei 400 V
Allowed horsepower:	3-phase 5.5 kW (squirrel-cage rotor n = 1500 rpm)
Contact break:	max. 2 x 4 mm
Ambient temperature:	-20 °C ... +60 °C
Mechanical life:	30000 operations
Switching frequency:	max. 1000/h
Actuating speed:	max. 3 m/s, min. 0.05 m/s
Actuating angle:	max. 30°
Weight:	approx. 3.7 kg
Cable cross-section of the cable glands:	min. Ø 14 mm max. Ø 18 mm
	II 2D


Contact variants

Roller lever

1 NC contacts



1 NO contact



Approvals




Ordering details

EX-M. 064-①-Y-R-1276-2②

No.	Option	Description
①	12	1 NO/2 NC
	21	2 NO/1 NC
	30	3 NO contacts
	22	2 NO/2 NC contacts
	31	3 NO/1 NC
	40	4 NO contacts
②	1877	Toothed shaft

Force-travel diagram



Ordering details

see page 72

EX-certified

screwed cable gland

EX-certified

screw plug

EX-KLE-M25x1.5


EX-VS-M25x1.5

see page 76

Actuator selection (actuators must be ordered separately)

Position switches

EX-M. 064 L



- Ex certified
- Metal enclosure
- 3 or 4 contact, snap action with double break
- Actuating direction always 55° left-hand side rotation
- 2 cable entries M25
- Protection class IP65, IP66 and IP67
- Splined shaft and lever available with 10° toothed


Technical data

Equipment category:	II 2D
Ex protection:	Ex tD A21 IP65 T90°C X
Standards:	EN 60947-5-1, EN 61241-0, EN 61241-1
Enclosure:	Grey cast iron, galvanized and painted
Protection class:	IP65, IP66 and IP67 to EN 60529
Contact material:	silver, gold-flashed
Switching system:	snap action with double break
Contact type:	change-over contact, galvanically separated contact bridges
Connection:	screw terminals M 5
Cable section:	max. 4 mm ² (incl. conductor ferrules)
U_{imp} :	6 kV
U_i :	500 V
I_{the} :	25 A
I_e/U_e :	25 A / 400 VAC AC-15
Utilisation category:	25 A gG D-fuse at 400 V
Max. fuse rating:	3-phase 5.5 kW (squirrel-cage rotor n = 1500 rpm)
Allowed horsepower:	max. 2 x 4 mm
Contact break:	-20 °C ... +60 °C
Ambient temperature:	30000 operations
Mechanical life:	max. 1000/h
Switching frequency:	max. 3 m/s, min. 0.05 m/s
Actuating speed:	max. 30°
Actuating angle:	approx. 3.7 kg
Weight:	min. Ø 14 mm max. Ø 18 mm
Cable cross-section of the cable glands:	II 2D


Contact variants

Roller lever

1 NC contacts



1 NO contact



Approvals




Ordering details

EX-M. 064-①Y-L-1276-2②

No.	Option	Description
①	03	3 NC contacts
	12	1 NO/2 NC
	21	2 NO/1 NC
	04	4 NC contacts
	13	1 NO/3 NC
	22	2 NO/2 NC contacts
②	1877	Toothed shaft

Force-travel diagram



Ordering details

see page 72

EX-certified

screwed cable gland

EX-certified

screw plug

EX-KLE-M25x1.5


EX-VS-M25x1.5

see page 76

Actuator selection (actuators must be ordered separately)


Position switches

Roller lever L




- Actuating speed max. 3 m/s with an actuating angle of α and $\beta = 30^\circ$
- Plastic roller
- Continuous adjustment of lever position 360°
- Splined shaft and lever available with 10° toothing
- Available with metal roller
- Available with rubber roller, ordering suffix -1

Roller lever V




- Actuating speed max. 3 m/s with an actuating angle of α and $\beta = 30^\circ$
- Plastic roller
- Continuous adjustment of lever position 360°
- Splined shaft and lever available with 10° toothing
- Available with metal roller
- Available with rubber roller, ordering suffix -1

Fork lever C




- Continuous adjustment of lever position 360°
- Splined shaft and lever available with 10° toothing

Roller lever A




- Actuating speed max. 3 m/s with an actuating angle of α and $\beta = 30^\circ$
- Plastic roller
- Continuous adjustment of lever position 360°
- Splined shaft and lever available with 10° toothing
- Available with metal roller
- Available with rubber roller, ordering suffix -1

Pull lever Z




- Continuous adjustment of lever position 360°
- Splined shaft and lever available with 10° toothing

Offset roller lever 4D




- Continuous adjustment of lever position 360°
- Splined shaft and lever available with 10° toothing

Roller lever 2A



- Actuating speed max. 3 m/s with an actuating angle of α and $\beta = 30^\circ$
- Plastic roller
- Continuous adjustment of lever position 360°
- Splined shaft and lever available with 10° toothing
- Available with metal roller
- Available with rubber roller, ordering suffix -1

Pull lever 2Z



- Continuous adjustment of lever position 360°
- Splined shaft and lever available with 10° toothing

Legend

- α : Actuating angle from right of switch axis
 β : Actuating angle from left of switch axis

Safety switch for hinged guards




The position switches with safety function are suitable for hinged guards, which need to be closed in order to ensure the required operational safety.

Content
EX-TV.S 335-3D

78

Safety switch for hinged guards

EX-TV.S 335-3D



- Metal enclosure
- Good resistance to oil and petroleum spirit
- The actuator can be turned by 4 x 90° using Torx T 20 screwdriver with pin
- Actuator shaft can be turned 360°
- 1 Cable entry M20
- Shaft bore Ø 8 and 10 mm

Technical data

Equipment category:	L II 3D
Ex protection:	Ex tD A22 IP67 T90°C X
Standards:	EN 60947-5-1; EN 61241-0; EN 61241-1; BG-GS-ET-15
Enclosure:	light-alloy diecast, paint finish
Actuator:	stainless steel 1.4301
Max. impact energy:	4 J
Actuating speed:	max. 1 m/s
Protection class:	IP67 to EN 60529
Contact material:	Silver
Contact types:	Change-over contact with double break type Zb, 3 NC contacts with galvanically separated contact bridges
Switching system:	A EN 60947-5-1, slow action, positive break NC contact
Connection:	screw terminals
Cable section:	max. 2.5 mm², min. 0.75 mm² (incl. conductor ferrules)
Cable entry:	M20
U _{imp} :	6 kV
U _i :	500 V
I _{the} :	10 A
Utilisation category:	AC-15; DC-13
I _e /U _e :	4 A / 230 VAC 4 A / 24 VDC 6 A gG D-fuse 10.7 mm
Max. fuse rating:	
Positive break travel:	each NC contact 5 N
Positive break force:	- 20 °C ... + 60 °C
Ambient temperature:	
Mechanical life:	> 1 million operations
Switching frequency:	max. 1000/h
Shaft bore:	Ø 8 mm / 10 mm 7°
Positive break angle:	
Positive break torque:	0.6 Nm
B _{10d} value to EN ISO 13849-1:	20 million
Cable cross-section of the cable glands:	min. Ø 7 mm max. Ø 12 mm L II 2D
Classification:	
Standards:	EN ISO 13849-1
B _{10d} Opener (NC):	20,000,000
Service life:	20 years
MTTF _d	$n_{op} = \frac{B_{10d}}{0,1 \times n_{op}} \quad t_{cycle}$

Approvals



Ordering details


Ex-TV.S 335-2Z-3

No.	Option	Description
①	8	Shaft bore Ø 8 mm
	10	Shaft bore Ø 10 mm
②	02	2 NC contacts
	03	3 NC contacts
	11	1NO/1NC contact
	12	1NO/2NC contacts
③		Cable entry M20


Contact variants

1 NO contact

1 NC contacts




2 NC contacts




1 NO contact

2 NC contacts




3 NC contacts




Safety switch for hinged guards

System components




Fixed hinge F


System components




EX-certified screwed cable gland



Adjustable hinge L



Universal joint K1



Universal joint K2

Ordering details


Fixed hinge F **101138414**
Adjustable hinge L **101138413**

Universal joint K1 **101138412**
(in combination with hinge F or L) only for
TV8S 521
Universal joint K2 **101147448**
for ES 13 SB, ES 95 SB-10mm, TV 10S 335
and TV10S 355

Ordering details

EX-certified
screwed cable gland **EX-KLE-M20x1,5**

Ordering details



Detailed technical information at:
www.schmersal.com

Belt alignment switch / Slack-wire switch




Belt alignment switches and slack-wire switches are suitable for use on material handling equipment. The belt alignment switch is actuated, when the conveyor belt becomes misaligned. Depending on the plant set-up, this signal can be used to switch off the machinery or plant either to provide an automatic correction of the belt alignment.

Content

EX-T/M 441-...	82
EX-T/M 250-...	83

Belt alignment switch / Slack-wire switch

EX-T/M 441-...



- Ex certified
- Metal enclosure
- Slow action, change-over contact with double break
- Snap action, change-over contact with double break
- 2 cable entries M20
- Belt alignment lever available with different roller lengths
- Protection class IP65, IP66 and IP67
- Suitable for heavy duty

Technical data


Equipment category:	II 2D
Ex protection:	Ex tD A21 IP65 T90°C X
Standards:	EN 60947-5-1; EN 61241-0, EN 61241-1
Enclosure:	Grey cast iron, galvanized and painted
Protection class:	IP65, IP66 and IP67 to EN 60529
Contact material:	silver, gold-flashed
Switching system:	Snap- and slow action with double break
Contact types:	Slow action: positive break NC contact \ominus ; double break of 2 separated contact bridges
Connection:	screw terminals M 4 max. 2.5 mm ²
Cable section:	(incl. conductor ferrules)
U_{imp} :	snap action: 4 kV; slow action: 6 kV
U_i :	slow action: 250 V; snap action: 400 V
I_{the} :	16 A
I_e/U_e :	Snap action: 4 A / 230 V; Slow action: 4 A / 400 V
Utilisation category:	AC-15
Max. fuse rating:	16 A gG D-fuse
Contact break:	Snap action: max. 2 \times 2.5 mm Slow action: max. 2 \times 6.0 mm
Switchover time:	Snap action: 35 ms
Bounce duration:	Snap action: 5 ms
Ambient temperature:	- 20 °C ... + 60 °C
Mechanical life:	10 million operations
Switching frequency:	max. 3000/h
Cable cross-section of the cable glands:	min. Ø 7 mm max. Ø 12 mm II 2D

Contact variants


1 NO contact

1 NC contacts

Snap action



Slow action



Approvals




Ordering details

EX-①441-11Y-②-③-1276-2

No.	Option	Description
①	M.	Snap action
	T.	Slow action
②	UE	Slow action with overlapping contacts
③	Actuator selection, see page 84	

Belt alignment switch / Slack-wire switch

EX-T/M 250-...



- Ex certified
- Metal enclosure
- Slow action, change-over contact with double break
- Snap action, change-over contact with double break
- 2 cable entries M25
- Belt alignment lever available with different roller lengths
- Protection class IP65, IP66 and IP67
- Suitable for heavy duty

Technical data


Equipment category:	II 2D
Ex protection:	Ex tD A21 IP67 T90°C X
Standards:	EN 60947-5-1; EN 61241-0, EN 61241-1
Enclosure:	Grey cast iron, galvanized and painted
Protection class:	IP65, IP66 and IP67 to EN 60529
Contact material:	silver, gold-flashed
Contact types:	snap action, change-over contact, slow action positive break NC contact \ominus double break with 2 separate contact bridges
Switching system:	Snap- and slow action
Connection:	screw terminals M 4
Cable section:	max. 2.5 mm ² (incl. conductor ferrules)
U_{imp} :	6 kV
U_i :	500 V
I_{the} :	16 A
I_e/U_e :	4 A / 400 VAC AC-15
Utilisation category:	16 A gG D-fuse
Max. fuse rating:	Snap action: max. 2 \times 2.5 mm
Contact break:	Slow action: max. 2 \times 2 mm 35 ms 5 ms
Switchover time:	-20 °C ... +60 °C
Bounce duration:	10 million operations
Ambient temperature:	max. 3000/h
Mechanical life:	min. Ø 14 mm
Switching frequency:	max. Ø 18 mm
Cable cross-section of the cable glands:	Ø II 2D

Contact variants


1 NO contact

1 NC contacts

Snap action




Slow action




2 NO contact

2 NC contacts

Snap action



Slow action



Approvals




Ordering details

EX-①250-②Z-③-1276-2

No.	Option	Description
①	M.	Snap action
	T.	Slow action
②	11	1 NO/1 NC contact
	22	2 NO/2 NC contacts
③	Actuator selection, see page 84	


Belt alignment switch / Slack-wire switch

System components




Belt alignment lever 243


System components




EX-certified screwed cable gland M20




Belt alignment lever 966




EX-certified screwed cable gland M25




Belt alignment lever 1224



EX-certified screw plug M20



Slack-wire lever type 14



EX-certified screw plug M25

Ordering details

Belt alignment lever

243

966

1224

Slack-wire lever (only
in combination with
EX-T/M 441) type 14

Ordering suffix -243

Ordering suffix -966

Ordering suffix -1224

suffix -type 14

Ordering details

EX-certified

screwed cable gland

EX-certified

screwed cable gland

EX-certified

screw plug

EX-certified

screw plug

EX-KLE-M20x1.5

EX-KLE-M25x1.5

EX-VS-M20x1.5

EX-VS-M25x1.5

Pull-wire emergency-stop switches




Pull-wire emergency stop switches are mounted on machines and sections of plants which cannot be protected by guards. In contrast to mushroom head emergency stop push buttons, on pull-wire switches the emergency stop command can be initiated from any point on the wire.

Content

Ex-ZQ 900-3D	86
EX-T3Z 068-...	88

Pull-wire emergency-stop switches

Ex-ZQ 900-3D



- to EN ISO 13850 / IEC 60947-5-5
- Metal enclosure
- 4 contacts
- position indication
- Robust design
- Large wiring compartment
- 3 cable entries M20
- One tension force for wire lengths from 5 to 50 m
- Wire up to 50 m long
- Reset pushbutton
- Twisting of towing eye not possible
- External watertight collar
- Wire pull and breakage detection
- Stainless
- Including Ex-certified screwed cable gland
- Including Ex-certified screw plug

Technical data

Equipment category:	II 3D
Ex protection:	Ex tD A22 IP67 T100°C
Standards:	IEC/EN 60947-5-1; IEC/EN 60947-5-5; EN 61241-0 EN 61241-1; EN ISO 13850
Enclosure:	zinc die-cast, enamel finish
Cover:	Steel
Max. impact energy:	7 J
Protection class:	IP67 to IEC/EN 60529
Contact material:	Silver
Contact types:	1 NC / 1 NO or 2 NC / 2 NO or 3 NC / 1 NO or 2 NC or 4 NC ⊕ IEC 60947-5-1 snap action, NC contacts with positive break
Switching system:	Screw terminals max. 2.5 mm ² (incl. conductor ferrules)
Connection:	
Cable section:	
Cable entry:	3x M20 6 kV 500 V 4 A
U _{imp} :	
U _i :	
I _{the} :	
Utilisation category:	AC-15, DC-13
I _e /U _e :	4 A / 230 VAC; 1 A / 24 VDC 6 A gG D-fuse
Max. fuse rating:	- 20 °C ... + 55 °C
Ambient temperature:	
Mechanical life:	> 1 million operations
Max. wire length:	50 m (Please observe the ambient temperature range and the wire supports)
Features:	wire pull and breakage detection
Cable cross-section of the cable glands:	min. Ø 7 mm max. Ø 12 mm II 2D
Classification:	
Standards:	EN ISO 13849-1
B _{10d} Opener (NC):	100.000
Service life:	20 years

$$MTTF_d = \frac{B_{10d}}{0,1 \times n_{op}} \quad n_{op} = \frac{d_{op} \times h_{op} \times 3600 \text{ s/h}}{t_{cycle}}$$

Approvals




Ordering details

EX-ZQ 900-①-3D

No.	Option	Description
①	11	1 NO/1 NC contact
	13	1 NO/3 NC contacts
	22	2 NO/2 NC contacts
	02	2 NC contacts
	04	4 NC contacts


Note

Recommended cable lengths for pull-wire Emergency-Stop switches in relation to the range of ambient temperature.
At 5 m distance intermediate wire supports are required, see accessories




Contact variants


1 NO/1 NC contact




2 NC contacts




1 NO/3 NC contacts



2 NO/2 NC contacts




4 NC contacts



Pull-wire emergency-stop switches

Mode of operation


Not actuated



Wire pull detection



Wire breakage detection



Mounting instructions

1 = Wire rope

2 = eyebolt

3 = nut

4 = Wire clamp

5 = tensioner

6 = wire thimble



7 = shackle

8 = wire tensioner

A = position indication

B = emergency-stop button

One-side operation




Mounting instructions

Note:

As the thimbles are subject to deformation in case of wire pull, the wire should be pulled several times after fitting.


After that, the wire must be re-tensioned using the eyebolt or the tensioner.

Thimble deformation



Pull-wire emergency-stop switches

EX-T3Z 068-...



- Ex certified
- to EN ISO 13850 / EN 60947-5-5
- Metal enclosure
- Up to 6 contacts
- Robust design
- 2 cable entries M20
- Low actuating force
- Wire up to 2 x 50 m long
- Reset by pull ring


Technical data

Equipment category:	Ex II 2D
Ex protection:	Ex tD A21 IP65 T90°C X
Standards:	EN 60947-5-1; EN 60947-5-5; EN ISO 13850; EN 61241-0, EN 61241-1
Enclosure:	Grey cast iron, painted
Cover:	Grey cast iron, painted
Protection class:	IP65 and IP66 to EN 60529
Contact material:	Silver, gold-flashed
Contact types:	Change-over contact with double break, max. 3 NO and 3 NC contacts
Switching system:	IEC 60947-5-1 snap action, NC contacts with positive break Screw terminals
Connection:	max. 1.5 mm ² , min. 0.75 mm ² solid and stranded wire with conductor ferrules
Cable section:	2 x M 20
Cable entry:	4 kV
U _{imp} :	250 VAC
U _i :	10 A
I _{the} :	AC-15, DC-13
Utilisation category:	2.5 A / 230 VAC
I _e /U _e :	6 A / 24 VDC
Max. fuse rating:	6 A gG D-fuse
Positive break torque:	1.8 Nm
Angle for positive break travel:	32°
Positive break force:	50 N
Actuating force:	max. 50 N, (30 N in wire direction)
Ambient temperature:	-20 °C ... +60 °C
Mechanical life:	50000 operations
Max. wire length:	2 x 50 m
Features:	wire pull and breakage detection
Cable cross-section of the cable glands:	min. Ø 7 mm max. Ø 12 mm
	Ex II 2D

Contact variants


1 NO contact

1 NC contacts




2 NO contact

2 NC contacts



3 NO contact

3 NC contacts



Approvals



Ordering details

EX-T3Z 068-①YR-1637

No.	Option	Description
①	11	1NO/1NC contact
	22	2NO/2NC contacts
	33	3NO/3NC contacts

Note

At 3 m distance intermediate wire supports are required, see accessories

Ordering details

EX-certified
screwed cable gland
Ex-certified
screw plug

EX-KLE-M20x1.5
EX-VS-M20x1.5

Pull-wire emergency-stop switches



Ordering details

Eyebolt BM 10 x 40	101084928
BM 8 x 70 (stainless steel)	101192471
Wire clamp 3 mm (stainless steel)	101203477
Duplex wire clamp 3 mm (stainless steel)	101190917
Wire thimble 4 mm (stainless steel)	101203475
Egg-shaped wire clamp (without Images)	101077072

Ordering details

Pulley (stainless steel)	101192433
Tensioner M6	101087930
Wire rope per m	on request
Wire unit complete	on request

Ordering details

Tension spring	101186696
S 900 wire tensioner	101186704
Shackle (stainless steel)	101186490

Ordering details



Detailed technical information at:
www.schmersal.com

Safety sensors



The use of magnetic safety sensors is of particular advantage, in cases where extremely dirty conditions can occur. This is provided by the simplicity of cleaning of the devices.

Another advantage is the possibility of concealed mounting behind non-magnetic materials. Working surfaces and storage areas can be designed without dust-collecting edges or other functional cut-outs and structures.


In applications, where a precise approach is not possible and larger tolerances are required, the magnetic safety sensors of the BNS series can also be used.

Content

EX-BNS 250-...-3G/D	92
EX-BNS 33-...-3G/D	94
EX-BNS 120-...-3G/D	96
EX-BNS 180-...-3G/D	98
EX-BNS 303-...-3G/D	100
EX-CSS 180-...-3G/D	102

Safety sensors

EX-BNS 250-...-3G/D



- Ex certified
- Thermoplastic enclosure
- with coding
- Smallest design
- long life, no mechanical wear
- Protection class IP67
- Actuation only possible with EX-BPS 250
- Intensive to transverse misalignment
- Concealed mounting possible
- Intensive to soiling

Technical data

Equipment category:	II 3GD
Explosion protection:	Ex nC IIC T6 X
EX-BNS 250:	Ex tD A22 IP67 T80°C X c 80°C
EX-BPS 250:	EN 60947-5-3, EN 61241-0, EN 61241-1, EN 60079-0, EN 60079-15, BG-GS-ET-14
Standards:	
Design:	rectangular
Enclosure:	glass-fibre reinforced thermoplastic
Max. impact energy:	1 J
Protection class:	IP67 to EN 60529
Connection:	Boflex cable
Cable section:	4 x 0.25 mm ²
Operating principle:	magnetic
Actuating magnet:	EX-BPS 250, coded
S _{ao} :	4 mm
S _{ar} :	14 mm
Switching condition indication:	LED only with ordering suffix G
Max. switching voltage	
without LED:	24 VDC
with LED:	24 VDC
Max. switching current	
without LED:	100 mA
with LED:	10 mA
Max. switching capacity	
without LED:	1 W
with LED:	240 mW
Ambient temperature:	- 25 °C ... + 70 °C
Storage and transport	
temperature:	- 25 °C ... + 70 °C
Max. switching frequency:	5 Hz
Resistance to shock:	30 g / 11 ms
Resistance to vibration:	10 ... 55Hz, Amplitude 1 mm

Classification:

Standards:	EN ISO 13849-1
B _{10d} NC/NO contact:	25.000.000
at 20% contact load	

Service life: 20 years

$$MTTF_d = \frac{B_{10d}}{0,1 \times n_{op}} \quad n_{op} = \frac{d_{op} \times h_{op} \times 3600 \text{ s/h}}{t_{cycle}}$$

Approvals



Ordering details

EX-BNS 250-①z②-③-3G/D

N° Option Description

①	11	1 NO / 1 NC contacts
12	1 NO / 2 NC contacts	
②	without LED	
G	with LED	
③	2187	Individual contact outlet (only with 1 NO / 2 NC)


Note

Enabling zone


The actuators for the magnetic safety sensors must be ordered separately.

Contact variants

1 NO / 1 NC contacts




1 NO / 2 NC contacts



1 NO / 2 NC

(Ordering suffix -2187 without LED)




Note

Contact symbols shown for the closed condition of the guard device.


The contact configuration for versions with or without LED is identical.

The LED is illuminated when the guard door is open.




Safety sensors

System components



Actuating magnet EX-BPS 250



Spacer BNS 250


Ordering details

Actuating magnet
Spacer

EX-BPS 250
BNS 250

Safety sensors

EX-BNS 33-...-3G/D



- Ex certified
- Thermoplastic enclosure
- with coding
- long life, no mechanical wear
- Protection class IP67
- Actuation only possible with EX-BPS 33
- Intensitive to transverse misalignment
- Concealed mounting possible
- Intensitive to soiling

Approvals



Ordering details

EX-BNS 33-①z②-③-3G/D

N° Option Description

①	11	1 NO / 1 NC contacts
	12	1 NO / 2 NC contacts
	02	2 NC contacts without LED
②	G	with LED
③	2187	Individual contact outlet (not possible for 1 NO/1 NC)

Technical data

Equipment category:	II 3GD
Explosion protection:	
EX-BNS 33:	Ex nC IIC T6 X Ex tD A22 IP67 T80°C X c 80°C
EX-BPS 33:	EN 60947-5-3, EN 61241-0, EN 61241-1, EN 60079-0, EN 60079-15, BG-GS-ET-14
Standards:	
Design:	rectangular
Enclosure:	glass-fibre reinforced thermoplastic
Max. impact energy:	1 J
Protection class:	IP67 to EN 60529
Connection:	Boflex cable
Cable section:	4 x 0.25 mm ² 6 x 0.25 mm ²
Ordering suffix ..-12-2187:	
Operating principle:	magnetic
Actuating magnet:	EX-BPS 33, coded
S _{ao} :	5 mm
S _{ar} :	15 mm
Switching condition indication:	LED only with ordering suffix G
Max. switching voltage without LED:	100 VAC/DC
with LED:	24 VDC
Max. switching current without LED:	max. 400 mA
Ordering suffix -2187:	250 mA
with LED:	10 mA
Max. switching capacity without LED:	10 W
Ordering suffix ...-2187:	3 W
with LED:	240 mW
Ambient temperature:	- 25 °C ... + 70 °C
Storage and transport temperature:	- 25 °C ... + 70 °C
Repeat accuracy R:	≤ 0.1 x S _{ao}
Max. switching frequency:	ca. 5 Hz
Resistance to shock:	30 g / 11 ms
Resistance to vibration:	10 ... 55Hz, Amplitude 1 mm


Classification:

Standards:	EN ISO 13849-1
B _{10d} NC/NO contact:	25.000.000
at 20% contact load	

Service life: 20 years

$$MTTF_d = \frac{B_{10d}}{0,1 \times n_{op}} \quad n_{op} = \frac{d_{op} \times h_{op} \times 3600 \text{ s/h}}{t_{cycle}}$$

Note



Enabling zone

The actuators for the magnetic safety sensors must be ordered separately.

Contact variants

1 NO / 1 NC contacts

BK 13 → 14 BU

WH 21 → 22 BN

1 NO / 2 NC contacts

BK 22 → 14 BU

WH 32 → C BN

1 NO / 2 NC (Ordering suffix -2187)

GY 13 → 14 PK

GN 21 → 22 YE

WH 31 → 32 BN

2 NC (Ordering suffix -2187)

BK 11 → 12 BU

WH 21 → 22 BN


Note

Contact symbols shown for the closed condition of the guard device.


The contact configuration for versions with or without LED is identical.

Safety sensors

System components



Actuating magnet EX-BPS 33



Spacer BN 31/BNS 33


Ordering details

Actuating magnet
Spacer

EX-BPS 33
BN 31/BNS 33

Safety sensors

EX-BNS 120-...-3G/D



- Ex certified
- Thermoplastic enclosure
- long life, no mechanical wear
- Protection class IP67
- Intensitive to transverse misalignment
- Intensitive to soiling
- Particularly large switching distance
- Suitable for food processing industry

Technical data

Equipment category:	Ex II 3GD
Ex protection:	Ex nC IIC T6 X Ex tD A22 IP67 T80°C X
Standards:	EN 60947-5-3, EN 61241-0, EN 61241-1, EN 60079-0, EN 60079-15, BG-GS-ET-14
Design:	cylindrical
Enclosure:	glass-fibre reinforced thermoplastic, tightening torque A/F 17 max. 90 Ncm
Max. impact energy:	1 J
Protection class:	IP67 to EN 60529
Connection:	Boflex cable
Cable section:	4 x 0.25 mm ²
Operating principle:	magnetic
Actuating magnet:	BP 6, BP 8, BP 10, BP 15 SS, not coded 10 mm (BP 6 / BP 8) 20 mm (BP 10 / BP 15 SS) 22 mm (BP 6 / BP 8) 32 mm (BP 10 / BP 15 SS)
S _{ao} :	–
S _{ar} :	–
Switching condition indication:	–
Switching voltage max. :	100 VAC/DC
Switching current max. :	250 mA
Switching capacity max. :	02z: 3 W -11z, -12z: 5 W
Ambient temperature:	- 25 °C ... + 70 °C
Storage and transport temperature:	- 25 °C ... + 70 °C
Max. switching frequency:	5 Hz
Resistance to shock:	30 g / 11 ms
Resistance to vibration:	10 ... 55Hz, Amplitude 1 mm

Classification:

Standards:	EN ISO 13849-1
B _{10d} NC/NO contact:	25.000.000 at 20% contact load
Service life:	20 years

$$MTTF_d = \frac{B_{10d}}{0,1 \times n_{op}} \quad n_{op} = \frac{d_{op} \times h_{op} \times 3600 \text{ s/h}}{t_{cycle}}$$

Contact variants

1 NO / 1 NC contacts

BK 13 → 14 BU

WH 21 → 22 BN

1 NO / 2 NC contacts

BK 22 → 14 BU

WH 32 → C BN

2 NC contacts

BK 11 → 12 BU

WH 21 → 22 BN

Approvals




Ordering details

EX-BNS 120-①z-3G/D

N°	Option	Description
①	11	1 NO / 1 NC contacts
	12	1 NO / 2 NC contacts
	02	2 NC contacts

Note



Enabling zone

The actuators for the magnetic safety sensors must be ordered separately.


Note

Contact symbols shown for the closed condition of the guard device.


The safety sensor is to be installed in such a way that operation with a magnet is not possible (covered installation in accordance with EN 1088).

Safety sensors


System components




BP 6



BP 8



BP 10



BP 15 SS

Ordering details

Actuating magnets:

unenclosed

unenclosed

unenclosed

stainless steel

BP 6


BP 8

BP 10

BP 15 SS

Safety sensors

EX-BNS 180-...-3G/D



- Ex certified
- Thermoplastic enclosure
- long life, no mechanical wear
- Protection class IP67
- Intensitive to transverse misalignment
- Intensitive to soiling
- Particularly large switching distance
- Suitable for food processing industry

Technical data

Equipment category:	Ex II 3GD
Ex protection:	Ex nC IIC T6 X Ex tD A22 IP67 T80°C X
Standards:	EN 60947-5-3, EN 61241-0, EN 61241-1, EN 60079-0, EN 60079-15, BG-GS-ET-14
Design:	cylindrical
Enclosure:	glass-fibre reinforced thermoplastic, tightening torque A/F 24 max. 500 Ncm
Max. impact energy:	1 J
Protection class:	IP67 to EN 60529
Connection:	Boflex cable
Cable section:	6 x 0.25 mm ²
Operating principle:	magnetic
Actuating magnet:	BP 6, BP 8, BP 10, BP 15 SS, not coded 8 mm (BP 6 / BP 8) 18 mm (BP 10 / BP 15 SS)
S_{ao} :	20 mm (BP 6 / BP 8) 28 mm (BP 10 / BP 15 SS)
S_{ar} :	
Switching voltage max.	
without LED:	120 VAC/DC
Switching current:	max. 250 mA
Switching capacity:	max. 5 W
Ambient temperature:	- 25 °C ... + 70 °C
Storage and transport	
temperature:	- 25 °C ... + 70 °C
Max. switching frequency:	5 Hz
Resistance to shock:	30 g / 11 ms
Resistance to vibration:	10 ... 55Hz, Amplitude 1 mm

Classification:

Standards:	EN ISO 13849-1
B_{10d} NC/NO contact:	25.000.000
	at 20% contact load

Service life: 20 years

$$MTTF_d = \frac{B_{10d}}{0,1 \times n_{op}} \quad n_{op} = \frac{d_{op} \times h_{op} \times 3600 \text{ s/h}}{t_{cycle}}$$

Contact variants

1 NO / 2 NC contacts

GY 13 → 14 PK
GN 21 → 22 YE
WH 31 → 32 BN


Approvals



Ordering details

EX-BNS 180-12z-2187-2-3G/D

Note



Enabling zone

The actuators for the magnetic safety sensors must be ordered separately.


Note

Contact symbols shown for the closed condition of the guard device.


The safety sensor is to be installed in such a way that operation with a magnet is not possible (covered installation in accordance with EN 1088).

Safety sensors


System components




BP 6



BP 8



BP 10



BP 15 SS

Ordering details

Actuating magnets:

unenclosed

unenclosed

unenclosed

stainless steel

BP 6


BP 8

BP 10

BP 15 SS

Safety sensors

EX-BNS 303-...-3G/D



- Ex certified
- Thermoplastic enclosure
- with coding
- long life, no mechanical wear
- Protection class IP67
- Intensitive to transverse misalignment
- Intensitive to soiling
- Suitable for food processing industry
- LED version available

Technical data

Equipment category:	Ex II 3GD
Ex protection:	Ex nC IIC T6 X
Standards:	Ex tD A22 IP67 T80°C X EN 60947-5-3, EN 61241-0, EN 61241-1, EN 60079-0, EN 60079-15, BG-GS-ET-14
Design:	cylindrical
Enclosure:	glass-fibre reinforced thermoplastic, tightening force A/F 36 mm max. 300 Ncm
Max. impact energy:	1 J
Protection class:	IP67 to EN 60529
Connection:	Boflex cable
Cable section:	6 x 0.25 mm ²
Operating principle:	magnetic
Actuating magnet:	BPS 300, BPS 303, BPS 303 SS, coded
S _{ao} :	5 mm
S _{ar} :	15 mm
Switching condition indication:	LED only with ordering suffix G
Max. switching voltage without LED:	max. 100 VAC/DC
with LED:	max. 24 VDC
Max. switching current without LED:	max. 400 mA
with LED:	10 mA
Max. switching capacity without LED:	10 W
with LED:	240 mW
Ambient temperature:	- 25 °C ... + 70 °C
Storage and transport temperature:	- 25 °C ... + 70 °C
Max. switching frequency:	5 Hz
Resistance to shock:	30 g / 11 ms
Resistance to vibration:	10 ... 55Hz, Amplitude 1 mm

Classification:

Standards:	EN ISO 13849-1
B _{10d} NC/NO contact:	25.000.000
at 20% contact load	
Service life:	20 years

$$MTTF_d = \frac{B_{10d}}{0,1 \times n_{op}} \quad n_{op} = \frac{d_{op} \times h_{op} \times 3600 \text{ s/h}}{t_{cycle}}$$

Approvals




Ordering details

EX-BNS 303-12z①-2187-3G/D

N°	Option	Description
①	G	without LED with LED

Note



Enabling zone

The actuators for the magnetic safety sensors must be ordered separately.

Contact variants

1 NO contacts

GY 13 → 14 PK
GN 21 → 22 YE
WH 31 → 32 BN

2 NC contacts

GY 13 → 14 PK
GN 21 → 22 YE
WH 31 → 32 BN

Note


Contact symbols shown for the closed condition of the guard device.

The contact configuration for versions with or without LED is identical.


The LED is illuminated when the guard door is open.

Safety sensors


System components



BPS 300



BPS 303




BPS 303 SS

Ordering details

Actuating magnet:	
with plastic enclosure	BPS 300
with plastic enclosure for food-processing industry	BPS 303
Stainless steel for food-processing industry	BPS 303 SS

Safety sensors

EX-CSS 180-...-3G/D



- Ex certified
- Thermoplastic enclosure
- Category 4 to EN 954-1
- Classification PDF-M to EN 60947-5-3
- Fit for SIL 3 applications to IEC 61508, PFH value $< 6.1 \times 10^{-9}$
- Electronic contact-free, coded system
- Large switching distance
- Misaligned actuation possible
- High repeat accuracy of the switching points
- Self-monitored series-wiring of max. 16 sensors
- Max. length of the sensor chain 200 m
- Comfortable diagnostics through sensor LED and electronic signalling output
- Early warning when operating near the limit of the sensor's hysteresis range
- 2 short-circuit proof PNP safety outputs (24 VDC per 500 mA)


Approvals



Ordering details


EX-CSS 8-180-2P+D-M-L-3G/D

Note



Legend


- S switching distance
- V axial misalignment
- S_{on} switch-on point
- S_{off} switch-off point
- S_h hysteresis range
- S_{ao} assured switch-on point
- S_{ar} Assured release point to EN 60947-5-3




Technical data

Equipment category:	Ex II 3GD
Ex protection:	Ex nA IIC T6 X
Standards:	Ex tD A22 IP67 T70°C X EN 60947-5-3, EN 954-1, IEC 61508, EN 61241-0, EN 61241-1, EN 60079-0, EN 60079-15
Design:	cylindrical
Enclosure:	glass-fibre reinforced thermoplastic
Max. impact energy:	1 J
Protection class:	IP65 and IP67
Termination:	Cable
Cable section:	7 x 0.25 mm ²
Cable length:	max. 200 m
Operating principle:	inductive
Actuator:	CST-180-1, CST-180-2
Category:	4 to EN 954-1
Classification:	up to PDF-M to IEC 60947-5-3
SIL classification:	suitable for SIL 3 applications to IEC 61508, PFH < 6.1×10^{-9}
Rated switching distance S_n :	8 mm
S_{ao} :	7 mm
S_{ar} :	10 mm
Hysteresis:	≤ 0.7 mm
Repeat accuracy R:	≤ 0.2 mm
Response time:	< 30 ms
Duration of risk:	≤ 30 ms
U_e :	24 VDC – 15 % / + 10 %
I_e :	1.0 A
I_o :	0.05 A
Leakage current I_r :	≤ 0.5 mA
Protection class:	II
Oversupply category:	III
Degree of pollution:	3
U_{imp} :	0.8 kV
U_i :	32 VAC/DC
Safety outputs:	short-circuit proof, p-type
Output current:	max. 0.5 A each output
U_d :	max. 0.5 V
I_e/U_e :	0.5 A / 24 VDC
Signalling output:	short-circuit proof, p-type
I_e/U_e :	0.05 A / 24 VDC
Utilisation category:	AC-12, DC-13
Ambient temperature:	- 20 °C ... + 40 °C
Storage and transport temperature:	- 25 °C ... + 85 °C
Switching frequency f:	ca. 3 Hz
Resistance to shock:	30 g / 11 ms
Resistance to vibration:	10 ... 55Hz, Amplitude 1 mm


System components



CST -180-1 actuator



CST -180-2 actuator



H 18 clamp


Safety sensors

Connection

Sensor with multifunctional connection:
EX-CSS 8-180-2P+D-M-L-3G/D

Connecting cable:

2 m length;
cable section 7 poles: 7 x 0.25 mm²



Wiring

Lead colours Connecting cable	Wiring
BN (brown)	A1 Ue
BU (blue)	A2 GND
VT (violet)	X1 Safety input 1
WH (white)	X2 Safety input 2
BK (black)	Y1 Safety output 1
RD (red)	Y2 Safety output 2
GY (grey)	Signalling output

Safety-monitoring module

Requirements for the safety monitoring module

2-channel p-type safety input. The safety monitoring module must tolerate internal functional tests of the sensors in milliseconds (max. 2 ms).

A range of suitable **safety monitoring modules** for these applications can be found in the „Electronic Safety Sensors and Solenoid Interlocks“ brochure.

Note

- Series-wiring of sensors:
16 self-monitoring CSS 180 safety sensors can be wired in series without loss of control category 4 to EN 954-1. The redundant output of the first sensor is wired into the input of the next sensor.
- The voltage drop over a long sensor chain should be taken into account when planning cable routing. It depends on several factors which are operating voltage, cable length, ambient temperature, number of sensors series connected, and input load of the safety control monitor.

Ordering details



Detailed technical information at:
www.schmersal.com

Magnetic reed switches



Magnetic reed switches are often used to replace mechanically actuated limit switches with plungers, roller and turning levers.


Content

EX-BN 20-...-3G/D

106

Magnetic reed switches

EX-BN 20-...-3G/D



- Ex certified
- Aluminium enclosure
- Long life
- Non-contact principle
- 1 Reed contact
- Particularly resistant to vibration
- Available for actuation from front or side
- Actuating distance up to 50 mm depending on actuating magnet and version
- Screw connection
- Protection class IP67
- 2 cable entries M 16
- Including Ex-certified screwed cable gland


Technical data

Equipment category:	Ex II 3GD
Ex protection:	Ex nC IIC T5 X
Standards:	Ex tD A22 IP67 T90°C X EN 61241-0, EN 61241-1, EN 60079-0, EN 60079-15
Enclosure:	Al Si12 die-casting, painted 4 J
Max. impact energy:	IP67 to EN 60529
Protection class:	screw terminals
Connection:	2x M16
cable entry:	magnetic
Operating principle:	max. 250 VAC/DC
Switching voltage:	max. 3 A
Switching current:	max. 120 VA/W
Switching capacity:	> 600 VAC (50 Hz)
Dielectric strength:	max. 18 m/s
Switching speed:	max. 300 S/s
Switching frequency:	Switching time
	"Close": 0.3 ms ... 1.5 ms "Open": max. 0.5 ms
	Bounce duration: 0.3 ms ... 0.6 ms
	Ambient temperature: -15 °C ... +70 °C
	Storage temperature: -25 °C ... +70 °C
	Mechanical life: 10 ⁸ operations
	Electrical life: 1 million - 1 billion operations, depending on load
	Resistance to vibration: 50 g on sine wave oscillation
	Switching point accuracy: ± 0.25 mm, T = constant
	Resistance to shock: 30 g / 11 ms
	Resistance to vibration: 10 ... 55 Hz
	Cable cross-section of the cable glands: Amplitude 1 mm
	min. Ø 6 mm max. Ø 10 mm


Switching distances, refer to next page.

Contact variants


1 NO contact EX-BN 20-10z
1 NC contact EX-BN 20-01z
with N-S actuating magnet BP 2



1 bistable contact EX-BN 20-rz
with N actuating magnet BP 20N



1 bistable contact EX-BN 20-rz
with S actuating magnet BP 20S



Approvals




Ordering details

EX-BN 20-①Z-3G/D

N°	Insert	Description
①	01	1 NC contacts
	02	2 NC contacts
	10	1 NO contacts
	20	2 NO contacts
	11	1 NC / 1 NO contact
R		1 bistable contact
2R		2 bistable contact
11R		2 bistable contact 1 NC / 1 NO

Note



Switching capacity

Note


In version -10 and -01: When the switches and actuators come together, the colours must coincide: Red (S) to red (S) and green (N) to green (N).

The actuators for the magnetic safety sensors must be ordered separately.


On the next pages, a range of suitable actuating magnets is presented.

Magnetic reed switches

Switch distances			System components
Actuating magnet	EX-BN 20-10z EX-BN 20-20z EX-BN 20-01z EX-BN 20-02z EX-BN 20-11z	EX-BN 20-rz EX-BN 20-2rz EX-BN 20-11rz	
BP 10 N		5	
BP 10 S		5	
2 x BP 10	12		
2 x BP 10 N		10	
2 x BP 10 S		10	
BP 15 N		7	
BP 15 S		7	
2 x BP 15/2	12		
2 x BP 15/2 N		15	
2 x BP 15/2 S		15	
BP 34 N		10-25	
BP 34 S		10-25	
BP 20	15		
BP 20 N		15	
BP 20 S		15	
BP 31	15		
BP 31 N		15	
BP 31 S		15	
BP 11	15		
BP 11 N		5	
BP 11 S		5	
2 x BP 11 N		15	
2 x BP 11 S		15	
BP 12	25		
BP 12 N		10	
BP 12 S		10	
2 x BP 12 N		5-20	
2 x BP 12 S		5-20	
BP 21	20-45		
BP 21 N		10-35	
BP 21 S		10-35	
2 x BP 21 N		15-50	
2 x BP 21 S		15-50	



EX-certified screwed cable gland



EX-certified screw plug

Ordering details

EX-certified
screwed cable gland


EX-KLE-M16x1.5

EX-certified
screw plug

EX-VS-M16x1.5


Magnetic reed switches

System components




BP 10

System components




BP 20


System components




BP 11




BP 15




BP 20 N / BP 20 S




BP 11 N / BP 11 S




BP 15/2




BP 31




2x BP 11 N / 2x BP 11 S



BP 34



BP 31 N / BP 31 S



BP 12

Ordering details

Actuating magnet
Unenclosed, N-S
Thermoplastic enclosure, N-S
Unenclosed, N-S
Thermoplastic enclosure, N-S

BP 10
BP 15
BP 15/2
BP 34

Ordering details

Actuating magnet
metal enclosure Al, N-S
metal enclosure Al, N
metal enclosure Al, S
Thermoplastic enclosure, N-S
Thermoplastic enclosure, N-S
Thermoplastic enclosure, N-S


BP 20
BP 20 N
BP 20 S
BP 31
BP 31 N
BP 31 S

Ordering details

Actuating magnet
metal enclosure Al, N-S
metal enclosure Al, N
metal enclosure Al, S
metal enclosure Al, 2x N
metal enclosure Al, 2x S
metal enclosure Al, N-S

BP 11
BP 11 N
BP 11 S
2x BP 11 N
2x BP 11 S
BP 12

Magnetic reed switches



Ordering details

Actuating magnet	
metal enclosure Al, N	BP 12 N
metal enclosure Al, S	BP 12 S
metal enclosure Al, 2x N	2x BP 12 N
metal enclosure Al, 2x S	2x BP 12 S
metal enclosure Al, N-S	BP 21
metal enclosure Al, N	BP 21 N
metal enclosure Al, S	BP 21 S

Ordering details

Actuating magnet	
metal enclosure Al, 2x N	2x BP 21 N
metal enclosure Al, 2x S	2x BP 21 S

Ordering details



Detailed technical information at:
www.schmersal.com

Control devices and indicator lights



The entire EX-R programme has a modular structure. Each control device \and allows a great diversity of variants: various versions of push-buttons and illuminated buttons, indicator lights, emergency-stop buttons, selector switches and key-operated selector switches are available.

Content	
EX-RDT...	114
EX-RDM...	114
EX-RDL...	115
EX-RDLM...	115
EX-RMLH...	116
EX-RDP40...	117
EX-RDRZ45...	118
EX-RDRZ45rt	119
EX-RW...21/32	120
EX-RW...21.1/32.1	120
EX-RS...	122
EX-RF 10...	124
EX-RF 03...	124
EX-RLDE ws 24	125
EX-EBG 311.O	126
EX-EBG 633.O	126
EX-EBG 665.O	126

Control devices and indicator lights

General description

Concept

With the development of the new programme of 22 mm Ex control devices and indicator lights, Elan provides the user with a state-of-the-art switchgear concept that is compliant to EN 61241 and EN 60 079, featuring additional device functionality, reliability and spatial use beyond the usual standard. The EX-RF/RLDE contact and light element system makes a special contribution here.

Well-tried and proven features and material from earlier Elan designs (metal front parts, caps in high-quality shock-proof thermoplastic) have been retained and improved.

The equipment is suitable for the Ex category II 2GD. The explosion protection or the type of protection of the devices is:

- Ex ib IIC T4 X
- Ex tD A21 IP65 T110°C X

Control devices and indicator light heads

A large diversity of fully insulated pushbuttons/impact buttons/illuminated buttons/pivoting pushbuttons etc. is offered. The front part of the actuating head is in chrome-plated brass. The programme is characterised by large actuating surfaces of at least 28 mm. The material of the button is brass-coated. The caps or lens covers of the illuminated pushbuttons and indicator lights are in shock-proof thermoplastic. In addition to the high mechanical strength, this material selection permits a more than average degree of resistance to heat and chemical effects.

Protection class

The front seal of these devices corresponds to protection class IP65 to EN DIN 60 529. The design features of the device sealing guarantee the maximum of protection over a long period of time, even in extreme conditions.

Mechanical protection

Mechanical tests are carried out in accordance with EN 60079-0. The enclosures or the exterior part of the enclosure, pushbuttons must withstand a high impact energy.

Programme structure

A control and indicator device consists of an actuator, a mounting flange and a contact or light element. The type designation of this type series starts with EX-R..., e. g. EX-RDT for a pushbutton. The mounting flange (divided into two, type EX-RLM) is included in the delivery of the device heads, both for the operating and the display elements.

Per control device, a maximum of 2 contact elements is provided.

One-hole fixing

The devices are designed for mounting holes of 22.3 mm + 0.4 mm according to DIN EN 60 947-5-1 Pt. 6.3.1. An additional cut-out to prevent rotation is not required.

Spacing

It is possible to install several devices with minimum dimensions in the following way:

Minimum distance between the mounting holes to DIN EN 60 947-5-1:

- horizontal: 40 mm
- vertical: 50 mm

Exceptions:

Selector switches/pushbuttons with long knob, emergency stop buttons EX-RDRZ45...:

- horizontal: 50 mm
- vertical: 60 mm


Mechanical protection to EN 60 079-0

Risk of mechanical hazard	High		Low	
	I	II	I	II
Group				
Enclosure and external accessible parts of the enclosure	20 Nm	7 Nm	7 Nm	4 Nm
Translucent parts without safety guard	7 Nm	4 Nm	4 Nm	2 Nm
	No further protective measures required		Mechanical protected fitting	

Control devices and indicator lights


Assembly schematic

Pushbutton




Fixing flange


Mounting flange





Contact carrier with contact
lugs and 2 plunger elements



Light element with integrated multi-LED



Contact elements




Control devices and indicator lights – Pushbuttons

EX-RDT...




• Pushbutton



EX-RDM...



• Pushbutton with membrane



Technical data

Equipment category:	Ex II 2GD
Ex protection:	Ex ib IIC T4 X
Standards:	Ex tD A21 IP65 T110°C X EN 60947-5-1, EN 60947-1, EN 61241-0, EN 61241-1, EN 60079-0, EN 60079-11
Max. impact energy (EN 60079-0):	7 J
Design:	round
Installation-ø:	22.3 mm
Grid dimensions:	40 x 50 mm
Front plate thickness:	1 ... 6 mm
Mounting position:	random
Designation:	identification plates, symbols
Climatic resistance to DIN EN 60068:	Part 2-30
Ambient temperature:	-20 °C ... + 55 °C
Switching frequency:	1,000 s/h
Protection class to EN 60529:	IP65
Full insulation Materials:	yes
Membranes:	PC (good resistance to chemical agents)
Front ring/buttons:	chrome-plated brass, powder-coated brass with mounting flange
Fixing:	
Max. tightening torque:	2 Nm
Resistance to shocks to EN 60068-2-27:	< 50 g
Resistance to vibrations to EN 60068-2-6:	5 g
Actuating stroke:	4 mm
Actuating force:	without membrane approx. 1.5 N with membrane approx. 2 N
Mechanical life:	1 x 10 ⁶ operations
Rohs conformity:	yes

Approvals



Approvals



Ordering details

Ex-RDT ① ②

N°	Option	Description
①	bk	black
	ye	yellow
	rd	red
	gn	green
	wh	white
	bu	blue
②	Identification plate, symbols: refer to page 128	

Ordering details

Ex-RDM ① ②


N°	Option	Description
①	bk	black
	ye	yellow
	rd	red
	gn	green
	wh	white
	bu	blue
②	Identification plate, symbols: refer to page 128	

Note

The EX-RLM fixing flange, consisting of mounting flange, contact carrier with contact lugs and 2 plunger elements, is not included in the delivery of the device heads (refer to page 127)


Control devices and indicator lights – Illuminated pushbuttons

EX-RDL...



• Illuminated pushbutton

EX-RDLM...



• Illuminated pushbutton with membrane

Technical data

Equipment category:	Ex II 2GD
Ex protection:	Ex ib IIC T4 X
Standards:	Ex tD A21 IP65 T110°C X EN 60947-5-1, EN 60947-1, EN 61241-0, EN 61241-1, EN 60079-0, EN 60079-11
Max. impact energy:	4 J
Design:	round
Installation-Ø:	22.3 mm
Grid dimensions:	40 x 50 mm
Front plate thickness:	1 ... 6 mm
Mounting position:	random
Designation:	identification plates, symbols
Climatic resistance to DIN EN 60068:	Part 2-30
Ambient temperature:	-20 °C ... + 55 °C
Switching frequency:	1,000 s/h
Protection class to EN 60529:	IP65
Full insulation	yes
Materials:	
Membranes:	PC (good resistance to chemical agents)
Front ring/buttons:	chrome-plated brass, powder-coated brass with mounting flange
Fixing:	
Max. tightening torque:	2 Nm
Resistance to shocks to EN 60068-2-27:	< 50 g
Resistance to vibrations to EN 60068-2-6:	5 g
Actuating stroke:	4 mm
Actuating force:	ca. 1.5 N
Mechanical life:	1 x 10 ⁶ operations
Rohs conformity:	yes

Approvals



Approvals



Ordering details

Ex-RDL ① ②

N°	Option	Description
①	bk	black
	ye	yellow
	rd	red
	gn	green
	wh	white
	bu	blue
②	Identification plate, symbols: refer to page 128	

Ordering details

Ex-RDLM ① ②


N°	Option	Description
①	bk	black
	ye	yellow
	rd	red
	gn	green
	wh	white
	bu	blue
②	Identification plate, symbols: refer to page 128	

Note

The EX-RDM fixing flange, consisting of mounting flange, contact carrier with contact lugs and 2 plunger elements, is not included in the delivery of the device heads (refer to page 127)

Control devices and indicator lights – Indicator lights

EX-RMLH...



• Indicator light with domed cap

Technical data

Equipment category:	II 2GD
Ex protection:	Ex ib IIC T4 X
	Ex tD A21 IP65 T110°C X
Standards:	EN 60947-5-1, EN 60947-1, EN 61241-0, EN 61241-1, EN 60079-0, EN 60079-11
Max. impact energy:	4 J
Design:	round
Installation-ø:	22.3 mm
Grid dimensions:	40 x 50 mm
Front plate thickness:	1 ... 6 mm
Mounting position:	random
Designation:	identification plates, symbols
Climatic resistance to DIN EN 60068:	Part 2-30
Ambient temperature:	-20 °C ... + 55 °C
Protection class to EN 60529:	IP65
Full insulation	yes
Materials:	
Lens covers	PC (good resistance to chemical agents)
Front ring/buttons:	chrome-plated brass, powder-coated brass with mounting flange
Fixing:	
Max. tightening torque:	2 Nm
Resistance to shocks to EN 60068-2-27:	< 50 g
Resistance to vibrations to EN 60068-2-6:	5 g
Rohs conformity:	yes

Approvals



Ordering details

Ex-RMLH ① ②

N°	Option	Description
①	ye	yellow
	rd	red
	gn	green
	wh	white
	bu	blue
②	Identification plate, symbols: refer to page 128	

Note

The EX-RLM fixing flange, consisting of mounting flange, contact carrier with contact lugs and 2 plunger elements, is not included in the delivery of the device heads (refer to page 127)


Control devices and indicator lights – Mushroom buttons

EX-RDP40...



Technical data

Equipment category:	Ex II 2GD
Ex protection:	Ex ib IIC T4 X
	Ex tD A21 IP65 T110°C X
Standards:	EN 60947-5-1, EN 60947-1, EN 61241-0, EN 61241-1, EN 60079-0, EN 60079-11
Max. impact energy:	4 J
Design:	round
Installation-ø:	22.3 mm
Grid dimensions:	50 x 60 mm
Front plate thickness:	1 ... 6 mm
Mounting position:	random
Designation:	identification plates, symbols
Climatic resistance to DIN EN 60068:	Part 2-30
Ambient temperature:	-20 °C ... + 55 °C
Switching frequency:	1,000 s/h
Protection class to EN 60529:	IP65
Full insulation	yes
Materials:	
Front ring/buttons:	chrome-plated brass, powder-coated brass with mounting flange
Fixing:	
Max. tightening torque:	2 Nm
Resistance to shocks to EN 60068-2-27:	< 50 g
Resistance to vibrations to EN 60068-2-6:	5 g
Actuating stroke:	4 mm
Actuating force:	approx. 2 N
Mechanical life:	1 x 10 ⁶ operations
Rohs conformity:	yes



- Mushroom button without latching function

Approvals



Ordering details

Ex-RDP40 ① ②

N°	Option	Description
----	--------	-------------

①	bk ye rd gn wh bu	black yellow red green white blue
---	----------------------------------	--


② Identification plate, symbols: refer to page 128

Note

The EX-RLM fixing flange, consisting of mounting flange, contact carrier with contact lugs and 2 plunger elements, is not included in the delivery of the device heads (refer to page 127)

Control devices and indicator lights – Mushroom buttons

EX-RDRZ45...



- Mushroom button with latching function

Technical data

Equipment category:	II 2GD
Ex protection:	Ex ib IIC T4 X
	Ex tD A21 IP65 T110°C X
Standards:	EN 60947-5-1, EN 60947-1, EN 61241-0, EN 61241-1, EN 60079-0, EN 60079-11
Max. impact energy:	4 J
Design:	round
Installation-ø:	22.3 mm
Grid dimensions:	50 x 60 mm
Front plate thickness:	1 ... 6 mm
Mounting position:	random
Climatic resistance to DIN EN 60068:	Part 2-30
Ambient temperature:	-20 °C ... + 55 °C
Switching frequency:	600 s/h
Protection class to EN 60529:	IP65
Full insulation	yes
Materials:	
Front ring/buttons:	chrome-plated brass, powder-coated brass with mounting flange
Fixing:	
Max. tightening torque:	2 Nm
Resistance to shocks to EN 60068-2-27:	< 50 g
Resistance to vibrations to EN 60068-2-6:	5 g
Actuating stroke:	5 mm
Actuating force:	approx. 2 N
Mechanical life:	1 x 10 ⁵ operations
Rohs conformity:	yes

Approvals



Ordering details

Ex-RDRZ45 ① ②


N°	Option	Description
①	bk	black
	ye	yellow
	gn	green
②	Identification plate, symbols: refer to page 128	

Note

The EX-RLM fixing flange, consisting of mounting flange, contact carrier with contact lugs and 2 plunger elements, is not included in the delivery of the device heads (refer to page 127)

Control devices and indicator lights – Emergency stop buttons

EX-RDRZ45rt



- Emergency stop button to ISO 13850, 2006

Technical data

Equipment category:	Ex II 2GD
Ex protection:	Ex ib IIC T4 X
	Ex tD A21 IP65 T110°C X
Standards:	EN 60947-5-1; EN 60947-5-5 EN 60947-1; EN 61241-1 EN 60079-0; EN 60079-11
Max. impact energy:	4 J
Design:	round
Installation-Ø:	22.3 mm
Grid dimensions:	50 x 60 mm
Front plate thickness:	1 ... 6 mm
Mounting position:	random
Climatic resistance to DIN EN 60068:	Part 2-30
Ambient temperature:	-20 °C ... + 55 °C
Switching frequency:	600 s/h
Protection class to EN 60529:	IP65
Full insulation	yes
Materials:	
Front ring/buttons:	chrome-plated brass, powder-coated brass with mounting flange
Fixing:	
Max. tightening torque:	2 Nm
Resistance to shocks to EN 60068-2-27:	< 50 g
Resistance to vibrations to EN 60068-2-6:	5 g
Actuating stroke:	5 mm
Actuating force:	approx. 2 N
Mechanical life:	1 x 10 ⁵ operations
Rohs conformity:	yes

Approvals



Ordering details


Ex-RDRZ45 rt

Note

The EX-RLM fixing flange, consisting of mounting flange, contact carrier with contact lugs and 2 plunger elements, is not included in the delivery of the device heads (refer to page127)


Control devices and indicator lights

EX-RW...21/32



- Maintained selector switch, spring return selector switch with short knob
- 2 or 3 positions

EX-RW...21.1/32.1



- Maintained selector switch, spring return selector switch with long knob
- 2 or 3 positions

Technical data

Equipment category:	Ex II 2GD
Ex protection:	Ex ib IIC T4 X
Standards:	Ex tD A21 IP65 T110°C X EN 60947-5-1, EN 60947-1, EN 61241-0, EN 61241-1, EN 60079-0, EN 60079-11
Max. impact energy:	4 J
Design:	round
Installation-ø:	22.3 mm
Grid dimensions:	50 x 60 mm
Front plate thickness:	1 ... 6 mm
Mounting position:	random
Designation:	identification plates, symbols
Climatic resistance to DIN EN 60068:	Part 2-30
Ambient temperature:	0 °C ... + 55 °C
Switching frequency:	1,000 s/h
Protection class to EN 60529:	IP65
Full insulation	yes
Materials:	
Knob:	PC (good resistance to chemical agents)
Front ring/buttons:	chrome-plated brass, powder-coated brass
Fixing:	with mounting flange
Max. tightening torque:	2 Nm
Resistance to shocks to EN 60068-2-27:	< 50 g
Resistance to vibrations to EN 60068-2-6:	5 g
Actuating stroke:	6 mm
Actuating force:	approx. 0.2 N
Mechanical life:	3 x 10 ⁵ operations
Rohs conformity:	yes

Approvals



Approvals



Ordering details

Ex-RW① ②

N°	Option	Description
①	T	Selector switch
	S	Selector switch
	ST	Spring-return rotary selector switch
	TS	Maintained spring-return rotary selector switch
	21	2 positions
②	32	3 positions

Ordering details













Ex-RW① ②.1

N°	Option	Description
①	T	Selector switch
	S	Selector switch
	ST	Spring-return rotary selector switch
	TS	Maintained spring-return rotary selector switch
	21	2 positions
②	32	3 positions

Note


The EX-RLM fixing flange, consisting of mounting flange, contact carrier with contact lugs and 2 plunger elements, is not included in the delivery of the device heads (refer to page 127)

Control devices and indicator lights

Brief description	Switching angle	Type
Spring-return rotary selector switch with 2 positions	1 x 55°	 
Selector switch with 2 latched positions	1 x 70°	 
Maintained spring-return rotary selector switch with 3 positions	2 x 35°	 
Selector switch with 3 positions; right: latching, left: switching	right 35 left 55°	 
Maintained spring-return rotary selector switch with 3 positions	2 x 55°	 
Maintained spring-return rotary selector switch with 3 positions, right: switching, left: latching	right 55 left 35°	 

Control devices and indicator lights

EX-RS...



- Key-operated selector switch
- 1, 2 or 3 positions

Technical data

Equipment category:	Ex II 2GD
Ex protection:	Ex ib IIC T4 X
	Ex tD A21 IP65 T110°C X
Standards:	EN 60947-5-1, EN 60947-1, EN 61241-0, EN 61241-1, EN 60079-0, EN 60079-11
Max. impact energy:	4 J
Design:	round
Installation-ø:	22.3 mm
Grid dimensions:	40 x 50 mm
Front plate thickness:	1 ... 6 mm
Mounting position:	random
Designation:	identification plates, symbols
Climatic resistance to DIN EN 60068:	Part 2-30
Ambient temperature:	0 °C ... + 55 °C
Switching frequency:	1,000 s/h
Protection class to EN 60529:	IP65
Full insulation	yes
Materials:	
Front ring/buttons:	chrome-plated brass, powder-coated brass with mounting flange
Fixing:	
Max. tightening torque:	2 Nm
Resistance to shocks to EN 60068-2-27:	< 50 g
Resistance to vibrations to EN 60068-2-6:	5 g
Actuating stroke:	6 mm
Actuating force:	approx. 0.2 N
Mechanical life:	1 x 10 ⁵ operations
Rohs conformity:	yes

Approvals



Ordering details

Ex-RS^{①②③}S^④

N°	Option	Description
①	S	Key-operated selector switch
	ST	Key-operated spring-return selector switch
②	2	position of the key
	3	
③	2	number of plungers
	3	
④	1	position for key retraction
	2	
	3	

Note

The EX-RLM fixing flange, consisting of mounting flange, contact carrier with contact lugs and 2 plunger elements, is not included in the delivery of the device heads (refer to page 127)

Control devices and indicator lights

Key-operated selector switches/selector switch pushbuttons, lock EKM 30

Brief description	Key-withdrawal position	Type
Key-operated selector switch with 2 latched positions	only left only right in both positions	Ex-RSS21S1 Ex-RSS21S2 Ex-RSS21S12
Key-operated selector switch with 3 latched positions	left middle right in all 3 positions	Ex-RSS32S1 Ex-RSS32S2 Ex-RSS32S3 Ex-RSS32S123
Key-operated spring-return selector switch with 1 touch position, automatic return to the zero position, latch position 55°	only left	Ex-RST21S1
Key-operated spring-return selector switch with 2 touch positions left and right, automatic return to the zero position	only middle	Ex-RST32S2
Key-operated selector switch pushbutton with 3 positions, touch position 35°, latch position 55° – left switching, right latching	S1 = only left S2 = only middle	Ex-RSST32S1 Ex-RSST32S2
Key-operated selector switch pushbutton with 3 positions, touch position 35°, latch position 55° – left switching, right latching	S2 = only middle S3 = only right	Ex-RSTS32S2 Ex-RSTS32S3
Spare key EKM 30 for CES lock (for EX-RSS..../RST.., standard for the above listed versions)	SDS2	


Special locks and master key function available: On request

Contact elements: See page 124

2 keys belong to the delivery range of the above listed devices


Control devices and indicator lights – Contacts

EX-RF 10...



- NC
- Screw connection
- Cable sections
 - single-strand 2 × (0.5 ... 2.5 mm²)
 - multi-strand with conductor ferrules 2 × (0.5 ... 1.5 mm³)
- Protection class
 - Connections: IP20 (finger-safe)
 - Wiring compartments: IP40

EX-RF 03...



- NO contacts
- Screw connection
- Cable sections
 - single-strand 2 × (0.5 ... 2.5 mm²)
 - multi-strand with conductor ferrules 2 × (0.5 ... 1.5 mm³)
- Protection class
 - Connections: IP20 (finger-safe)
 - Wiring compartments: IP40

Technical data

Equipment category:	Ex II 2GD
Explosion protection:	Ex ib IIC T4 X
Standards:	Ex tD A21 IP65 T110°C X EN 60947-5-1, EN 61241-0, EN 61241-1, EN 60079-11
U _i :	250 V
I _i :	3.3 A for Ex ib 5.0 A at Ex ic
C _i :	~ 0
L _i :	~ 0
U:	250 V
I:	5 A
P:	max. 1500 W
Contact reliability:	5 VDC/1 mA
Proof of positive opening:	2.5 kV impulse voltage
Positive opening path:	approx. 2 mm after achieving opening point
Air clearance and creepage distance to DIN EN 60 664-1:	4 kV/3
Switching frequency:	1.200 s/h
Switching points:	
NC contact:	approx. 1 mm
NO contact:	approx. 2.5 mm
Temperature range:	-20° C ... + 55° C
Climate resistance to DIN EN 60068:	Part 2-20
Mounting position:	random
Mechanical life to EN 60 947-5-1:	10 × 10 ⁶ operations
Actuating force at stroke end:	approx. 4.5 N
Terminal designations:	to EN 60947-1
Tightening torque for the connecting screw:	max. 1 Nm

Approvals



Ordering details

Ex-RF ①

N°	Option	Description
①	10	Contact labelling 1, 2
	10.1	Contact labelling 11, 12

Approvals



Ordering details

Ex-RF ①

N°	Option	Description
①	03	Contact labelling 3, 4
	03.1	Contact labelling 13, 14


Control devices and indicator lights – Light terminal blocks

EX-RLDE ws 24

Technical data



Equipment category:	Ex II 2GD
Explosion protection:	Ex ib IIC T4 X Ex tD A21 IP65 T110°C X
Standards:	EN 60947-5-1, EN 61241-0, EN 61241-1, EN 60079-11
U _i :	30 V
I _i :	not relevant (max. 30 mA)
P _i :	not relevant (max. 30 mA)
C _i :	~ 0
L _i :	~ 0
U:	24 V +/-10%
I:	30 mA
P:	0.9 W
Temperature range:	-20° C ... + 55° C
Climate resistance to DIN EN 60068:	Part 2-20
Mounting position:	random
Terminal designations:	to EN 60947-1
Tightening torque for the connecting screw:	max. 1 Nm



- Light terminal block
- Screw connection
- Cable sections
 - single-strand 2 × (0.5 ... 2.5 mm²)
 - multi-strand with conductor ferrules 2 × (0.5 ... 1.5 mm²)
- Protection class
- Connections: IP20 (finger-safe)
- Wiring compartments: IP40

Approvals




Ordering details

Ex-RLDE ws 24


Control devices and indicator lights – Enclosure

EX-EBG 311.O




- Empty enclosure in V4A
- Version with 1 fitting hole for installation
Ø 22.3 mm
- incl. 1 cable gland M20

EX-EBG 633.O



- Empty enclosure in V4A
- Version with 3 fitting holes for installation
Ø 22.3 mm
- incl. 1 cable gland M25

EX-EBG 665.O



- Empty enclosure in V4A
- Versions with 5 fitting holes for installation
Ø 22.3 mm
- incl. 2 cable glands M25
- incl. 1 locking screw

Approvals



Ordering details

EX-EBG 331.O

Approvals



Ordering details

EX-EBG 633.O

Approvals



Ordering details

EX-EBG 665.O


Control devices and indicator lights – Accessories

System components




Mounting tool RMW

System components



Identification label EX-RZSO



Mounting flange EX-RLM

Ordering details

Mounting tool for mounting flange
Blanking plug

RMW
EX-RB



Ordering details

Identification label
Mounting flange






EX-RZSO
EX-RLM

Control devices and indicator lights – Symbols


Drives

	401 Electric motor		402 Pump general		403 Gear pump		405 Coolant
	406 Oil lubrication		407 Rotary indexing table		408 Shuttle table forward		409 back
	410 Brake fan		411 Caution – live		412 Clamp table rectangular		413 Electrical machine


Signals

	501 On		502 Jog		503 Automatic		504 Off
	505 Everything off		506 On – off		507 Increase of a variable		508 Decrease of a variable
	509 Pause (time elapse)		510 Manual operation		511 Visual		512 Hydraulics

Words

	513		514		515		516
	517		518		519		520
	521		522		523		524

Letters¹

	901		902		903		904
---	------------	---	------------	---	------------	---	------------

Other numerals available, e.g. for number 9 ordering code 709

Control devices and indicator lights – Symbols

Linear motion

	101 Working motion feed		102 Rapid motion or idling		103 Rapid motion		104 Feed
	105 Interrupted motion jogging		106 Reciprocating motion				
	107 Limited motion		108 Indexing		109 Motion in 2 directions		

Rotary motion

	201 Continuous clockwise rotation		202 Anti-clockwise rotation		203 Clockwise rotation STOP		204 Anti-clockwise rotation STOP
	205 1 revolution clockwise		206 Anti-clockwise		207 Rotary indexing		208 Interrupted rotary motion
	209 Clockwise motion restricted		210 Anti-clockwise motion restricted		211 Clockwise motion from a restriction		211 Anti-clockwise motion from a restriction

Additional options

	301 Clamping, chucking		302 Release		303 Braking		304 Release brake
	305 Unlock		306 Lock				

Arabic numerals

	700		701		702		
	801		802		803		

More details



Detailed technical information at:
www.schmersal.net

Key transfer system



The fundamental functional characteristic of a trapped key system is that, depending on the operating condition of the machine control, the key is trapped and cannot be withdrawn.

- in automatic mode (with the safety guard locked) in a control element, usually a key-operated selector switch or
- if the safety guard is open (in an electrically de-energised condition), in the guard locking device, i.e. a lock

Content

EX-SHGV-...-3G/D	134
EX-SVM 1/...-6/...-2G/D	135
EX-SVM 1/...-10/...-2G/D	135
EX-SHGV-...-2G/D	136
EX-SHGV-...-2G/D	136

EX-Trapped key system



Mode of operation

The fundamental functional characteristic of a trapped key system is that, depending on the operating condition of the machine control, the key is trapped and cannot be withdrawn.

- in automatic mode (with the safety guard locked) in a control element, usually a key-operated selector switch or
- if the safety guard is open (in an electrically de-energised condition), in the guard locking device, i.e. a lock

In other words, a principle feature of the system is that the removable key is trapped either in the guard locking device or in the switch lock.

The locking device of the guard is designed in such a way that the trapped key can only be enabled if the guard is closed and locked (failsafe). Only in this way can the key be transferred from here to the key-operated selector switch.

When the machine control system is switched on the key is trapped and cannot be removed for as long as the switch is set to ON.

If the transfer time between the opening of the key-operated selector switch and the locking of the guard is not sufficient for a hazardous machine motion to come to a standstill, a key-operated selector switch interlocking device may also be required.

Framework conditions

When using the EX-SHGV safety door interlocking system it must be ensured that

- the time between switching off at the control panel and access to the guard is greater than the stopping time of any hazardous motion, or that the key-operated selector switch interlocking device of the type SVE is used;
- only one key is used in the trapped key system and any spare keys available are stored carefully;
- the separate actuators of the EX-SHGV guard locking devices are fitted to the guard in such a way, e.g. with the non-reusable screws supplied with the equipment, that they cannot be released by simple means;
- the entry throat for the separate actuator is fitted in the guard locking device in a concealed position where at all possible. This recommendation applies generally to interlocking devices with separate actuator.

Please note:

- Owing to the trapped key system the systems are less suited to charging doors or moving guards with more frequent access.
- Even if key and lock barrel have 200 individual cuts / tumbler arrangements, a key can be copied in the same way as a separate actuator. Any damage caused as a result of such wilful manipulation of a guard no longer falls within the protection of statutory accident insurance (otherwise there would also be no BG test certificate for the SHGV system) for example.
- Every EX-SHGV system comes with a spare key should the original one be lost under the strict condition that it is kept carefully and not used in the operational key transfer procedure.

EX-Trapped key system



EX-SHV/E key-operated selector switch

The EX-SHV/E key-operated selector switch as control element to interrupt or switch off automatic mode.



Guard locking device Type EX-SHV

The design of the Guard locking device EX-SHV is based on that of a position switch with separate actuator, but the function of the position monitoring and locking is based exclusively on a mechanical principle of operation using the integrated lock barrel and the positively connected mechanism as well as the interaction between actuator and the articulating mechanism in the device head.



Version with a second lock barrel

The version with a second lock barrel using which the operation of lock barrel 1 can be blocked if an operator needs to access a room and wishes to protect himself from unintentional start-up of the machine control system by a third party.




EX-SVM key distribution station

The EX-SVM key distribution station is used when multiple guards must be operated with one key selector switch.

EX-Trapped key system

EX-SHGV-...-3G/D



- Key-operated selector switch
- Ex certified
- Mounting hole 22.3 mm
- Metal front ring
- Good resistance to oil and petroleum spirit

Technical data

Equipment category:	Ex II 3GD
Ex protection:	Ex nL IIC T5 X Ex tD A22 IP65 T110°C X
Standards:	EN 60947-1 EN 60947-5-1 EN 61241-1 EN 60079-0 EN 60079-15
Mounting hole Ø:	22.3 mm
Front plate thickness:	1.5 ... max. 6 mm
Spacing:	50 x 50 mm
Max. impact energy:	1 J
Actuating speed:	max. 1 m/s
Protection class:	
Key-operated selector switch:	IP65
Contact element:	IP44
Contact type:	change-over contact with double break, type Zb, with galvanically separated contact bridges, NC contact with positive break
Contact material:	fine silver
Connection:	Screw terminals
U _i :	36 VDC
I _i :	100 mA
P _i :	0.9 W
C _i :	~ 0
L _i :	~ 0
Utilisation category:	AC-15, DC-13
I _e /U _e :	6 A / 250 VAC 4 A / 24 VDC
Max. fuse rating:	6 A gG D-fuse
Ambient temperature:	0 °C ... + 70 °C
Mechanical life:	10 million operations

Contact variants

1 NO / 1 NC EF 103.1

23 → 24
11 → 12

EF 103.2

43 → 44
31 → 32

Approvals



Ordering details

EX-SHGV/ESS21S2/①/11033-3G/D

No.	Option	Description
①	e.g. 201	individual key numbers

Note

Contact variants

Contact element EF103.1	1 NC / 1 NO
Contact element EF103.2	1 NC / 1 NO

included in delivery.

If more contacts are needed, on request.

EX-Trapped key system

EX-SVM 1/..-6/..-2G/D







EX-SVM 1/..-10/..-2G/D



Technical data

Equipment category:	Ex II 2GD
Ex protection:	c 85°C X
Standards:	EN 13463-1, EN 61241-0
Design:	Enclosure for top mounting or front plate mounting
Material:	Enclosure for top mounting AISi12 front plate 1.4301
Actuating speed:	max. 1 m/s
Mechanical life:	10 million operations



- Key distribution station
- with 6 keys
- Ex certified
- Metal enclosure
- Good resistance to oil and petroleum spirit
- Metal front plate
- 6 Cylinder lock for solenoid keys EX-SHGV..

- Key distribution station
- with 10 keys
- Ex certified
- Metal enclosure
- Good resistance to oil and petroleum spirit
- Metal front plate
- 10 Cylinder lock for solenoid keys EX-SHGV..

Approvals



Ordering details

EX-SVM1/①-6②/③-2G/D

No.	Option	Description
①	e.g. 34	individual key number for main cylinder lock
②	...	individual key number for solenoid key EX-SHGV..
③	A	Enclosure for surface mounting
	E	Front plate mounting

Approvals



Ordering details

EX-SVM1/①-10②/③-2G/D

No.	Option	Description
①	e.g. 34	individual key number for main cylinder lock
②	...	individual key number for solenoid key EX-SHGV..
③	A	Enclosure for surface mounting
	E	Front plate mounting

EX-Trapped key system

EX-SHGV-...-2G/D







EX-SHGV-...-2G/D



Technical data

Equipment category: II 2GD
Ex protection: c 85°C X
Standards: EN 13463-1, EN 61241-0
Design: fixings to EN 50041
Enclosure: Al Si12 die-casting, painted
Actuating speed: max. 1 m/s
Mechanical life: 10 million operations



- Interlock
- Ex certified
- Mounting details to EN 50041
- Metal enclosure
- Good resistance to oil and petroleum spirit

- Interlock
- with a second lock barrel

Approvals



Ordering details

EX-SHGV/①01/②+③-2G/D

No.	Option	Description
①	B	Cylinder lock on the back
	L	Lock barrel to left
	R	Lock barrel to the right
②	e.g. 201	individual key numbers
③	e.g. BO	For the appropriate actuator see page 137

Approvals




EX-SHGV/①D1/①/③+④-2G/D


No.	Option	Description
①	L	Lock barrel to left
	R	Lock barrel to the right
②	e.g. 201	individual key number for LHS or RHS cylinder lock
③	e.g. 34	individual key number for second cylinder lock
④	e.g. BO	For the appropriate actuator see page 137

EX-Trapped key system


System components




Straight actuator EX-BO



Angled actuator EX-BOW



Straight radius actuator EX-BOR



Angled radius actuator EX-BOWR

Ordering details

Straight actuator	EX-BO
Angled actuator	EX-BOW
Straight radius actuator	EX-BOR
Angled radius actuator	EX-BOWR

Addresses

Hauptsitz - Headquarters

K.A. Schmersal GmbH & Co. KG
Industrielle Sicherheitsschaltungssysteme
Postfach 24 02 63,
42232 Wuppertal
Möddinghofe 30
D-42279 Wuppertal
Phone: +49-2 02-64 74-0
Fax: +49-2 02-64 74-1 00
info@schmersal.com
www.schmersal.com

Germany - Northern region

Wettenberg
K.A. Schmersal GmbH & Co. KG
Vertriebsbüro Wettenberg
Im Ostpark 2
D-35435 Wettenberg
Phone: +49-6 41-98 48-5 75
Fax: +49-6 41-98 48-5 77
vbwettenberg@schmersal.com

Hamburg / Münster
K.A. Schmersal GmbH & Co. KG
Vertriebsbüro Hamburg
Innungsstraße 3
D-21244 Buchholz i.d.N.
Phone: +49-41 81-9 22 0-0
Fax: +49-41 81-9 22 0-20
vbhamburg@schmersal.com

Berlin
KSA Komponenten der Steuerungs- und Automatisierungstechnik GmbH
Pankstr. 8-10 / Aufg. L
D-13127 Berlin
Phone: +49-30-47 48 24 00
Fax: +49-30-47 48 24 05
info@ksa-gmbh.de
www.ksa-gmbh.de

Hannover
ELTOP GmbH
Robert-Bosch-Str. 8
D-30989 Gehrden
Phone: +49-51 08-92 73 20
Fax: +49-51 08-92 73 21
eltop@eltop.de
www.eltop.de

Köln
Stollenwerk
Technisches Büro GmbH
Scheuermühlenstr. 40
D-51147 Köln
Phone: +49-22 03-9 66 20-0
Fax: +49-22 03-9 66 20-30
info@stollenwerk.de
www.stollenwerk.de

Siegen
Siegfried Klein
Elektro-Industrie-Vertretungen
In der Steinwiese 46
D-57074 Siegen
Phone: +49-2 71-67 78
Fax: +49-2 71-67 70
info@sk-elekrotechnik.de
www.sk-elekrotechnik.de

Leipzig
K.A. Schmersal GmbH & Co. KG
Vertriebsbüro Leipzig
Servicepark
Druckereistraße 4
D-04159 Leipzig
Phone: +49-3 41-4 87 34 50
Fax: +49-3 41-4 87 34 51
vbleipzig@schmersal.com

Germany - Southern region

Nürnberg
K.A. Schmersal GmbH & Co. KG
Vertriebsbüro Nürnberg
Lechstraße 21
D-90451 Nürnberg
Phone: +49-9 11- 6 49 60 53
Fax: +49-9 11-63 29 07 29
vnuernberg@schmersal.com

Saarland

Herbert Neundoerfer Werksvertretungen GmbH & Co. KG
Am Campus 5
D-66287 Göttelborn
Phone: +49-68 25-95 45-0
Fax: +49-68 25-95 45-99
info@herbert-neundoerfer.de
www.herbert-neundoerfer.de

Bayern Süd

INGAM Ing. Adolf Müller GmbH
Industrievertreterungen
Elly-Staegmeyr-Str. 15
D-80999 München
Phone: +49-89-8 12 60 44
Fax: +49-89-8 12 69 25
info@ingam.de
www.ingam.de

Bietigheim

K.A. Schmersal GmbH & Co. KG
Technologiezentrum
Pleidelsheimer Straße 15
74321 Bietigheim-Bissingen
Phone: +49-71 42-9 10 28-0
Fax: +49-71 42-9 10 28-28
tzbw@schmersal.com

Europe

Austria - Österreich

AVS-Schmersal Vertriebs Ges. m.b.H.
Birôstraße 17
1232 Wien
Phone: +43-1-6 10 28
Fax: +43-1-6 10 28-1 30
info@avs-schmersal.at
www.avsschmersal.at

Belgium - Belgien

Schmersal Belgium NV/SA
Nieuwlandlaan 73
Industriezone B413
3200 Aarschot
Phone: +32-16-57 16 18
Fax: +32-16-57 16 20
info@schmersal.be
www.schmersal.be

Bulgaria - Bulgarien

CDL Sensorik OOD
Stefan Caragea Street
No 10 Office 4
7002 Ruse City
Phone: +359-0 40-7 35 16 55 25
Fax: +359-0 40-2 69 25 33 44
office@cdlsensorik.com
www.cdlsensorik.com

Bosnia and Herzegovina

Tipteh d.o.o. Sarajevo
Ulica Braniilaca Šipa 21c
71000 Sarajevo
Phone: +387- 61 92 36 23
nadir.durmic@tipteh.ba
www.tipteh.ba

Croatia - Kroatien

Tipteh Zagreb d.o.o.
Pescanska 170
10000 Zagreb
Phone: +385-1-3 81 65 74
Fax: +385-1-3 81 65 77
tipgeh.zagreb@zg.t-com.hr

Czech Republic - Tschech. Republik

MERCOM COMPONENTA s.r.o.
Bechyňská 640
199 00 Praha 9 – Letňany
Phone: +420-267 31 46 40-2
mercom@mercom.cz
www.mercom.cz
www.schmersal.cz

Denmark - Dänemark

Schmersal Danmark A/S
Lautruphøj 1-3
2750 Ballerup
Phone: +45-70 20 90 27
Fax: +45-70 20 90 37
info@schmersal.dk
www.schmersal.dk

Finland - Finnland

Advancetec Oy
Äyrifiltti 12 B
01510 Vantaa
Phone: +358-2 07 19 94 30
Fax: +358-9 35 05 26 60
advancetec@advancetec.fi
www.schmersal.fi

France - Frankreich

Schmersal France
BP 18 - 38181 Seyssins Cedex
8, rue Raoul Follereau
38180 Seyssins
Phone: +33-4 76 84 23 20
Fax: +33-4 76 48 34 22
info-fr@schmersal.com
www.schmersal.fr

Greece - Griechenland

Kalamarakis Sapounas S.A.
Ionias & Neromilou
PO Box 46566 Athens
13671 Chamomilos Acharnes
Athens
Phone: +30-210-2 40 60 00-6
Fax: +30-210-2 40 60 07
ksa@ksa.gr
www.ksa.gr

Hungary - Ungarn

NTK Ipari-Elektronikai és Kereskedelmi Kft
Gesztenyefa u. 4.
9027 Györ
Phone: +36-96-52 32 68
Fax: +36-96-43 00 11
info@ntk-kft.hu
www.ntk-kft.hu

Iceland - Island

Reykjafell Ltd.
Skipholtt 35
125 Reykjavík
Phone: +354-5 88 60 10
Fax: +354-5 88 60 88
reykjafell@reykjafell.is

Italy - Italien

Schmersal Italia s.r.l.
Via Molino Vecchio, 206
25010 Borgosatollo, Brescia
Phone: +39-0 30-2 50 74 11
Fax: +39-0 30-2 50 74 31
info@schmersal.it
www.schmersal.it

Macedonia - Mazedonien

Tipteh d.o.o. Skopje
Ul. Jani Lukovski br. 2/33
1000 Skopje
Phone: +389-70-39 94 74
Fax: +389-23-17 41 97
tipgeh@on.net.mk

Netherlands - Niederlande

Schmersal Nederland B.V.
Lorentzstraat 31
3846 AV Harderwijk
Phone: +31-3 41-43 25 25
Fax: +31-3 41-42 52 57
info-nl@schmersal.com
www.schmersal.nl

Norway - Norwegen

Schmersal Norge
Hoffsveien 92
0377 Oslo
Phone: +47-22 06 00 70
Fax: +47-22 06 00 80
info-no@schmersal.com
www.schmersal.no

Poland - Polen

Schmersal - Polska Sp.j.
ul. Baletowa 29
02-867 Warszawa
Phone: +48-22-8 16 85 78
Fax: +48-22-8 16 85 80
info@schmersal.pl
www.schmersal.pl

Portugal - Portugal

Schmersal Ibérica, S.L.
Apartado 30
2626-909 Póvoa de Sta. Iria
Phone: +351 - 21 959 38 35
info-pt@schmersal.com
www.schmersal.pt

Romania - Rumänien

CD SENSORIC SRL
Str. George Enescu 21
550248 Sibiu
Phone: +40-2 69-25 33 33
Fax: +40-2 69-25 33 44
proiecte@cdl.ro
www.cdl.ro

Russia - Russland

ООО AT electro Moskau
ul. Avtosavodskaya 16-2
109280 Moskau
Phone: +7-49 5-9 21 44 25
Fax: +7-49 5-9 26 46 45
info@at-e.ru
www.at-e.ru

OOO AT electro Petersburg

Polytechniskaya str, d.9,B
194021 St. Petersburg
Phone: +7-81 2-7 03 08 17
Fax: +7-81 2-7 03 08 34
spb@at-e.ru

AT- Electronics Ekaterinburg

Bebelya str. 17, room 405
620034 Ekaterinburg
Phone: +7-34 3-2 45 22 24
Fax: +7-34 3-2 45 98 22
ural@at-e.ru

Slovakia - Slowakei

MERCOM COMPONENTA s.r.o.
Bechyňská 640
199 00 Praha 9 – Letňany
Phone: +4 20-267 31 46 40-2
mercom@mercom.cz
www.mercom.cz
www.schmersal.cz

Slovenia - Slowenien

Tipteh d.o.o.
Ulica Ivana Roba 21
1000 Ljubljana
Phone: +386-1-2 00 51 50
Fax: +386-1-2 00 51 51
info@tipgeh.si
www.tipgeh.si

Spain - Spanien

Schmersal Ibérica, S.L.
Pol. Ind. La Masía
Camí de les Cabories, Nave 4
08798 Sant Cugat Sesgarrigues
Phone: +34-902 56 64 57
info-es@schmersal.com
www.schmersal.es

Sweden - Schweden

Schmersal Nordiska AB
F O Petersons gata 28
421 31 Västra Frölunda
Phone: +46-31-3 38 35 00
Fax: +46-31-3 38 35 39
info-se@schmersal.com
www.schmersal.se

Switzerland - Schweiz

Schmersal Schweiz AG
Moosmattstraße 3
8905 Arni
Phone: +41-43-3 11 22 33
Fax: +41-43-3 11 22 44
info-ch@schmersal.com
www.schmersal.ch

Addresses

- **Turkey - Türkei**
BETA Elektrik
Okçumusa Caddesi
Anten Han No. 44
34420 Karaköy / İstanbul
Phone: +90-212-235 99 14
Fax: +90-212-253 54 56
info@betaelektrik.com
www.betaelektrik.com
- **United Kingdom - Großbritannien**
Schmersal Ltd.
Sparrowhawk Close
Enigma Business Park
Malvern Worcestershire WR14 1GL
Phone: +44-16 84-57 19 80
Fax: +44-16 84-56 02 73
support@schmersal.co.uk
www.schmersal.co.uk
- **Ukraine - Ukraine**
INCOMTECH-PROJECT Ltd
17-25, Hertsen St., of. 9
04050 Kyiv Ukraine
Phone: +38 044 486 2537
www.i-p.com.ua/

VBR Ltd.
41, Demiivska Str.
03040 Kyiv Ukraine
Phone: +38 (044) 259 09 55
Fax: +38 (044) 259 09 55
office@vbr.com.ua
www.vbr.com.ua/about_en.htm
- **Worldwide**
- **Argentina - Argentinien**
Condelectric S. A.
info@condelectric.com.ar
www.condelectric.com.ar
ELECTRO-DOS
contacto@electro-dos.com.ar
www.electro-dos.com.ar
- **Australia - Australien**
Control Logic Pty. Ltd.
25 Lavarack Avenue, PO Box 1456
Eagle Farm, Queensland
Phone: +61-7 36 23 12 12
Fax: +61-7 36 23 12 11
sales@control-logic.com.au
www.control-logic.com.au
- **Belarus - Weißrussland**
ZAO Eximelektro
Ribalko Str. 26-110
BY-220033 Minsk, Belarus
Phone: +375-17-298-44-11
Fax: +375-17-298-44-22
eximelektro@tut.by
www.exim.by
- **Bolivia - Bolivien**
Bolivien International
Fil-Parts
3er. Anillo, 1040, Frente al Zoo
Santa Cruz de la Sierra
Phone: +591 (3) 3 42 99 00
presidente@filparts.com.bo
www.filparts.com.bo
- **Brazil - Brasilien**
ACE Schmersal
Eletroeletrônica Industrial LTDA
Rodovia Boituva - Porto Feliz, KM 12
Jardim Esplanada - CEP: 18550-000,
Boituva, SP
Phone: +55-15-32 63-98 00
Fax: +55-15-32 63-98 99
export@schmersal.com.br
www.schmersal.com.br
- **Canada - Kanada**
Schmersal Canada LTD.
15 Regan Road Unit #3
Brampton, Ontario L7A 1E3
Phone: (905) 495-7540
Fax: (905) 495-7543
Info-ca@schmersal.com
www.schmersalcanada.com
- **Chile - Chile**
Vitel S.A.
francisco@vitel.cl
www.vitel.cl
SOLTEX
central@soltex.cl
www.soltex.com.cl
INSTRUTEC
gcaceres@instrutec.cl
www.instrutec.cl
OEG
jmp@oeggroup.com
www.oeggroup.cl
EECOL INDUSTRIAL ELECTRIC
ventas@eecol.cl
www.eecol.cl
- **PR China - VR China**
Schmersal Industrial
Switchgear (Shanghai) Co. Ltd.
Cao Ying Road 3336
201712 Shanghai / Qingshu
Phone: +86-21-63 75 82 87
Fax: +86-21-63 75 82 97
sales@schmersal.com.cn
www.schmersal.com.cn
- **Colombia - Kolumbien**
EQUIPELCO
aospina@equipelco.com
www.equipelco.com
SAMCO
jvargas@samcoingenieria.com
www.samcoingenieria.com
- **Ecuador - Ecuador**
SENSORTEC S.A
AV. Napo y Pinto Guzmán
Quito
Phone: +593 091 40 27 65
+593 095 04 86 11
infogye@sensortecsa.com
www.sensortecsa.com
- **Guatemala - Guatemala**
PRESTELECTRO
AV Petapa 44-22,
Zona 12; Cent. Com Florencia 01012
Phone: +502 24 42-33 46
Anabella.Barrios@prestelectro.com
www.prestelectro.com
- **India - Indien**
Schmersal India Private Limited
Plot No G 7/1,
Ranjangaon MIDC,
Taluka Shirur,
District Pune 412220, India
Phone: +91 21 38 61 47 00
Fax: +91 20 66 86 11 14
info-in@schmersal.com
www.schmersal.in
- **Indonesia - Indonesien**
PT. Wiguna Sarana Sejahtera
Jl. Daan Mogot Raya No. 47
Jakarta Barat 11470
Phone: +62-21-5 63 77 70-2
Fax: +62-21-5 66 69 79
email@ptwiguna.com
www.ptwiguna.com
- **Israel - Israel**
A.U. Shay Ltd.
23 Imber St. Kiriat Ariej.
P.O. Box 10049
Petach Tikva 49222 Israel
Phone: +9 72-3 9 23 36 01
Fax: +9 72-3 9 23 46 01
shay@uriel-shay.com
www.uriel-shay.com
- **Japan - Japan**
Schmersal Japan Branch Office
3-39-8 Shoan, Suginami-ku
Tokyo 167-0054
Phone: +81-3-3247-0519
Fax: +81-3-3247-0537
safety@schmersaljp.com
www.schmersal.jp
- **Korea - Korea**
Mahani Electric Co. Ltd.
20, Gungmal-ro, Gwacheon-si,
Gyeonggi-do 427-060, Korea
Phone: +82-2-21 94-33 00
Fax: +82-2-21 94-33 97
yskim@mec.co.kr
www.mec.co.kr
- **Litauen/Estland/Lettland**
BOPALIT
Mus galite rasti:
Baltu pr. 145, LT-47125, Kaunas
Phone: +370 37 298989
Phone: +370 37 406718
infoboplait.lt
www.boplait.lt
- **Malaysia - Malaysien**
Ingermark (M) SDN.BHD
No. 29, Jalan KPK 1/8
Kawasan Perindustrian Kundang
48020 Rawang, Selangor Darul Ehsan
Phone: +6 03-60-34 27 88
Fax: +6 03-60-34 21 88
enquiry@ingermark.com
- **Mexico - Mexiko**
ISEL SA de CV
mario.c@isel.com.mx
www.isel.com.mx
INNOVATIVE AUTOMOTION SOLUTIONS
ias@iasmx.com
www.iasautomation.com.mx
DINAMICA S.A de C.V
ias@iasmx.com
www.iasautomation.com.mx
SIGRAMA S.A de C.V
ias@iasmx.com
www.iasautomation.com.mx
VGR TECHNOLOGIES
ias@iasmx.com
www.iasautomation.com.mx
- **New Zealand - Neuseeland**
Hamer Automation
85A Falsgrave Street
Philipstown
Christchurch, New Zealand
Phone: +64-33 66 24 83
Fax: +64-33 79 13 79
sales@hamer.co.nz
www.hamer.co.nz
- **Pakistan - Pakistan**
eurotech JLT
Office No.3404, 34th Floor,
HDS Tower, Sheikh Zayed Road,
Jumeirah Lakes Towers (JLT),
P.O.Box 643650, Dubai, UAE
Phone: +9 71-4-4 21 46 00
Fax: +9 71-4-4 21 46 01
sales@eurotech.ae
www.eurotech.ae
- **United Arab Emirates - Vereinigte Arabische Emirate**
eurotech JLT
Office No.3404, 34th Floor,
HDS Tower, Sheikh Zayed Road,
Jumeirah Lakes Towers (JLT),
P.O.Box 643650, Dubai, UAE
Phone: +9 71-4-4 21 46 00
Fax: +9 71-4-4 21 46 01
sales@eurotech.ae
www.eurotech.ae
- **USA - USA**
Schmersal Inc.
15 Skyline Drive
Hawthorne, NY 10532
Phone: +1-(0) 8 88-4 96-51 43
Fax: +1-(0) 9 14-3 47-15 67
infousa@schmersal.com
www.schmersalusa.com
- **Uruguay - Uruguay**
Giston S.A.
Pedernal 1896 – Of. 203
Montevideo
Phone: +598 (2) 2 00 07 91
colmedo@giston.com.uy
www.giston.com.uy
- **Venezuela - Venezuela**
EMI Equipos y Sistemas C.A.
Calle 10, Edf. Centro Industrial
Martinisi, Piso 3, La Urbina
Caracas
Phone: +58 (212) 2 43 50 72
ventas@emi-ve.com
www.emi-ve.com
- **Vietnam - Vietnam**
Ingermark (M) Sdn Bhd, Rep Office
No. 10 Alley 1/34, Lane 1,
Kham Thien Str.,
Kham Thien Ward Dong Da Dist.,
10000 Hanoi, Vietnam.
Phone: +04-35 16 27 06
Fax: +04-35 16 27 05
ingvietn18@ymail.com
www.ingermark.com



The Schmersal Group

The privately-owned Schmersal Group has been developing and manufacturing products to enhance the safety at work for decades. The company was founded in 1945 and is represented by seven manufacturing sites on three continents and with its own companies and sales partners in more than 60 nations. In the demanding field of machine safety, the Schmersal Group is one of the international market and competence leaders. Based on a comprehensive product range, the company's approximately 2000 employees develop and design complete solutions for the safety of man and machine.

Customers of the Schmersal Group include „global players“ from mechanical engineering and plant manufacturing and machine users. They benefit from the comprehensive know-how of the company when it comes to the standard-compliant integration of safety technology in the production processes. Furthermore, Schmersal has special sector expertise in the application fields that demand high quality and special characteristics from safety switching systems. These include food production, the packaging industry, machine tool construction, lift engineering, heavy industry and the automotive industry.

Against the backdrop of increasing numbers of standards and directives, tec.nicum offers a comprehensive range of safety services as part of the Schmersal Group services division: Certified functional safety engineers advise customers on selecting suitable safety equipment, CE compliance assessments and risk assessment, on a world-wide basis.

Product ranges



Safe switching and monitoring

- Guard door monitoring (Safety switches)
- Command devices with safety function
- Tactile safety devices
- Optoelectronic safety devices

Safe signal processing

- Safety relay components
- Safety controllers
- Safety bus systems

Automation

- Position detection
- Command and signalling devices

Industries



- Elevators and Escalators
- Packaging
- Food
- Automotive
- Machine tools
- Heavy industry

Services



- Application support
- CE conformity assessment
- Risk assessment
- Upgrading / Retrofit
- Technical planning and implementation
- Training courses

Competences



- Machine safety
- Automation
- Explosion protection
- Hygienic design

Precautions have been taken to assure accuracy of the information in this catalogue. Typographic or pictorial errors that are brought to our attention will be corrected in subsequent issues.

www.schmersal.com



 **SCHMERSAL**
Safe solutions for your industry