



AZM150SK-02/02RIT-024-B6R

- Thermoplastic enclosure
- Eight approach levels thanks to rotating head
- Individually coded version with coding level "High" according to ISO 14119
- Simple fitting, especially on 40 mm profiles

Data

Ordering data

EAN (European Article Number)	4030661547688
eCl@ss number, Version 9.0	27-27-26-03
eCl@ss number, Version 11.0	27-27-26-03

Approval - Standards

Certificates	TÜV cULus CCC EAC
--------------	----------------------------

General data

Standards	EN 60947-5-1 EN ISO 14119
Coding level according to ISO 14119	High
Active principle	electromechanical
Enclosure material	Thermoplastic, Polyamide PA 6 GF
Material of the contacts, electrical	Silver

Gross weight 632.7 g

General data - Features

Power to unlock Yes
Number of actuating directions 2
Number of safety contacts 4

Safety appraisal

Standards EN ISO 13849-1
Mission Time 20 Year(s)

Safety appraisal - Safety outputs

B10d Normally-closed contact (NC) 2,000,000 Operations

Mechanical data

Mechanical life, minimum 1,000,000 Operations
Clamping force in accordance with ISO14119 F_{zh} 1,500 N
Clamping force, maximum F_{max} 1,950 N
Latching force, approx. 50 N
positive break travel 10 mm
Positive break force, minimum 40 N
Actuating speed, maximum 0.2 m/s
Mounting Screws

Mechanical data - Connection technique

Terminal Connector Screw terminals
Cable entry 3 x M20 x 1,5
Cable section, minimum 1 x 0.25 mm²

Cable section, maximum	1 x 2.5 mm ²
------------------------	-------------------------

Mechanical data - Dimensions

Length of sensor	64 mm
Width of sensor	40 mm
Height of sensor	204 mm

Ambient conditions

Degree of protection	IP65 to EN 60529 IP67 to EN 60529
Ambient temperature, minimum	-25 °C
Ambient temperature, maximum	+55 °C
Storage and transport temperature, minimum	-40 °C
Storage and transport temperature, maximum	+85 °C

Ambient conditions - Insulation value

Rated insulation voltage U_i	300 V
Rated impulse withstand voltage U_{imp}	4 kV

Electrical data

Thermal test current	5 A
Rated control voltage	24 VDC
Required rated short-circuit current to EN 60947-5-1	400 A
Utilisation category AC-15	230 VAC
Utilisation category AC-15	3 A
Utilisation category DC-13	24 VDC
Utilisation category DC-13	2.5 A
Electrical power consumption, maximum	8.5 W
Switching element	Opener (NC)

Switching principle

Creep circuit element

Switching frequency

1,000 /h

Other data

Note (applications)

sliding safety guard
removable guard
hinged safety guard

Scope of delivery

Included in delivery

Slot cover for dust-proof covering of the opening not in use

Notes

Note (Emergency exit)

In case of emergency actuation from within the hazardous area
Mounting only within the guarded area

Note (Manual release)

For maintenance, installation, etc.
On the cover side
By means of M5 triangular key

Ordering code

Product type description:
AZM150SK-(1)R(2)(3)(4)-(5)-(6)

(1)

02/11	Magnet: 2 NC contacts; actuator: 1 NC contact/1 NO contact
11/11	Magnet: 1 NC contact/1 NO contact; actuator: 1 NC contact/1 NO contact
11/02	Magnet: 1 NC contact/1 NO contact; actuator: 2 NC contacts
02/02	Magnet: 2 NC contacts; actuator: 2 NC contacts

(2)

without	Standard coding
I	Individual coding

(3)

without	Power to unlock
A	Power to lock

(4)

without	Manual release on the cover side
T	Emergency exit on the cover side
N	Emergency release

(5)

24 VDC	Us: 24 VDC
110VAC	Us: 110 VAC
230VAC	Us: 230 VAC

(6)

Note:	Actuator inclusive with individually coded device versions I:
B1	with actuator B1
B5	with actuator B5
B6L	with actuator B6L
B6R	with actuator B6R

Documents

Operating instructions and Declaration of conformity

AZM150 V2 (2.8 MB, 08/26/2021, B)

Operating instructions (supplementary sheet/quick guide)

MP-AZM150 (226.1 kB, 02/15/2021)

UL Certificate

AZM150 (806.9 kB, 08/16/2021)

CCC certification

AZM150 (4.2 MB, 03/02/2021)

Brochure

AZM150 - The slim solenoid interlock (2.1 MB, 12/14/2020)

Pictures

Product picture (catalogue individual photo)



ID: azm150-n-1

| 1.2 MB | .jpg | 352.778 x 952.853 mm - 1000 x 2701 px - 72 dpi

| 78.6 kB | .png | 74.083 x 200.025 mm - 210 x 567 px - 72 dpi

| 35.2 kB | .jpg | 159.456 x 430.389 mm - 452 x 1220 px - 72 dpi

System components

Accessories

SZ150-1



Actuator



AZM150-B1

- Straight actuator
- Particularly suitable for sliding doors



AZM150-B5

- Angled actuator
- Particularly suitable for sliding doors



AZM150-B6

- Flexible actuator
- Particularly suitable for hinged guards

Schmersal, Inc., 15 Skyline Drive, Hawthorne, NY 10532

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on: 11/9/2021, 6:03 PM