



BS655-Z22-G024

- Platform concept with different function units
- Metal enclosure
- Wide range of alternative actuators
- Protection class IP66, IP67
- Switching point setting
- Symmetry thanks to toothed, centrally located shaft
- Central connection terminal

Data

Ordering data

Product type description	BS655-Z22-G024
Article number (order number)	153031623
EAN (European Article Number)	4030661533056
eCl@ss number, version 12.0	27-27-06-01
eCl@ss number, version 11.0	27-27-06-01
eCl@ss number, version 9.0	27-27-06-01
ETIM number, version 7.0	EC000030
ETIM number, version 6.0	EC000030

Approvals - Standards

Certificates	TÜV cULus CCC
--------------	---------------------

General data

Standards	EN 620 EN IEC 60947-5-1
Enclosure material	Grey cast iron, painted
Material of the contacts, electrical	Silver
Material of the housing cover	Grey cast iron, painted
Gross weight	6,035 g

General data - Features

Indicator lamp	Yes
Number of auxiliary contacts	2
Number of safety contacts	2
Number of signal lamps	1

Safety classification

Standards	EN ISO 13849-1
Mission time	20 Year(s)

Safety classification - Safety outputs

B _{10D} Normally-closed contact (NC)	2,000,000 Operations
---	----------------------

Mechanical data

Mechanical life, minimum	1,000,000 Operations
Positionierschritte für den Betätiger	10 °

Mechanical data - Connection technique

Cable entry	2 x M25 x 1.5
Cable section, minimum	0.5 mm ² , flexible
Cable section, maximum	2.5 mm ² , flexible

Ambient conditions

Degree of protection	IP67 IP66
Ambient temperature, minimum	-25 °C
Ambient temperature, maximum	+60 °C
Protection class	I

Ambient conditions - Insulation values

Rated insulation voltage U_i	300 V
Rated impulse withstand voltage U_{imp}	4 kV
Degree of pollution to IEC/EN 60947-1	3

Electrical data

Thermal test current	6 A
Utilisation category AC-15	230 VAC
Utilisation category AC-15	3 A
Utilisation category DC-13	24 VDC
Utilisation category DC-13	3 A

Status indication

Colour of the indicator lamp	Red
Note (LED switching conditions display)	Supply voltage U_B : 24 VDC

Ordering code

Product type description:

BS65(1)(2)(3)(4)

(1)

215 Grey cast iron, painted

6 thermosetting resin

(2)

Z22 Snap action 2 NO contact / 2 NC contact

T22 Slow action, 2 NO contacts / 2 NC contacts

Z33 Snap action, 3 NO contacts / 3 NC contacts

T33 Slow action, 3 NO contacts / 3 NC contacts

(3)

without without indicator lamp

G024 Indicator lamp (only for Z/T22), red (24 VDC)

G115 Indicator lamp (only for Z/T22), red (115 VAC)

G230 Indicator lamp (only for Z/T22), red (230 VAC)

(4)

without Standard version (without Dupline® input module)

DN With integrated Dupline® input module

Pictures

Product picture (catalogue individual photo)




ID: khds-f25

| 273.1 kB | .jpg | 352.778 x 235.303 mm - 1000 x 667 px - 72 dpi

| 23.4 kB | .png | 74.083 x 49.389 mm - 210 x 140 px - 72 dpi

Dimensional drawing basic component




ID: kbs65g01

| 3.5 kB | .png | 74.083 x 44.097 mm - 210 x 125 px - 72 dpi

| 98.3 kB | .jpg | 352.778 x 209.55 mm - 1000 x 594 px - 72 dpi

Dimensional drawing basic component




ID: kbs65g02

| 71.6 kB | .jpg | 352.778 x 167.922 mm - 1000 x 476 px - 72 dpi

| 2.9 kB | .png | 74.083 x 35.278 mm - 210 x 100 px - 72 dpi

| 5.5 kB | .jpg | 89.253 x 42.686 mm - 253 x 121 px - 72 dpi

Dimensional drawing basic component



ID: kbs65g03

| 127.4 kB | .jpg | 352.778 x 195.439 mm - 1000 x 554 px - 72 dpi

| 4.7 kB | .png | 74.083 x 40.922 mm - 210 x 116 px - 72 dpi

| 11.9 kB | .jpg | 115.711 x 63.853 mm - 328 x 181 px - 72 dpi

Schmersal, Inc., 15 Skyline Drive, Hawthorne, NY 10532

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on: 10/3/2022, 4:15 PM