

Archive



## M2K 017-22Y

- 3 Cable entry M 20 x 1.5

### Data

#### Ordering data

|                               |                |
|-------------------------------|----------------|
| Note (Delivery capacity)      | Not available! |
| Product type description      | M2K 017-22Y    |
| Article number (order number) | 101054968      |
| EAN (European Article Number) | 4030661002743  |

#### Certifications

|              |            |
|--------------|------------|
| Certificates | CCC<br>EAC |
|--------------|------------|

#### General data

|              |                   |
|--------------|-------------------|
| Product name | 017 tilt lever 2K |
| Gross weight | 405.000 g         |

#### General data - Features

|                    |   |
|--------------------|---|
| Number of openers  | 2 |
| Number of shutters | 2 |

#### Mechanical data

|                          |                      |
|--------------------------|----------------------|
| Mechanical life, minimum | 5,000,000 Operations |
| Actuating force          | 5.5 N                |
| Contact opening          | 2 x 1.2 mm           |

## Mechanical data - Connection technique

|                        |   |
|------------------------|---|
| Terminal Connector     | Screw connection  |
| Cable section, minimum | 1.5 mm <sup>2</sup>   |
| Cable section, maximum | 2.5 mm <sup>2</sup>   |
| Note (Cable section)   | All indications about the cable section are including the conductor ferrules. |
| Wire cross-section     | 13 AWG  |

## Electrical data

|                            |  |
|----------------------------|--|
| Utilisation category AC-15 | 400 VAC                                |
| Utilisation category AC-15 | 2.5 A                                  |
| Switching element          | NO contact, NC contact                 |
| Note (Switching element)   | galvanically separated contact bridges |
| Switching principle        | Snap switch element                    |
| Bounce duration, maximum   | 2.5 ms                                 |
| Switchover time, maximum   | 40 ms                                  |

## Pictures

### Product picture (catalogue individual photo)



ID: kt15kf02


| 82,8 kB | .png | 74.083 x 135.467 mm - 210 x 384

Pixel - 72 dpi

| 733,1 kB | .jpg | 232.833 x 426.156 mm - 660 x 1208

Pixel - 72 dpi

## Diagram



ID: k2o2sk04

| 19,1 kB | .cdr |

K.A. Schmersal GmbH & Co. KG, Möddinghofe 3, D-42279 Wuppertal

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on 11.09.2020 19:13:43