



### M3R330-11Y-M20

- Long life
- Metal enclosure
- free of silicon
- 1 Cable entry M 20 x 1.5
- Suitable for low actuating speeds
- proved in power station applications
- 40 mm x 76 mm x 40 mm ( basic component)
- with bellows to protect against heavy soiling
- Actuator heads can be repositioned by 4 x 90°

## Data

### Ordering data

Product type description	M3R 330-11Y
Article number (order number)	101161735
EAN (European Article Number)	4030661196855
eCl@ss number, Version 9.0	27-27-06-01

### Certifications

Certificates	cULus
	EAC
	DNV GL

### General data

Product name	M 330 side roller plunger 3R
Standards	EN 60947-5-1
Active principle	mechanical
Slide form	Castor
Enclosure material	Cast iron
Enclosure coating material	painted
Material of the contacts, electrical	Silver
Roller material	Plastic
Gross weight	245.000 g

## General data - Features

Number of openers	1
Number of shutters	1

## Mechanical data

Actuating element	Roller plunger
Mechanical life, minimum	30,000,000 Operations
Actuating force, minimum	17 N
Contact opening	2 x 0.5 mm
Actuating speed, minimum	1 mm/min
Repeat accuracy of switching points	0.02

## Mechanical data - Connection technique

Terminal Connector	Screw connection
Cable section, minimum	1.5 mm <sup>2</sup>
Cable section, maximum	2.5 mm <sup>2</sup>
Note (Cable section)	All indications about the cable section are including the conductor ferrules.
Wire cross-section	13 AWG

## Mechanical data - Dimensions

Height of sensor	103.5 mm
Length of sensor	40 mm
Width of sensor	75.3 mm
Width of Castor	4.6 mm

## Ambient conditions

Protection class	IP 65 to IEC/EN 60529
Ambient temperature, minimum	-30 °C
Ambient temperature, maximum	+90 °C
Resistance to shock	50 g / 6 ms

## Ambient conditions - Insulation value

Rated impulse withstand voltage	4 kV
---------------------------------	------

## Electrical data

Thermal test current	6 A
Utilisation category AC-15	230 VAC
Utilisation category AC-15	2.5 A
Switching element	NO contact, NC contact
Note (Switching element)	galvanically separated contact bridges

Switching principle	Snap switch element
Bounce duration, maximum	43,221 ms
Switchover time, maximum	10 ms

## Ordering code

Product type description:

M(1) 330-11Y-(2)-(3)

(1)

<b>S</b>	Plunger S
<b>2S</b>	Telescopic plunger 2S
<b>R</b>	Roller plunger R
<b>K</b>	Offset roller lever K
<b>3K</b>	Angle roller lever 3K
<b>3S</b>	Side plunger 3S
<b>3R</b>	Side roller plunger 3R
<b>AF</b>	Spring rod lever AF
<b>4D</b>	Fork roller level 4D
<b>8H</b>	Roller lever 8H
<b>7H</b>	Roller lever 7H
<b>10H</b>	Rod lever 10H
<b>H</b>	Roller lever H
<b>4H</b>	Spring rod lever on shaft 4H
<b>2H</b>	Leaf spring lever 2H
<b>3H</b>	Roller lever 3H
<b>9H</b>	Rod lever 9H
<b>6H</b>	Leaf spring lever 6H

(2)

<b>without</b>	without LED switching conditions display
<b>G24</b>	with LED switching conditions display

(3)

<b>AuNi</b>	Gold-nickel alloy contacts
<b>1164</b>	Splined shaft and lever available with 10° tothing
<b>1366</b>	For temperatures up to +160°C

## Pictures

## Product picture (catalogue individual photo)



ID: km330f10


| 697,0 kB | .jpg | 242.358 x 336.55 mm - 687 x 954

Pixel - 72 dpi

| 69,8 kB | .png | 74.083 x 102.658 mm - 210 x 291

Pixel - 72 dpi

## Dimensional drawing basic component



ID: 1m330g01

| 24,6 kB | .cdr |

| 4,0 kB | .png | 74.083 x 51.858 mm - 210 x 147 Pixel

- 72 dpi

| 107,3 kB | .jpg | 352.778 x 247.297 mm - 1000 x 701

Pixel - 72 dpi

## Switch travel diagram



ID: km330s06

| 1,2 kB | .png | 74.083 x 52.564 mm - 210 x 149 Pixel

- 72 dpi


## Diagram



ID: k1o1sk07

| 17,3 kB | .cdr |

## Dimensional drawing actuator



ID: 1m330b10

| 3,5 kB | .png | 74.083 x 51.858 mm - 210 x 147 Pixel

- 72 dpi

| 81,4 kB | .jpg | 352.778 x 247.297 mm - 1000 x 701

Pixel - 72 dpi

K.A. Schmersal GmbH & Co. KG, Möddinghofe 3, D-42279 Wuppertal

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on 11.09.2020 22:46:42