



MJ 461-22Y

- Metal enclosure
- 2 cable entries M 20 x 1.5
- 118 mm x 155 mm x 64 mm (basic component)
- Actuator heads can be repositioned by 4 x 90°

Data

Ordering data

Product type description	MJ 461-22Y
Article number (order number)	101059169
EAN (European Article Number)	4030661035017
eCl@ss number, Version 9.0	27-27-06-01

Certifications

Certificates	EAC DNV GL
--------------	---------------

General data

Product name	461 offset roller lever J
Standards	EN 60947-5-1
Active principle	mechanical
Slide form	Castor
Enclosure material	Grey cast iron, galvanised
Enclosure coating material	painted
Material of the contacts, electrical	Silver
Roller material	Plastic
Gross weight	2240.000 g

General data - Features

Number of openers	2
Number of shutters	2

Mechanical data

Actuating element	Offset roller lever
Mechanical life, minimum	5,000,000 Operations
Actuating angle, from left of switch axis	45 °
Actuating angle, from right of switch axis	30 °
Contact opening	max. 2 x 2.5 mm
Actuating speed, minimum	1 mm/min
Actuating speed, maximum	0.5 m/s
Note (Actuating speed)	Actuating speed with vertical actuating angle to switch axis

Mechanical data - Connection technique

Terminal Connector	Screw connection
Cable section, minimum	1.5 mm ²
Cable section, maximum	2.5 mm ²
Note (Cable section)	All indications about the cable section are including the conductor ferrules.
Wire cross-section	13 AWG

Mechanical data - Dimensions

Height of sensor	235 mm
Length of sensor	64 mm
Width of sensor	118 mm
Width of Castor	9 mm
Diameter of Castor	36 mm

Ambient conditions

Protection class	IP 65 to IEC/EN 60529
Ambient temperature, minimum	-30 °C
Ambient temperature, maximum	+90 °C

Ambient conditions - Insulation value

Rated impulse withstand voltage	4 kV
---------------------------------	------

Electrical data

Thermal test current	16 A
Utilisation category AC-15	230 VAC
Utilisation category AC-15	4 A
Switching element	NO contact / NC contact

Note (Switching element)	with double break
Switching principle	Snap switch element
Bounce duration, maximum	5 ms
Switchover time, maximum	35 ms

Notes

Note (General)	Actuation from the right should be avoided, since this reduces the mechanical life of the position switch.
----------------	--

Pictures

Product picture (catalogue individual photo)



ID: bt441f06

| 30,3 kB | .png | 74.083 x 71.967 mm - 210 x 204
Pixel - 72 dpi

| 228,4 kB | .jpg | 228.6 x 221.897 mm - 648 x 629
Pixel - 72 dpi

Product picture (catalogue individual photo)




ID: kt461f01

| 76,0 kB | .png | 73.731 x 122.061 mm - 209 x 346
Pixel - 72 dpi

| 1,1 MB | .jpg | 352.778 x 582.436 mm - 1000 x 1651
Pixel - 72 dpi

Dimensional drawing basic component




ID: 1t461g01

| 9,2 kB | .png | 74.083 x 51.153 mm - 210 x 145 Pixel
- 72 dpi

| 35,2 kB | .cdr |

| 110,5 kB | .jpg | 352.778 x 243.769 mm - 1000 x 691
Pixel - 72 dpi

Dimensional drawing actuator



ID: 1t422b05

| 100,7 kB | .jpg | 352.778 x 247.297 mm - 1000 x 701
Pixel - 72 dpi
| 10,4 kB | .png | 74.083 x 51.858 mm - 210 x 147
Pixel - 72 dpi

Operating principle



ID: 235rz03

| 131,9 kB | .jpg | 352.778 x 773.642 mm - 1000 x
2193 Pixel - 72 dpi
| 2,7 kB | .png | 74.083 x 162.278 mm - 210 x 460
Pixel - 72 dpi
| 15,5 kB | .cdr |

K.A. Schmersal GmbH & Co. KG, Möddinghofe 3, D-42279 Wuppertal

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on 14.09.2020 17:49:52