



RS656-Z22-G115

- Thermoplastic enclosure
- wire pull and breakage detection
- Protection class IP66, IP67
- Central connection terminal
- Mechanical switching position indication
- two-side operation / wire up to 2 x 100 m

Data

Ordering data

Product type description	RS656-Z22-G115
Article number (order number)	153031645
EAN (European Article Number)	4030661533018
eCl@ss number, version 12.0	27-37-12-01
eCl@ss number, version 11.0	27-37-12-01
eCl@ss number, version 9.0	27-37-12-01
ETIM number, version 7.0	EC002026
ETIM number, version 6.0	EC002026

Approvals - Standards

Certificates	TÜV cULus CCC
--------------	---------------------

General data

Standards	EN 620 EN ISO 13850 EN IEC 60947-5-1 EN IEC 60947-5-5
Enclosure material	thermosetting resin
Material of the contacts, electrical	Silver
Material of the housing cover	thermosetting resin
Length of the wire, maximum	100 m
Gross weight	2,775 g

General data - Features

Indicator lamp	Yes
Number of auxiliary contacts	2
Number of safety contacts	2

Safety classification

Standards	EN ISO 13849-1
Mission time	20 Year(s)

Safety classification - Safety outputs

B _{10D} Normally-closed contact (NC)	100,000 Operations
---	--------------------

Mechanical data

Actuating element	Roller lever N300
Mechanical life, minimum	100,000 Operations
Actuation direction	Each time 75° right-hand side and left-hand side rotation

Mechanical data - Connection technique

Termination	Spring pulley connection
Cable entry	2 x M25 x 1.5
Cable section, minimum	0.5 mm ² , flexible
Cable section, maximum	2.5 mm ² , flexible

Ambient conditions

Degree of protection	IP67 IP66
Ambient temperature, minimum	-40 °C
Ambient temperature, maximum	+70 °C
Protection class	II

Ambient conditions - Insulation values

Rated insulation voltage U_i	300 V
Rated impulse withstand voltage U_{imp}	4 kV
Degree of pollution to IEC/EN 60947-1	3

Electrical data

Thermal test current	6 A
Utilisation category AC-15	230 VAC
Utilisation category AC-15	3 A
Utilisation category DC-13	24 VDC
Utilisation category DC-13	3 A
Switching principle	Snap action

Other data

Note (applications)	Pull-wire emergency stop switches
---------------------	-----------------------------------

Ordering code

Product type description:

RS65(1)-Z22-(2)-(3)

(1)

5 Grey cast iron, painted

6 thermosetting resin

(2)

G024 Indicator lamp 24 VDC, red

G115 Indicator lamp 115 VAC, red

G230 Indicator lamp 230 VAC, red

(3)

without Standard version (without Dupline® input module)

DS With integrated Dupline® input module

Documents

Operating instructions and Declaration of conformity

RS655 / RS656

(1.3 MB, 12/19/2019)

CCC certification

BS655 / BS656 / RS655 / RS656 (2.7 MB, 10/05/2020)

UL Certificate

BS655 / BS656 / RS655 / RS656 (208.8 kB, 03/10/2021)

Brochure

Brochure

(8.4 MB, 03/22/2021)

Pictures

Product picture (catalogue individual photo)




ID: krs65f03

| 285.2 kB | .jpg | 352.778 x 216.958 mm - 1000 x 615 px - 72 dpi

| 25.5 kB | .png | 74.083 x 45.508 mm - 210 x 129 px - 72 dpi

Dimensional drawing basic component




ID: Krs65g01

| 4.4 kB | .png | 74.083 x 53.975 mm - 210 x 153 px - 72 dpi

| 121.8 kB | .jpg | 352.778 x 256.117 mm - 1000 x 726 px - 72 dpi

Dimensional drawing basic component




ID: Krs65g02

| 3.4 kB | .png | 74.083 x 38.453 mm - 210 x 109 px - 72 dpi

| 82.8 kB | .jpg | 352.778 x 183.092 mm - 1000 x 519 px - 72 dpi

Dimensional drawing basic component



ID: Krs65g03

| 4.8 kB | .png | 74.083 x 42.333 mm - 210 x 120 px - 72 dpi

| 131.6 kB | .jpg | 352.778 x 201.436 mm - 1000 x 571 px - 72 dpi

Assembly example



ID: Krs655m05-

| 33.8 kB | .jpg | 352.778 x 35.278 mm - 1000 x 100 px - 72 dpi

System components

Control-Modul



SRB301ST 230V

- Suitable for the signal processing of outputs with contact sensors
- 3 safety contacts, STOP 0
- 1 Signalling output

Accessories



ACC-EBLT-M10-5PCS



ACC-EBLT-M10-RVA-5PCS



ACC-EBLT-M8-5PCS



ACC-EBLT-M8-RVA-5PCS



ACC-RS65X-TS



ACC-TBLE-RVA



ACC-PWR-EBLT-BM8X70-A2



ACC-PWR-EBLT-BM10X40



ACC-PWR-RC-DUPLEX-3MM-NIRO

- for Wire rope Ø 3 mm



S 900

- Smooth adjustment
- Only one tool
- Antiskid
- Time-saving
- Ergonomic
- No risk of injury

ACC-PWR-SKL-A0,16-VA



- Shackle for fixing the wire rope to the eyebolt

ACC-PWR-WT-3MM-NIRO



- for Wire rope Ø 3 mm
- to DIN 6899

ACC-PWR-RC-3MM-NIRO



ACC-PWR-RC-3MM-ZN



- for Wire rope Ø 3 mm

ACC-PWR-TB-M6-2



- For exact adjustment of the tension of the wire rope
- to DIN 1480

ACC-PWR-PLY-S



- To guide the wire rope where the path is not a straight line
- for Wire rope Ø 5 mm