



T2L 035-20Z

- Metal enclosure
- Protection class IP67
- 3 Cable entry M 20 x 1.5
- operating shaft with ball bearings
- 58 mm x 142 mm x 61,5 mm (basic component)
- Actuator head can be repositioned in steps 4 x 90°

Data

Ordering data

Product type description	T2L 035-20Z
Article number (order number)	101056298
EAN (European Article Number)	4030661016269
eCl@ss number, Version 9.0	27-27-06-01

Certifications

Certificates	CCC
	EAC

General data

Product name	035 offset roller lever 2L
Standards	EN 60947-5-1
Active principle	mechanical
Slide form	Castor
Enclosure material	Grey cast iron, galvanised
Enclosure coating material	painted
Material of the contacts, electrical	Silver
Roller material	Metal film
Gross weight	1725.000 g

General data - Features

Number of shutters	2
--------------------	---

Mechanical data

Actuating element	Roller lever
Mechanical life, minimum	10,000,000 Operations
Actuating angle, from left of switch axis	30 °
Actuating angle, from right of switch axis	30 °
Contact opening	2 x 2.5 mm
Actuating speed, minimum	1 mm/min
Actuating speed, maximum	1 m/s
Note (Actuating speed)	Actuating speed with vertical actuating angle to switch axis

Mechanical data - Connection technique

Terminal Connector	Screw connection
Cable section, minimum	1.5 mm ²
Cable section, maximum	2.5 mm ²
Note (Cable section)	All indications about the cable section are including the conductor ferrules.
Wire cross-section	13 AWG

Mechanical data - Dimensions

Width of the actuator	36 mm
Length of the actuator	21 mm
Height of the actuator	73 mm
Width of Castor	8 mm
Diameter of Castor	36 mm

Ambient conditions

Protection class	IP 67 to IEC/EN 60529
Ambient temperature, minimum	-30 °C
Ambient temperature, maximum	+90 °C

Ambient conditions - Insulation value

Rated impulse withstand voltage	6 kV
---------------------------------	------

Electrical data

Thermal test current	10 A
Utilisation category AC-15	400 VAC
Utilisation category AC-15	4 A
Switching element	Normally open contact (NO)
Note (Switching element)	with double break
Switching principle	Creep circuit element

Switching frequency 3,000 /h

Ordering code

Product type description:

(1)2L 035-(2)Z(3)-(4)

(1)

T Slow action

M Snap action

(2)

11 1 NO contacts/1 NC contact

02 2 NC contact

20 2 NO contacts

(3)

UE Slow action with overlapping contacts

H Slow action with staggered contacts

(4)

C Magnetic blow-out

Pictures

Product picture (catalogue individual photo)



ID: k-035f01

| 86,8 kB | .png | 74.083 x 155.928 mm - 210 x 442

Pixel - 72 dpi

| 1,1 MB | .jpg | 352.778 x 742.95 mm - 1000 x 2106

Pixel - 72 dpi

Dimensional drawing basic component

