



## V-SK4P-M12P-S-G-1,5M-BK-2-X-T-4

### Data

#### Ordering data

Product type description	V-SK4P-M12P-S-G-1,5M-BK-2-X-T-4
Article number (order number)	103025136
EAN (European Article Number)	4030661512266
eCl@ss number, version 12.0	27-06-03-11
eCl@ss number, version 11.0	27-06-03-11
eCl@ss number, version 9.0	27-06-03-11
ETIM number, version 7.0	EC001855
ETIM number, version 6.0	EC001855

#### General data

Standards	EN IEC 61076-2-111
Gross weight	221 g

#### General data - Features

Halogen free	Yes (1)
Cable drag chain suitable	Yes (1)
Number of poles	4

Number of cable wires	4
-----------------------	---

### **Mechanical data**

Tightening torque, maximum	1 Nm
----------------------------	------

### **Mechanical data - Connection technique**

Length of cable	1.5 m
Wire cross-section	1.5 mm <sup>2</sup>
Cable diameter	9.6 mm
Bending radius (fixed)	4 x Ø-cable
Bending radius (repeated)	7.5 x Ø-cable
Colour of the Cable mantle	Black
Material of the Cable mantle	PUR

### **Mechanical data - connector side A**

Connector typ	Female connector, M12
Design	straight
Connector coding	T
Connector latching	Screw locking
Material of the gland	Metal, CuZn, nickel-plated
Material of the handle	Plastic, TPU
Colour of the handle	Black

### **Mechanical data - connector side B**

Connector typ	Male connector, M12
Design	straight
Connector coding	T
Connector latching	Screw locking

Material of the gland	Metal, CuZn, nickel-plated
Material of the handle	Plastic, TPU
Colour of the handle	Black

## Ambient conditions

Degree of protection	IP65 IP67 IP68
Ambient temperature, minimum (Connector)	-30 °C
Ambient temperature, maximum (Connector)	+90 °C
Temperature (fixed), minimum	-40 °C
Temperature (fixed), maximum	+80 °C
Temperature (repeated), minimum	-25 °C
Temperature (repeated), maximum	+80 °C

## Electrical data

Thermal test current	12 A
Rated operating voltage	63 V
Operating current	12,000 mA

## Pictures

### Product picture (catalogue individual photo)



ID: k1204f18  
 | 21.4 kB | .png | 74.083 x 53.269 mm - 210 x 151 px - 72 dpi  
 | 199.1 kB | .jpg | 352.778 x 254.353 mm - 1000 x 721 px - 72 dpi  
 | 13.2 kB | .jpg | 112.889 x 81.492 mm - 320 x 231 px - 72 dpi

Schmersal, Inc., 15 Skyline Drive, Hawthorne, NY 10532

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on: 10/19/2022, 3:42 PM