



NO IMAGE
AVAILABLE

VFB-SK8P/4P-M12-S-G-2,5M-BK-2-X-A-4

Data

Ordering data

Product type description	VFB-SK8P/4P-M12-S-G-2,5M-BK-2-X-A-4
Article number (order number)	103032864
EAN (European Article Number)	4030661529868
eCl@ss number, version 12.0	27-06-03-11
eCl@ss number, version 11.0	27-06-03-11
eCl@ss number, version 9.0	27-06-03-11
ETIM number, version 7.0	EC001855
ETIM number, version 6.0	EC001855

General data

Standards	EN IEC 61076-2-101
Gross weight	92 g

General data - Features

Halogen free	Yes (1)
--------------	---------

Cable drag chain suitable	Yes (1)
Number of cable wires	4

Mechanical data

Tightening torque, maximum	1 Nm
----------------------------	------

Mechanical data - Connection technique

Length of cable	2.5 m
Wire cross-section	0.25 mm ²
Cable diameter	4.3 mm
Bending radius (fixed)	5 x Ø-cable
Bending radius (repeated)	10 x Ø-cable
Colour of the Cable mantle	Black
Material of the Cable mantle	PUR

Mechanical data - connector side A

Connector typ	Male connector, M12
Design	straight
Connector coding	A
Connector latching	Screw locking
Material of the gland	Metal, CuZn, nickel-plated
Material of the handle	Plastic, TPU
Colour of the handle	Black
Number of pol, side A	8

Mechanical data - connector side B

Connector typ	Female connector, M12
Design	straight

Connector coding	A
Connector latching	Screw locking
Material of the gland	Metal, CuZn, nickel-plated
Material of the handle	Plastic, TPU
Colour of the handle	Black
Number of pol, side B	4

Ambient conditions

Degree of protection	IP65 IP67 IP68
Ambient temperature, minimum (Connector)	-25 °C
Ambient temperature, maximum (Connector)	+85 °C
Temperature (fixed), minimum	-40 °C
Temperature (fixed), maximum	+90 °C
Temperature (repeated), minimum	-30 °C
Temperature (repeated), maximum	+90 °C
Temperature (drag chain), minimum	-25 °C
Temperature (drag chain), maximum	+60 °C

Electrical data

Thermal test current	2 A
Rated operating voltage	30 V
Operating current	2,000 mA

Pin assignment

PIN 1	Brown
PIN 2	Blue
PIN 3	Black

Pictures

Product picture (catalogue individual photo)



**NO IMAGE
AVAILABLE**

ID: no-pic01

| 98.4 kB | .jpg | 352.778 x 352.778 mm - 1000 x 1000 px - 72 dpi

| 3.3 kB | .png | 74.083 x 74.083 mm - 210 x 210 px - 72 dpi

Schmersal, Inc., 15 Skyline Drive, Hawthorne, NY 10532

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on: 10/19/2022, 3:20 PM