

Fiber Optic Cables

MODEL	GXH500J series	Heat resistance to 350 °C, covered with SS spiral tube	Search ID No.																																						
	Reflective		114																																						
<p>CAD</p> <p style="text-align: right;">The tightening torque for the threaded part should be up to 0.8 N·m.</p>																																									
<p>Applicable amplifier</p> <div style="display: flex; justify-content: space-around;"> <div style="text-align: center;"> <p>F80R SERIES</p> </div> <div style="text-align: center;"> <p>F70 SERIES</p> <p>F71</p> </div> </div>																																									
<p>Detecting distances for individual amplifier models (mm)</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td rowspan="2" style="background-color: #e0f2f1;">F80R</td> <td style="background-color: #e0f2f1;">Long-distance</td> <td style="background-color: #e0f2f1;">135 (130)</td> </tr> <tr> <td style="background-color: #e0f2f1;">High-speed</td> <td style="background-color: #e0f2f1;">75 (70)</td> </tr> <tr> <td colspan="2" style="background-color: #e0f2f1;">F70R/AR</td> <td style="background-color: #e0f2f1;">75 (70)</td> </tr> <tr> <td colspan="2" style="background-color: #e0f2f1;">F71R</td> <td style="background-color: #e0f2f1;">45 (40)</td> </tr> </table> <p style="text-align: right; font-size: small;">Values in parentheses show detecting distances for combinations with GXL520J.</p>				F80R	Long-distance	135 (130)	High-speed	75 (70)	F70R/AR		75 (70)	F71R		45 (40)																											
F80R	Long-distance	135 (130)																																							
	High-speed	75 (70)																																							
F70R/AR		75 (70)																																							
F71R		45 (40)																																							
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>Model</th> <th>GXH505J</th> <th>GXH510J</th> <th>GXH520J</th> </tr> </thead> <tbody> <tr> <td>Fiber optic cable length(m)</td> <td>0.5</td> <td>1</td> <td>2</td> </tr> <tr> <td>Ambient temperature</td> <td colspan="3" style="text-align: center;">- 60 ~ + 350 °C</td> </tr> <tr> <td rowspan="2">Material</td> <td>Covering</td> <td colspan="2" style="text-align: center;">SUS spiral</td> </tr> <tr> <td>Core</td> <td colspan="2" style="text-align: center;">Glass</td> </tr> <tr> <td rowspan="2">Diameter</td> <td>Cable</td> <td colspan="2" style="text-align: center;">2.8</td> </tr> <tr> <td>Core</td> <td colspan="2" style="text-align: center;">Binding diameter: 1.1 (2-section)</td> </tr> <tr> <td>Allowable bending radius</td> <td colspan="3" style="text-align: center;">R25</td> </tr> <tr> <td>Standard detection object diameter</td> <td colspan="3" style="text-align: center;">100 x 100mm white drawing paper (with F70R)</td> </tr> <tr> <td>Smallest allowable detection object diameter</td> <td colspan="3" style="text-align: center;">φ 0.015 (excluding F71R)</td> </tr> </tbody> </table>				Model	GXH505J	GXH510J	GXH520J	Fiber optic cable length(m)	0.5	1	2	Ambient temperature	- 60 ~ + 350 °C			Material	Covering	SUS spiral		Core	Glass		Diameter	Cable	2.8		Core	Binding diameter: 1.1 (2-section)		Allowable bending radius	R25			Standard detection object diameter	100 x 100mm white drawing paper (with F70R)			Smallest allowable detection object diameter	φ 0.015 (excluding F71R)		
Model	GXH505J	GXH510J	GXH520J																																						
Fiber optic cable length(m)	0.5	1	2																																						
Ambient temperature	- 60 ~ + 350 °C																																								
Material	Covering	SUS spiral																																							
	Core	Glass																																							
Diameter	Cable	2.8																																							
	Core	Binding diameter: 1.1 (2-section)																																							
Allowable bending radius	R25																																								
Standard detection object diameter	100 x 100mm white drawing paper (with F70R)																																								
Smallest allowable detection object diameter	φ 0.015 (excluding F71R)																																								

MODEL	GX500J series	Heat resistance to 230 °C, M4 screw	Search ID No.																																						
	Reflective		115																																						
<p>CAD</p> <p style="text-align: right;">The tightening torque for the threaded part should be up to 0.8 N·m.</p>																																									
<p>Applicable amplifier</p> <div style="display: flex; justify-content: space-around;"> <div style="text-align: center;"> <p>F80R SERIES</p> </div> <div style="text-align: center;"> <p>F70 SERIES</p> <p>F71</p> </div> </div>																																									
<p>Detecting distances for individual amplifier models (mm)</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td rowspan="2" style="background-color: #e0f2f1;">F80R</td> <td style="background-color: #e0f2f1;">Long-distance</td> <td style="background-color: #e0f2f1;">135 (130)</td> </tr> <tr> <td style="background-color: #e0f2f1;">High-speed</td> <td style="background-color: #e0f2f1;">75 (70)</td> </tr> <tr> <td colspan="2" style="background-color: #e0f2f1;">F70R/AR</td> <td style="background-color: #e0f2f1;">75 (70)</td> </tr> <tr> <td colspan="2" style="background-color: #e0f2f1;">F71R</td> <td style="background-color: #e0f2f1;">45 (40)</td> </tr> </table> <p style="text-align: right; font-size: small;">Values in parentheses show detecting distances for combinations with GX510J/520J.</p>				F80R	Long-distance	135 (130)	High-speed	75 (70)	F70R/AR		75 (70)	F71R		45 (40)																											
F80R	Long-distance	135 (130)																																							
	High-speed	75 (70)																																							
F70R/AR		75 (70)																																							
F71R		45 (40)																																							
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>Model</th> <th>GX505J</th> <th>GX510J</th> <th>GX520J</th> </tr> </thead> <tbody> <tr> <td>Fiber optic cable length(m)</td> <td>0.5</td> <td>1</td> <td>2</td> </tr> <tr> <td>Ambient temperature</td> <td colspan="3" style="text-align: center;">Tip: - 60 ~ +230 °C / Covering: 200 °C</td> </tr> <tr> <td rowspan="2">Material</td> <td>Covering</td> <td colspan="2" style="text-align: center;">Silicon tube</td> </tr> <tr> <td>Core</td> <td colspan="2" style="text-align: center;">Glass</td> </tr> <tr> <td rowspan="2">Diameter</td> <td>Cable</td> <td colspan="2" style="text-align: center;">2.8</td> </tr> <tr> <td>Core</td> <td colspan="2" style="text-align: center;">Binding diameter: 1.1 (2-section)</td> </tr> <tr> <td>Allowable bending radius</td> <td colspan="3" style="text-align: center;">R25</td> </tr> <tr> <td>Standard detection object diameter</td> <td colspan="3" style="text-align: center;">100 x 100mm white drawing paper (with F70R)</td> </tr> <tr> <td>Smallest allowable detection object diameter</td> <td colspan="3" style="text-align: center;">φ 0.015 (excluding F71R)</td> </tr> </tbody> </table>				Model	GX505J	GX510J	GX520J	Fiber optic cable length(m)	0.5	1	2	Ambient temperature	Tip: - 60 ~ +230 °C / Covering: 200 °C			Material	Covering	Silicon tube		Core	Glass		Diameter	Cable	2.8		Core	Binding diameter: 1.1 (2-section)		Allowable bending radius	R25			Standard detection object diameter	100 x 100mm white drawing paper (with F70R)			Smallest allowable detection object diameter	φ 0.015 (excluding F71R)		
Model	GX505J	GX510J	GX520J																																						
Fiber optic cable length(m)	0.5	1	2																																						
Ambient temperature	Tip: - 60 ~ +230 °C / Covering: 200 °C																																								
Material	Covering	Silicon tube																																							
	Core	Glass																																							
Diameter	Cable	2.8																																							
	Core	Binding diameter: 1.1 (2-section)																																							
Allowable bending radius	R25																																								
Standard detection object diameter	100 x 100mm white drawing paper (with F70R)																																								
Smallest allowable detection object diameter	φ 0.015 (excluding F71R)																																								