

TECO Westinghouse

ISSUED 9/18/2020	PERFORMANCE DATA 3-PHASE PERMANENT MAGNET MOTOR	ENCLOSURE TEFC
TYPE DVEM		CATALOG# PM0024C

NAMEPLATE INFORMATION

OUTPUT		POLE	FRAME SIZE	VOLTAGE	HZ	RATED AMBIENT	INS. CLASS	TIME RATING	SERVICE FACTOR
HP	KW								
2	1.5	6	145TC	230/460	90	40°C	F	CONT.	1

VARIABLE FREQUENCY DRIVE SERVICE

VARIABLE TORQUE				OHMS/PHASE EQUIVALENT WYE CIRCUIT (AT RATED OPERATING TEMPERATURE 25°C)			
HZ	HP	RPM	TORQUE (lb-ft)	RESIST.	Ld	Lq	BEMF
9~90	0.12~2	180~1800	3.52~5.90	3.574 Ω	15.04 mH	26.63 mH	169 mV/rpm

CONSTANT TORQUE				CONSTANT HORSEPOWER			
HZ	HP	RPM	TORQUE (lb-ft)	HZ	HP	RPM	TORQUE (lb-ft)
60~90	1.34~2	1200~1800	5.90	90~135	2	1800~2700	5.90~3.91

TYPICAL PERFORMANCE

FULL LOAD RPM	EFFICIENCY			POWER FACTOR			SOUND PRESSURE LEVEL @ 3 FT Db(A)
	FULL LOAD %	3/4 LOAD %	1/2 LOAD %	FULL LOAD %	3/4 LOAD %	1/2 LOAD %	
1800	88.2	86.2	81.8	99.2	99.6	99.8	55

CURRENTS				TORQUE	INERTIA
NO LOAD 230V (A)	NO LOAD 460V (A)	FULL LOAD 230V (A)	FULL LOAD 460V (A)	FULL LOAD (lb-ft)	ROTOR WR2 (lb-ft ²)
1.40	0.70	6.00	3.00	5.90	0.079

APPROVED:	M. PRATER	DRAWING NO.	31057PM0024C	REVISION:	0
-----------	------------------	-------------	---------------------	-----------	----------