

TECO Westinghouse

ISSUED 9/18/2020	PERFORMANCE DATA 3-PHASE PERMANENT MAGNET MOTOR	ENCLOSURE TEFC
TYPE DVEM		CATALOG# PM0204C

NAMEPLATE INFORMATION

OUTPUT		POLE	FRAME SIZE	VOLTAGE	HZ	RATED AMBIENT	INS. CLASS	TIME RATING	SERVICE FACTOR
HP	KW								
20	15	6	256TC	230/460	90	40°C	F	CONT.	1

VARIABLE FREQUENCY DRIVE SERVICE

VARIABLE TORQUE				OHMS/PHASE EQUIVALENT WYE CIRCUIT (AT RATED OPERATING TEMPERATURE 25°C)			
HZ	HP	RPM	TORQUE (lb-ft)	RESIST.	Ld	Lq	BEMF
9~90	1.20~20	180~1800	35.1~58.7	0.304 Ω	4.76 mH	9.74 mH	181 mV/rpm

CONSTANT TORQUE				CONSTANT HORSEPOWER			
HZ	HP	RPM	TORQUE (lb-ft)	HZ	HP	RPM	TORQUE (lb-ft)
60~90	13.37~20	1200~1800	58.7	90~135	20	1800~2700	58.7~39.1

TYPICAL PERFORMANCE

FULL LOAD RPM	EFFICIENCY			POWER FACTOR			SOUND PRESSURE LEVEL @ 3 FT Db(A)
	FULL LOAD %	3/4 LOAD %	1/2 LOAD %	FULL LOAD %	3/4 LOAD %	1/2 LOAD %	
1800	93.9	93.9	93.8	93.6	96.6	98.6	70

CURRENTS				TORQUE	INERTIA
NO LOAD 230V (A)	NO LOAD 460V (A)	FULL LOAD 230V (A)	FULL LOAD 460V (A)	FULL LOAD (lb-ft)	ROTOR WR2 (lb-ft ²)
1.60	0.80	56.00	28.00	58.7	0.754

APPROVED:	M. PRATER	DRAWING NO.	31057PM0204C	REVISION:	0
-----------	------------------	-------------	---------------------	-----------	----------