


# DATASHEET

## Contactors



### Main Features

Reference	: CWB
Product code	: 15477393
Rated current Ie AC-3 (Ue ≤ 440 V)	: 110 A
Main contacts (power)	: 3 NO
Auxiliary contacts	: 1 NO + 1 NC
Control voltage	: 24-60V 50/60Hz-DC
Type of terminal	: Screw

### Basic data

Rated utilization voltage Ue	
- IEC / UL	: 1000 V / 600 V
Isolation voltage Ui (pollution degree 3)	
- IEC / UL	: 1000 V / 600 V
Rated impulse withstand voltage Uimp	: 8 kV
- Frequency limits [1]	: 25 Hz ... 400 Hz
- Mechanical lifespan	
AC-operated contactor	: 6 million
DC-operated contactor	: 6 million
Electrical lifespan - Ie AC3	: 1.1 million
Number of coil terminals (AC Coil)	
AC coil contactors	: 2
- DC coil contactors	: 2
Resistance to vibration (IEC 60068-2-6)	
opened contactor	: 4 g
closed contactor	: 4 g
Resistance to mechanical shock (½ sinusoid = 11ms)	
opened contactor	: 10 g
closed contactor	: 15 g
Installation	: DIN 35 mm (EN 50022)
Degree of protection (IEC 60529)	
Main circuit	: IP10
Control circuit	: IP20

### Alternating current - control circuit

Isolation voltage Ui (pollution degree 3)		: 1000 V / 600 V
- IEC / UL		
Standard voltages for 50/60 Hz		: 24...500 V
Command circuit operation limits		
- control circuit 60 Hz	- pick up	: 0.8...1.1xUs
	- drop out	: 0.1...0.6xUs
- control circuit 50 Hz	- pick up	: 0.8...1.1xUs
	- drop out	: 0.1...0.6xUs
- Average coil consumption		
- operating at 60 Hz	- closed magnetic circuit	: Not available
	- power factor (cos φ)	: Not available
	- Thermal power dissipated	: 2,3 W
	- closing the magnetic circuit	: Not available
- operating at 50 Hz	- closed magnetic circuit	: Not available
	- power factor (cos φ)	: Not available
	- Thermal power dissipated	: Not available
	- closing the magnetic circuit	: Not available
Average time of operation		
- closing the NO contacts		: 32...48 ms
- opening the NO contacts		: 30...55 ms

### Direct current - command circuit

- IEC / UL		
Standard voltages		: 24...500 V
Command circuit operation limits		
- pick up		: 0.8...1.1xUs
- drop out		: 0.1...0.6xUs
Average consumption		
- closed magnetic circuit		: 2...5 W
- closing the magnetic circuit		: 180...220 W
Thermal power dissipated		: 2...5 W
Average time of operation		
- closing the NO contacts		: 32...48 ms
- opening the NO contacts		: 30...55 ms

### Main contacts (power)

Rated utilization current Ie	
- AC-3 (Ue ≤ 440 V)	: 110 A

# DATASHEET

## Contactors



- AC-4 (Ue ≤ 440 V)	: 58 A
- AC-1 (θ ≤ 55 °C, Ue ≤ 690 V)	: 151 A
Rated utilization voltage Ue	
- IEC / UL	: 1000 V / 600 V
Number of main contacts	: 3 NO
Establishment capacity (IEC 60947)	: 1200 A
Breaking capacity (IEC/EN 60947)	
- Ue≤400V	: 1200 A
- Ue=500V	: 1000 A
- Ue=690V	: 765 A
Temporary permissible current (without previously current conduction during 15 min at θ ≤ 40 °C)	
- 1 sec	: 1350 A
- 10 sec	: 780 A
- 10 sec	: 780 A
- 1 min	:
- 10 min	: 150 A
Protection against short circuit of the contacts main fuse (gL/gG)	
- @600V - UL/CSA	: 8 kA
- type 1 coordination	: 250 A
- type 2 coordination	: Not available
Average power dissipated per pole	
AC-1 (θ ≤ 55 °C, Ue ≤ 690 V)	: 17 W
AC-3 (Ue ≤ 440 V)	: 9 W
<b>Utilization category AC-3</b>	
Rated current Ie (θ ≤ 55 °C)	
- Ue ≤ 440V	: 110 A
- Ue ≤ 500V	: 97 A
- Ue ≤ 690V	: 70 A
Maximum percentage (600 ops./h)	: 100 %

Orientative values of power (IEC)-three-phase induction motors (50/60 Hz)-IV poles-1800 rpm		
Voltage	kW	cv or HP
220 / 240 V	30 kW	40 cv
380 / 400 V	55 kW	75 cv
415 / 440 V	55 kW	75 cv
500 V	55 kW	75 cv
660 / 690 V	55 kW	75 cv

Orientative values of power (UL)		
Voltage	1 Phase	3 Phase
120 V	10	Not available
200 V	Not applicable	30
208 V	Not available	Not available
240 V	20	40
480 V	Not available	75
600 V	Not available	75

### Utilization category AC-4

Rated current Ie (θ ≤ 55 °C)	
- Ue ≤ 440V	: 58 A
- Ue ≤ 500V	: 51 A
- Ue ≤ 690V	: 37 A

Orientative values of power (IEC)-three-phase induction motors (50/60 Hz)-IV poles-1800 rpm		
Voltage	kW	cv or HP
220 / 240 V	16.5 kW	22 HP
380 / 400 V	28 kW	38 HP
415 / 440 V	33 kW	44 HP
500 V	30 kW	40 HP
660 / 690 V	30 kW	40 HP

### Utilization category AC-1 (3 P/NA)

Maximum percentage (600 ops./h)	: 1
---------------------------------	-----

Maximum power operation θ ≤ 55°C (three resistors)	
Voltage	Power
220 / 240 V	57 kW
380 / 400 V	99 kW
415 / 440 V	114 kW
500 V	130 kW
660 / 690 V	179 kW

### Auxiliary contacts

Standards compliance	: IEC 600947-5-1
Insulation voltage Ui	
- IEC / UL	: 1000 V / 600 V

# DATASHEET

## Contactors



Rated utilization voltage  $U_e$   
 - IEC / UL : 690 V / 690 V  
 Conventional thermal current  $I_{th}$  ( $\theta \leq 55^\circ\text{C}$ ) : 10 A  
 Rated current  $I_e$  - IEC 60947-5-1/AC-15  
 - 220 / 240 V : 10 A  
 - 380 / 440 V : 4 A  
 - 500 V : 2,5 A  
 - 660 / 690 V : 1,5 A  
 Rated current  $I_e$  - IEC 60947-5-1/DC-13  
 - 24 V : 4 A  
 - 48 V : 2 A  
 - 110 V : 0,7 A  
 - 220 V : 0,3 A  
 - 440 V : 0,15 A  
 Establishment capacity - (AC-15 and  $U_e \leq 690\text{V}$  50/60Hz) : 10 x  $I_e$   
 Interruption capacity - (AC-15 and  $U_e \leq 400\text{V}$  50/60Hz) : 1 x  $I_e$   
 Protection against short circuit of the contacts main fuse (gL/gG) : 10 A  
 Control circuit reliability : 17/5 V/mA  
 Electrical lifespan : 1 Million  
 Mechanical lifespan : 6 million  
 Non-overlapping time between NO and NC contacts : 1,5 ms  
 Impedance per pole : 2,5 m $\Omega$

### Connection

Main contacts  
 Type of the screw : M8 internal hexagonal  
 Section of the conductors

Type of the conductor	Section (IEC)	Section (UL)
Rigid cable	1 x Not available	1 x
	2 x Not available	2 x
Flexible cable without terminal	1 x Not available	1 x
	2 x Not available	2 x
Flexible cable with terminal	1 x Not contain	1 x
	2 x Not contain	2 x

Tightening torque (IEC/UL) : 6 Nm / 53 lb.in  
 Control circuit  
 Type of the screw : M3,5 Flat/Phillips  
 Section of the conductors

Type of the conductor	Section (IEC)	Section (UL)
Rigid cable	1 x 1...4 mm <sup>2</sup>	1 x
	2 x 1...4 mm <sup>2</sup>	2 x
Flexible cable without terminal	1 x 1...4 mm <sup>2</sup>	1 x
	2 x 1...4 mm <sup>2</sup>	2 x
Flexible cable with terminal	1 x 1...4 mm <sup>2</sup>	1 x
	2 x 1...2,5 mm <sup>2</sup>	2 x

Tightening torque (IEC/UL) : 1 Nm / 8.8 lb.in

### Direct current application

Utilization category DC-1 (L/R  $\leq$  1 ms)

Voltage	Rated utilization current ( $I_e$ )			
	Pole(s) in series			
	1	2	3	4
$U_e \leq 24\text{V}$	151 A	151 A	151 A	Not available
$U_e \leq 48\text{V}$	151 A	151 A	151 A	Not available
$U_e \leq 60\text{V}$	151 A	151 A	151 A	Not available
$U_e \leq 125\text{V}$	21 A	151 A	151 A	Not available
$U_e \leq 220\text{V}$	2.7 A	14 A	69 A	Not available
$U_e \leq 440\text{V}$	1.4 A	2.7 A	14 A	Not available
$U_e \leq 600\text{V}$	Not available	1,4 A	2.7 A	Not available

Utilization category DC-3 (L/R  $\leq$  2.5 ms)

Voltage	Rated utilization current ( $I_e$ )			
	Pole(s) in series			
	1	2	3	4
$U_e \leq 24\text{V}$	137 A	137 A	137 A	Not available
$U_e \leq 48\text{V}$	00018	137 A	137 A	Not available
$U_e \leq 60\text{V}$	137 A	137 A	137 A	Not available
$U_e \leq 125\text{V}$	6.9 A	110 A	137 A	Not available
$U_e \leq 220\text{V}$	1,4 A	6,9 A	62 A	Not available
$U_e \leq 440\text{V}$	Not available	1.4 A	6.9 A	Not available
$U_e \leq 600\text{V}$	Not available	Not available	1.3 A	Not available

# DATASHEET

## Contactors



Operation category DC-5 (L/R ≤ 15ms)

Voltage	Rated utilization current (Ie)			
	Pole(s) in series			
	1	2	3	4
Ue ≤ 24V	145 A	145 A	145 A	Not available
Ue ≤ 48V	145 A	145 A	145 A	Not available
Ue ≤ 60V	145 A	145 A	145 A	Not available
Ue ≤ 125V	7.3 A	116 A	145 A	Not available
Ue ≤ 220V	Not available	5.8 A	59 A	Not available
Ue ≤ 440V	Not available	Not available	4.4 A	Not available
Ue ≤ 600V	Not available	Not available	Not available	Not available

### Ambient temperature

Operation : -25 °C ... +55 °C  
 Storage : -55 °C ... +80 °C  
 Maximum altitude with no change of rated values [2] : 3000 m

### Dimensions

Height : 149 mm (5.87 in)  
 Width : 72 mm  
 Depth : 144.5 mm (5.688 in)  
 Weight : 1.6 kg

### Standards

IEC 60947-1  
 UL 508

### Certifications

CE, UL and EAC

### Notes

- 1) Values above 60 Hz should have current reduction;
- 2) For altitudes of 3000 to 4000 m (0.90 x 0.80 x Ie and Ui) and from 4000 to 5000 m (0.80 x 0.75 x Ie and Ui).