



### Main Features

Reference	: CWM
Product code	: 11747363
Rated current Ie AC-3 (Ue ≤ 440 V)	: 400 A
Main contacts (power)	: 3 NO
Auxiliary contacts	: 2 NO + 2 NC
Control voltage	: 100-240V 50/60Hz/100-220V DC
Type of terminal	: Screw

### Basic data

Rated utilization voltage Ue	
- IEC / UL	: 690 V / 600 V
Isolation voltage Ui (pollution degree 3)	
- IEC / UL	: 1000 V / 600 V
Rated impulse withstand voltage Uimp	: 8 kV
- Frequency limits [1]	: 50 Hz ... 60 Hz
- Mechanical lifespan	
AC-operated contactor	: 5 million
DC-operated contactor	: 5 million
Electrical lifespan - Ie AC3	: 0.5 million
Number of coil terminals (AC Coil)	
AC coil contactors	: 2
- DC coil contactors	: 2
Resistance to vibration (IEC 60068-2-6)	
opened contactor	: 2 g
closed contactor	: 4 g
Resistance to mechanical shock (½ sinusoid = 11ms)	
opened contactor	: 8 g
closed contactor	: 10 g
Installation	: Not available
Degree of protection (IEC 60529)	
Main circuit	: IP00
Control circuit	: IP20

### Alternating current - control circuit

Isolation voltage Ui (pollution degree 3)		: 1000 V / 600 V
- IEC / UL		
Standard voltages for 50/60 Hz		:
Command circuit operation limits		
- control circuit 60 Hz	- pick up	:
	- drop out	:
- control circuit 50 Hz	- pick up	:
	- drop out	:
- Average coil consumption		
- operating at 60 Hz	- closed magnetic circuit	:
	- power factor (cos φ)	:
	- Thermal power dissipated	:
	- closing the magnetic circuit	:
- operating at 50 Hz	- closed magnetic circuit	:
	- power factor (cos φ)	:
	- Thermal power dissipated	:
	- closing the magnetic circuit	:
Average time of operation		
- closing the NO contacts		:
- opening the NO contacts		:

### Direct current - command circuit

- IEC / UL	
Standard voltages	: 100...220 V
Command circuit operation limits	
- pick up	: 0,85xUs
- drop out	: 0,3...0,6xUs
Average consumption	
- closed magnetic circuit	: Not available
- closing the magnetic circuit	: Not available
Thermal power dissipated	: 5 W
Average time of operation	
- closing the NO contacts	: 55 ms
- opening the NO contacts	: 55 ms

### Main contacts (power)

Rated utilization current Ie	
- AC-3 (Ue ≤ 440 V)	: 400 A

# DATASHEET

## Contactors



- AC-4 (Ue ≤ 440 V)	: 300 A
- AC-1 (θ ≤ 55 °C, Ue ≤ 690 V)	: 520 A
Rated utilization voltage Ue	
- IEC / UL	: 690 V / 600 V
Number of main contacts	: 3 NO
Establishment capacity (IEC 60947)	: 4000 A
Breaking capacity (IEC/EN 60947)	
- Ue≤400V	: 4000 A
- Ue=500V	: Not available
- Ue=690V	: Not available
Temporary permissible current (without previously current conduction during 15 min at θ ≤ 40 °C)	
- 1 sec	: Not available
- 1 sec	: Not available
- 1 sec	: Not available
- 1 min	:
- 10 min	: Not available
Protection against short circuit of the contacts main fuse (gL/gG)	
- @600V - UL/CSA	: 10 kA
- type 1 coordination	: Not available
- type 2 coordination	: 630 A
Average power dissipated per pole	
AC-1 (θ ≤ 55 °C, Ue ≤ 690 V)	: Not available
AC-3 (Ue ≤ 440 V)	: Not available
<b>Utilization category AC-3</b>	
Rated current Ie (θ ≤ 55 °C)	
- Ue ≤ 440V	: 400 A
- Ue ≤ 500V	: 350 A
- Ue ≤ 690V	: 300 A
Maximum percentage (600 ops./h)	: Not available

Orientative values of power (IEC)-three-phase induction motors (50/60 Hz)-IV poles-1800 rpm		
Voltage	kW	cv or HP
220 / 240 V	110 kW	150 cv
380 / 400 V	220 kW	300 cv
415 / 440 V	220 kW	300 cv
500 V	220 kW	300 cv
660 / 690 V	260 kW	350 cv

Orientative values of power (UL)		
Voltage	1 Phase	3 Phase
120 V	Not available	Not available
200 V	Not applicable	Not available
208 V	Not available	Not available
240 V	Not available	Not available
480 V	Not available	Not available
600 V	Not available	Not available

### Utilization category AC-4

Rated current Ie (θ ≤ 55 °C)	
- Ue ≤ 440V	: 300 A
- Ue ≤ 500V	: Not available
- Ue ≤ 690V	: Not available

Orientative values of power (IEC)-three-phase induction motors (50/60 Hz)-IV poles-1800 rpm		
Voltage	kW	cv or HP
220 / 240 V	75 kW	100 HP
380 / 400 V	150 kW	200 HP
415 / 440 V	150 kW	200 HP
500 V	Not available	Not available
660 / 690 V	Not available	Not available

### Utilization category AC-1 (3 P/NA)

Maximum percentage (600 ops./h)	: 1
---------------------------------	-----

Maximum power operation θ ≤ 55°C (three resistors)	
Voltage	Power
220 / 240 V	171 kW
380 / 400 V	296 kW
415 / 440 V	296 kW
500 V	390 kW
660 / 690 V	538 kW

### Auxiliary contacts

Standards compliance	: Not available
Insulation voltage Ui	
- IEC / UL	: Not available / Not available

# DATASHEET

## Contactors



Rated utilization voltage  $U_e$   
 - IEC / UL : Not available / Not available  
 Conventional thermal current  $I_{th}$  ( $\theta \leq 55^\circ\text{C}$ ) : Not available  
 Rated current  $I_e$  - IEC 60947-5-1/AC-15  
 - 220 / 240 V : Not available  
 - 380 / 440 V : Not available  
 - 500 V : Not available  
 - 660 / 690 V : Not available  
 Rated current  $I_e$  - IEC 60947-5-1/DC-13  
 - 24 V : Not available  
 - 48 V : Not available  
 - 110 V : Not available  
 - 220 V : Not available  
 - 440 V : Not available  
 Establishment capacity - (AC-15 and  $U_e \leq 690\text{V}$  50/60Hz) : Not available  
 Interruption capacity - (AC-15 and  $U_e \leq 400\text{V}$  50/60Hz) : Not available  
 Protection against short circuit of the contacts main fuse (gL/gG) : Not available  
 Control circuit reliability : Not available  
 Electrical lifespan : Not available  
 Mechanical lifespan : Not available  
 Non-overlapping time between NO and NC contacts : Not available  
 Impedance per pole : Not available

### Connection

Main contacts  
 Type of the screw : M12 hexagonal  
 Section of the conductors

Type of the conductor	Section (IEC)	Section (UL)
Rigid cable	1 x Not available	1 x
	2 x Not available	2 x
Flexible cable without terminal	1 x Not available	1 x
	2 x Not contain	2 x
Flexible cable with terminal	1 x Not contain	1 x
	2 x Not contain	2 x

Tightening torque (IEC/UL) : 22.6 Nm / Not contain  
 Control circuit  
 Type of the screw : M4 Flat/Phillips  
 Section of the conductors

Type of the conductor	Section (IEC)	Section (UL)
Rigid cable	1 x Not available	1 x
	2 x 1...2,5 mm <sup>2</sup>	2 x
Flexible cable without terminal	1 x Not contain	1 x
	2 x 1...2,5 mm <sup>2</sup>	2 x
Flexible cable with terminal	1 x Not contain	1 x
	2 x 1...2,5 mm <sup>2</sup>	2 x

Tightening torque (IEC/UL) : 2,3 Nm / Not available

### Direct current application

Utilization category DC-1 ( $L/R \leq 1$  ms)

Voltage	Rated utilization current ( $I_e$ )			
	Pole(s) in series			
	1	2	3	4
$U_e \leq 24\text{V}$	430 A	430 A	430 A	Not available
$U_e \leq 48\text{V}$	430 A	430 A	430 A	Not available
$U_e \leq 60\text{V}$	Not available	Not available	Not available	Not available
$U_e \leq 125\text{V}$	Not available	Not available	Not available	Not available
$U_e \leq 220\text{V}$	Not available	350 A	430 A	Not available
$U_e \leq 440\text{V}$	Not available	Not available	Not available	Not available
$U_e \leq 600\text{V}$	Not available	Not available	Not available	Not available

Utilization category DC-3 ( $L/R \leq 2.5$  ms)

Voltage	Rated utilization current ( $I_e$ )			
	Pole(s) in series			
	1	2	3	4
$U_e \leq 24\text{V}$	Not available	Not available	Not available	Not available
$U_e \leq 48\text{V}$	Not available	Not available	Not available	Not available
$U_e \leq 60\text{V}$	Not available	Not available	Not available	Not available
$U_e \leq 125\text{V}$	Not available	Not available	Not available	Not available
$U_e \leq 220\text{V}$	Not available	Not available	Not available	Not available
$U_e \leq 440\text{V}$	Not available	Not available	Not available	Not available
$U_e \leq 600\text{V}$	Not available	Not available	Not available	Not available

# DATASHEET

## Contactors



Operation category DC-5 (L/R ≤ 15ms)

Voltage	Rated utilization current (Ie)			
	Pole(s) in series			
	1	2	3	4
Ue ≤ 24V	430 A	430 A	430 A	Not available
Ue ≤ 48V	Not available	Not available	Not available	Not available
Ue ≤ 60V	Not available	Not available	Not available	Not available
Ue ≤ 125V	Not available	Not available	Not available	Not available
Ue ≤ 220V	Not available	310 A	350 A	Not available
Ue ≤ 440V	Not available	Not available	Not available	Not available
Ue ≤ 600V	Not available	Not available	Not available	Not available

### Ambient temperature

Operation : -10 °C ... +40 °C  
 Storage : -30 °C ... +65 °C  
 Maximum altitude with no change of rated values [2] : 3000 m

### Dimensions

Height : 243 mm (9.57 in)  
 Width : 209 mm (8.23 in)  
 Depth : 200,7 mm (7.90 in)  
 Weight : 11.667 kg

### Standards

IEC 60947-1  
 UL 508

### Certifications

EAC

### Notes

- 1) Values above 60 Hz should have current reduction;
- 2) For altitudes of 3000 to 4000 m (0.90 x 0.80 x Ie and Ui) and from 4000 to 5000 m (0.80 x 0.75 x Ie and Ui).

