

Permanent Light 216 / Bulb

Bulb 7W BA15D 24V



Part No.: 955.015.35



| MECHANICAL DATA | | |
|-----------------------|--------|--|
| Height | 54 mm | |
| Diameter | 16 mm | |
| Housing colour | Silver | |
| Weight with packaging | 9 g | |
| Product weight | 9 g | |

| ELECTRICAL DATA | | |
|-----------------------------|----------|--|
| Operating voltage | 24V | |
| Operating voltage frequency | 50Hz | |
| Operating voltage tolerance | +/- 10% | |
| Rated operational voltage | 24 VDC | |
| Rated operational current | 292 mA | |
| Rated inrush current | 2.920 mA | |
| Power illuminant | 7 W | |

| OPTICAL DATA | |
|---------------------|-------|
| Lamp fitting/socket | BA15d |

| APPROVAL DATA | | |
|------------------------------|-----|--|
| Conforms with CE | Yes | |
| WEEE | No | |
| Conforms with ATEX-directive | No | |
| Conforms with CCC | No | |
| Conforms with FCC | No | |
| Conforms with IC | No | |
| EAC certificate available | No | |
| Conforms with AS-I | No | |
| ICAO Certification | No | |
| Conforms with DNV | No | |
| Conforms with RoHS CN | No | |

For additional installation and mounting information, refer to the appropriate user guide at www.werma.com. This printed copy is for information only and is subject to alteration.